



Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BUYER: Hill, Lisa
 PHONE #: 401-222-2142

CREATION DATE : 02-OCT-06
 BID NUMBER: 7002448
 TITLE: EXMARK LAZER MOWER

 BID CLOSING DATE AND TIME:
 23-OCT-2006 11:30:00

**B
I
L
L

T
O**
 URI ACCOUNTS PAYABLE
 CARLOTTI ADMINISTRATION BLDG
 75 LOWER COLLEGE ROAD, SUITE 1
 KINGSTON, RI 02881
 US

**S
H
I
P

T
O**
 URI CENTRAL RECEIVING
 ATTN: SEE BELOW
 PLAINS RD
 KINGSTON, RI 02881
 US

Requisition Number: 1011551

Line	Description	Quantity	Unit	Unit Price	Total
1	NO SUBSTITUTION TO MAKE OR MODEL Exmark LZ27LKA6045 Lazer Mower in accordance with the attached specifications. Price offered must be net of trade-in of one (1) Howard Price Blazer Model 360EZ, Serial Number 260-234, 25 HP Kohler URI Facilities Services 523 Plains Road, Sherman Bldg. Attn: Dave Bascom (401) 874-5515 Less Trade-in of one (1) Howard Price Blazer: Model 360EZ, Serial Number 260-234, 25HP Kohler	1	Each		
2	Ultra Vac 3 bag collection system, installed on the above. URI Facilities Services 523 Plains Road, Sherman Bldg. Attn: Dave Bascom (401) 874-5515 Less Trade-in of one (1) Howard Price Blazer: Model 360EZ, Serial Number 260-234, 25HP Kohler	1	Each		

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

BID SPECIFICATIONS

MID-MOUNT ZTR MOWER

Exmark Lazer 27 KA Liquid Cooled LZ27LKA604

SPECIFICATIONS

Engines—27-hp Kawasaki® Liquid-Cooled. Engine governed to 3750 rpm.

Air Filter—Heavy-duty canister.

Drive System—Two Hydro-Gear 12cc variable displacement pumps with integral SCR valves, powering two high-torque Parker/Ross wheel motors with 1.25" diameter tapered shafts.

Ground Speed—0 to 10.0 mph forward, 0 to 6.3 mph reverse, infinitely variable.

Hydro Fluid—Mobil 1® SuperSyn oil.

Tracking Adjustment—Single adjustment knob (no tools required).

Cutting Deck—60" Formed and continuous seam welded with 10-gauge top and 7-gauge skirt, 4-point suspension, full floating deck with 6 adjustable anti-scalp rollers. Deck: 5.5" deep.

Cutting Height—1.5" to 5.0" in .25" increments and adjustable from operator's seat.

Deck Lift—Manually raises into transport position from operator's seat, without changing cutting height. Hand operated or foot assist.

Drive Tires—24 x 12-1/2, 4-ply Multi Trac.

Front Caster Tires—12 x 6.5-6, Heavy duty smooth tread, semi pneumatic tires.

Casters—5/8 inch thick double-yoke, caster wheel assembly with pre-installed bearing cups.

Steering and Motion Control—Hydraulically dampened twin levers adjust fore and aft.

Curb Weight—1403 lbs.

Dimensions—60" Side Discharge

Width	Deflector Up	61.4"	Deflector Down	72.2"
	Length	80.7"	W/ROPS folded	89.5"
Height	Base unit	48"		
	W/ROPS folded	54.0"		
	W/ROPS up	72.0"		

Blades—3-20.5" blades.

Blade-Tip Speed—18,000-18,500 fpm.

Blade Spindles—1.75" diameter mounted in cast aluminum alloy spindle housings with dual maintenance free bearings.

Tractor Frame—Welded heavy-duty tubular steel.

Turning Radius—True zero turn.

Drive-Wheel Release—Allows unit movement without engine running.

Parking Brake—Lever-actuated drum and band integrated with transmission neutral interlock.

Fuel Capacity—13.5 gallons, twin fuel tanks.

Storage Compartment—Standard

Electrical—12-volt battery with 30-amp alternator.

PTO Engagement—Mag Stop Electromagnetic clutch. 200 Ft Lb. 2 year warranty.

Hour Meter—Standard.

Engine Temperature Gage—Standard.

Voltage Gage—Standard.

- Cooling System**—Three-row core, flat fin radiator with continuously running fan.
 - Safety Package**—Operator Presence Controls (OPC) and drive system interlock.
 - Seat**—High-back, "EVC" (Elastomeric Vibration Control) seat which has no springs. Seat adjusts fore and aft and features padded height adjustable armrests for maximum comfort.
 - Cup Holder**—Standard.
 - Roll Over Protection**—2 post foldable ROPS standard with seat belt and latch.
 - Accessories Available**—
 - Exmark Turf Stripper (STRLZ60)
 - Mulch Kit (MK604)
 - Hitch Kit (1-631665)
 - Grass Catcher 3-bushel capacity (GC36MC)
 - Ultra Vac Collection System
 - 3 bags, 13.5 bushel capacity (LUV60C)
 - Dump from seat, 11 bushel capacity (UVD60C)
 - Trash Container (TC25)
 - Full Suspension Seat (LS Seat)
 - CustomRide Seat Suspension (103-4754)
 - *Light Kit (FRPSLKIT)
 - *Sunshade (FRPSSHADE)
- *Items require the two post foldable ROPS to be installed

Contract Terms and Conditions

Table of Contents

Terms and Conditions.....	II
Standard Terms and Conditions	II
RIVIP INFO - BID SUBMISSION REQUIREMENTS	II
VENDOR SPECIFICATIONS	II

Terms and Conditions

Standard Terms and Conditions

RIVIP INFO - BID SUBMISSION REQUIREMENTS

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

VENDOR SPECIFICATIONS

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.

BID SPECIFICATIONS

MID-MOUNT ZTR MOWER

Exmark Lazer 27 KA Liquid Cooled LZ27LKA604

SPECIFICATIONS

- Engines**—27-hp Kawasaki® Liquid-Cooled. Engine governed to 3750 rpm.
- Air Filter**—Heavy-duty canister.
- Drive System**—Two Hydro-Gear 12cc variable displacement pumps with integral SCR valves, powering two high-torque Parker/Ross wheel motors with 1.25" diameter tapered shafts.
- Ground Speed**—0 to 19.0 mph forward, 0 to 6.3 mph reverse, infinitely variable.
- Hydro Fluid**—Mobil 1® SuperSyn oil.
- Tracking Adjustment**—Single adjustment knob (no tools required).
- Cutting Deck**—60" Formed and continuous seam welded with 10-gauge top and 7-gauge skirt. 4-point suspension, full floating deck with 6 adjustable anti-scalp rollers. Deck: 5.5" deep.
- Cutting Height**—1.5" to 5.0" in .25" increments and adjustable from operator's seat.
- Deck Lift**—Manually raises into transport position from operator's seat, without changing cutting height. Hand operated or foot assist.
- Drive Tires**—24 x 12-1/2, 4-ply Multi Trac.
- Front Caster Tires**—18 x 6.5-6, Heavy duty smooth tread, semi pneumatic tires.
- Casters**—5/8 inch thick double-yoke, caster wheel assembly with pre-installed bearing cups.
- Steering and Motion Control**—Hydraulically dampened twin levers adjust fore and aft.
- Curb Weight**—1403 lbs.
- Dimensions**—60" Side Discharge

Width	Deflector Up	61.4"	Deflector Down	72.2"
	Length	80.7"	W/ROPS folded	89.5"
Height	Base unit	48"		
	W/ROPS folded	54.0"		
	W/ROPS up	72.0"		
- Blades**—3-20.5" blades.
- Blade-Tip Speed**—18,000-18,500 fpm.
- Blade Spindles**—1.75" diameter mounted in cast aluminum alloy spindle housings with dual maintenance free bearings.
- Tractor Frame**—Welded heavy-duty tubular steel.
- Turning Radius**—True zero turn.
- Drive-Wheel Release**—Allows unit movement without engine running.
- Parking Brake**—Lever actuated drum and band integrated with transmission neutral interlock.
- Fuel Capacity**—13.5 gallons, twin fuel tanks.
- Storage Compartment**—Standard
- Electrical**—12-volt battery with 30-amp alternator.
- PTO Engagement**—MagStop Electromagnetic clutch, 200 Ft Lb. 2 year warranty.
- Hour Meter**—Standard
- Engine Temperature Gage**—Standard.
- Voltage Gage**—Standard.

Cooling System—Three-row core, flat fin radiator with continuously running fan.
Safety Package—Operator Presence Controls (OPC) and drive system interlock.
Seat—High-back, “EV” (Elastomeric Vibration Control) seat which has no springs. Seat adjusts fore and aft and features padded height adjustable armrests for maximum comfort.
Cup Holder—Standard.

Roll Over Protection—2 post foldable ROPS standard with seat belt and latch.

Accessories Available—
Exmark Turf Striper (STRLZ60)
Mulch Kit (MK604)
Hitch Kit (1-631665)
Grass Catcher 3-bushel capacity (GC36MC)
Ultra Vac Collection System
-3 bags, 13.5 bushel capacity (LUV60C)
-Dump from seat, 11 bushel capacity (UVD60C)
Trash Container (TC25)
Full Suspension Seat (LS Seat)
CustomRide Seat Suspension (103-4754)
*Light Kit (FRPSLKIT)
*Sunshade (FRPSSHADE)

*Items require the two post foldable ROPS to be installed

BID SPECIFICATIONS COLLECTION SYSTEMS

Ultra Vac 3 bag unit

Application — Extmark Lazer Z and Lazer Z XP

Overall Unit Length with Bagger

60" deck, air-cooled: 106.65" (270.89 cm)

60" deck, liquid-cooled: 106.90" (271.53 cm)

60" deck, air-cooled XS & liquid-cooled XP: 107.90" (274.07 cm)

72" deck, air-cooled: 110.75" (281.30 cm)

72" deck, liquid-cooled: 111.00" (281.94 cm)

72" deck, air-cooled XS & liquid-cooled XP: 112.00" (284.48cm)

Overall Unit Width with Bagger

60" deck: 74.44" (189.08 cm)

72" deck: 86.49" (219.68 cm)

Total Bagging System Weight — 60" deck: 290 lbs. (132 kg) includes weight kit;

72" deck: 237 lbs. (108 kg), includes weight kit.

Collection Bins — 3 commercial-grade, cloth mesh bags with reinforced bottoms.

Total Collection Capacity — 13.4 bushels (3 bags and hood).

Dump Mechanism — Manual lift off.

Blower Tube — 7.75" diameter, fixed, abrasion-resistant polyethylene.

Impeller — 5 bladed, abrasion resistant steel, 15.0" diameter.

Impeller Axis — Vertical for more efficient discharge flow.

Impeller Housing — 3/16" thick abrasion-resistant steel.

Bearings — 1" (2.54 cm) sealed "non-greaseable" bearings