

[ADVANTAGES](#)[SPECIFICATIONS/
DOCUMENTS](#)[ATTACHMENTS](#)[REVIEWS](#)[VIDEOS](#)

DOCUMENTS

[900 Series Snow Throwers Brochure](#)[930 SWE Operator's Manual](#)

SPECIFICATIONS

SPECIFICATIONS

Push Button Electric Start	Standard (110 volt)
Oil Fill Tube	Extended
Clearing Width	30"
Intake Height	22"
Auger Diameter	16"
Auger Design	Heavy-duty serrated steel
Impeller Diameter	16"
Drive System	Steerable wheel / positive traction
Grease Filtings	Standard
Zero-Turn Posi-Steer™	Power steering / trigger
Speeds	6 forward / 2 reverse
Heated Hand Grips	Capable
Single-Hand Operation	Standard
Pitch Control	Remote
Chute Rotation	Crank / 190°
Chute	High impact / clog-resistant
Chute Clearing Device	Standard
Headlight	In-dash
Tires	16" x 6.5"
Deluxe Skid Shoes	COOL BLUE™ rust resistant, non-marking, reversible
Tread	X-TRAC™
Shave Plate	Stainless steel
Fuel Capacity	5 qt.
Engine	357cc Cub Cadet® OHV 4-cycle
Approximate Weight	383 lbs
Warranty	3-year limited residential & 1-year limited commercial

Contract Terms and Conditions

Table of Contents

Terms and Conditions..... VI
 BID STANDARD TERMS AND CONDITIONS VI
 TERMS AND CONDITIONS FOR THIS BID VI
 VENDOR SPECIFICATIONS VI

Terms and Conditions

BID STANDARD TERMS AND CONDITIONS

TERMS AND CONDITIONS FOR THIS BID

VENDOR SPECIFICATIONS

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED) FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED