



# Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS  
ONE CAPITOL HILL  
PROVIDENCE RI 02908

BUYER: Mosca, Gary  
PHONE #: 401-574-8124

CREATION DATE : 11-JAN-12  
BID NUMBER: 7449389  
TITLE: 2012 4X4 DUMP TRUCK WITH SNOW PLOW - RIC  
  
BID CLOSING DATE AND TIME:09-FEB-2012 10:00:00

**B  
I  
L  
L  
T  
O**  
RIC-PURCHASING  
600 MOUNT PLEASANT AVENUE  
PROVIDENCE, RI 02908  
US

**S  
H  
I  
P  
T  
O**  
RIC SPECIAL INSTRUCTIONS  
SEE BELOW  
SEE BELOW, RI N/A  
US

Requisition Number: 1255191

Note to Bidders: Questions concerning this solicitation may be emailed to gary.mosca@purchasing ri gov no later than 1/25/12 @ 12:00 NOON EST  
Questions should be submitted in a Microsoft word attachment. Please reference the RFQ # on all correspondence

Questions received if any will be posted on the internet as an addendum to this solicitation. It is the responsibility of all interested parties to download this information

Line	Description	Quantity	Unit	Unit Price	Total
1	Req. 1255191 - 2012 4x4 DUMP TRUCK WITH SNOW PLOW PER SPECIFICATIONS - RIC VENDORS MUST FILL OUT AND SUBMIT THE (3) THREE PAGE SPECIFICATION SHEET WITH THEIR BID.	1 00	Each		

Delivery: \_\_\_\_\_

Terms of Payment: \_\_\_\_\_

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

1255191 – 2012 4X4 DUMP TRUCK WITH SNOW PLOW

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	↓ Yes/No	↓ Specify Alternative (if responding no) ↓
2012 DUMP TRUCK WITH SNOW PLOW		
<b>CAB &amp; CHASSIS</b>		
Engine: 6.2 Liter Gas V8, 385 HP -405 FT./LBS Torque		
Transmission: 5_speed Torqshift Automatic w/OD		
Fuel Type: Regular Unleaded		
Fuel Capacity: 40 Gallons		
GVWR: 17,950 lb Payload		
Wheelbase: 141"/ 60" axle to cab		
Axel Ratio: 4 88		
Tires: 225/70Rx 19.5G BSW AS		
Wheels: 19.5" Argent Painted Steel (6)		
Seating: HD Vinyl Bench Seat w/ Recline		
Radio: AM/FM Stereo w/ digital clock and 2 speakers		
Paint Color: White		
Snow Plow Prep Package: Heavy Duty Alternator, Spring Package		
Running Boards – High Strength aluminum running Boards with a diamond plate pattern		
4x4 electronic shift -on-the-fly with auto-manual locking hubs and rotary control on instrument panel		
Misc: 6 keys, operation manual, manually adjusted side mirrors, front windshield visors, speedometer, variable intermittent, wipers, and tachometer		
<b>ADDITIONAL LIGHTING OPTION REQUEST:</b> Cab Bar Lighting - Color: Yellow		
<b>DUMP BODY</b>		
Inside Length: 9 feet		

1255191 – 2012 4X4 DUMP TRUCK WITH SNOW PLOW

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	↓ Yes/No	↓ Specify Alternative (if responding no)
Width: 7 feet		
<p>Materials: See list below</p> <p><b>Sides:</b> Side panels should be constructed of 10 gauge high tensile steel, all exposed bends shall be 1: radius                      Front corner posts shall be 3" deep and to have an aerodynamic design, no intermediate side posts                      Top rail shall be box section 3- 3/4" wide x 5- 1/2" tall.                      Top rail section shall be enclosed with flange formed into floor for a "double wall" construction. Centerbend to fold back at 20 degrees at top and bottom to bend back at 35 degrees from horizontal. No seam shall be visible outside or bottom of top rail.                      5" inch wide 35 degree sloped rub rails                      Minimum 8" wide full depth rear corner post                      Minimum 5-1/2" deep rear corner post                      6" Board pockets 100% fully solid welded construction</p>		
<p><b>Tailgate:</b> Tailgate panel shall be constructed of a one piece sheet of 10 gauge high tensile steel. All horizontal bracing, including top rail, to be dirt shedding using large radius die. No center vertical braces minimum 1/2" flame cut offset upper tailgate hinge. Minimum 3/4" lower tailgate pin incorporated in lower vertical tailgate brace. Minimum 1/4" diameter proof coil spreader chains, 1/2" lower latch assembly. 1/2" plate flame cut lower pin cradle. Complete tailgate latching assembly reinforced with a 1/4" backing plate. 100% fully solid welded construction</p>		
<p><b>Front Head:</b> Front head panel shall be constructed of a one piece sheet of 10 gauge high tensile steel. Three bend top rail (minimum 3" wide, 2" deep w/ a 7/8" return flange). To be a minimum 6" higher than the side height and be 100% fully solid welded construction.</p>		
<p><b>Floor:</b> Constructed of two center seam welded pieces of 10 gauge high tensile steel with flange in vertical portion of floor to form top rail section, 80" inside width, 2" to radius floor to side bracing with smooth transition from floor side (no weld)</p>		
<p><b>Understructure:</b> All 8 gauge high tensile steel fabricated understructure, cross-members interlaced through long members for maximum floor support and weight savings,</p>		

1255191 – 2012 4X4 DUMP TRUCK WITH SNOW PLOW

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	↓ Yes/No	↓ Specify Alternative (if responding no)
<p>3” deep cross-members with 8” deep long-members.</p> <p><b>Hoist:</b> Single cylinder dual support arm hoist, 4” cylinder on scissor lift, chrome plated (Vickers, DPH 900-1100) piston rod, minimum 50 degree dump angle.</p>		
<p><b>Misc:</b> ¼ cab protector and complete, fully operational installation operators manual.</p> <p><b>Body Capacity:</b> 3 5-4.5 cubic yards</p> <p><b>Side/Rear heights:</b> 18” / 24”</p> <p><b>Weight:</b> 2104 lbs including Hoist</p> <p><b>Hoist Capacity:</b> 1520 Hoist w/ 5” chrome cylinder, heavy duty platform hinge, monarch electric hyd operated, single acting, grease able fittings on all, bearing points and a removable cylinder head.</p> <p><b>Color:</b> White to match chassis</p>		
<p><b>SNOW PLOW</b></p> <p><b>Blade Height:</b> 34 inches</p> <p><b>Blade Gauge:</b> 11 Gauges</p> <p><b>Trip Springs:</b> 4 compression type trip springs</p> <p><b>Ribs:</b> Eight</p> <p><b>Angling Rams:</b> 2” X 16”</p> <p><b>Plowing Width:</b> Full angle, 7’ 11”</p> <p><b>Weight:</b> Approximately 1350 lbs</p> <p><b>Wear Shoes:</b> Four cast iron shoes</p> <p><b>Cutting Edge:</b> ½” X 8”, center punched, reversible</p> <p><b>In Cab Control:</b> Compact Joy Stick Control</p> <p><b>Vehicle Mount:</b> Minute Mount 2 vehicle mounting system</p> <p><b>Misc:</b> Head lamps, directional lamps on mounting system w/ in cab switch, all hydraulic hoses and safety carry chain</p> <p><b>Color:</b> Yellow</p>		

**Contract Terms and Conditions**

**Table of Contents**

Terms and Conditions..... VI  
    BID STANDARD TERMS AND CONDITIONS ..... VI  
        TERMS AND CONDITIONS FOR THIS BID ..... VI  
        VENDOR SPECIFICATIONS ..... VI  
        RIVIP INFO - BID SUBMISSION REQUIREMENTS ..... VI  
        AUTO / VEHICLE PURCHASE ORDER ..... VI  
        AWARD ..... VI  
        DELIVERY PER AGENCY ..... VI

## **Terms and Conditions**

### **BID STANDARD TERMS AND CONDITIONS**

### **TERMS AND CONDITIONS FOR THIS BID**

#### **VENDOR SPECIFICATIONS**

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED

#### **RIVIP INFO - BID SUBMISSION REQUIREMENTS**

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

#### **AUTO / VEHICLE PURCHASE ORDER**

THE FOLLOWING ADDITIONAL TERMS AND CONDITIONS APPLY TO THIS PURCHASE ORDER: 1. ALL VEHICLES MUST BE DELIVERED WITHOUT DEALER'S NAME OR ADVERTISING OF ANY TYPE VISIBLE ON THE BODY. 2. EACH VEHICLE DELIVERED TO THE STATE MUST BE ACCOMPANIED BY A "CERTIFICATE OF ORIGIN" CONTAINING THE MANUFACTURER'S VEHICLE IDENTIFICATION NUMBER (VIN), THE NUMBER OF ENGINE CYLINDERS AND ENGINE TYPE, A GENERAL DESCRIPTION OF THE BODY, AND THE MODEL NAME OR NUMBER. CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO STATE OF RI/FLEET OPERATIONS, ONE CAPITOL HILL, PROVIDENCE, RI 02908 UNLESS THE VEHICLE IS BEING PURCHASED BY THE RHODE ISLAND STATE POLICE. IF SO, CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO RHODE ISLAND STATE POLICE, 311 DANIELSON PIKE, NORTH SCITUATE, RI 02857. 3. THE VENDOR MUST WARRANT FULL AND UNENCUMBERED TITLE TO THE VEHICLE(S) AS OF THE DATE OF DELIVERY TO THE STATE. 4. TITLE CERTIFICATES MUST BE PROVIDED AT THE TIME OF DELIVERY TO THE STATE

#### **AWARD**

THE STATE, AT ITS SOLE DISCRETION, SHALL RESERVE THE RIGHT TO MAKE ONE OR MULTIPLE AWARDS FOR THIS REQUIREMENT AND/OR TO REJECT ANY OR ALL BIDS

#### **DELIVERY PER AGENCY**

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY