Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
ONE CAPITOL HILL
PROVIDENCE RI 02908

CREATION DATE : 29-NOV-12
BID NUMBER: 7458322
TITLE: TEN WHEEL DUMP TRUCK - DEM

BID CLOSING DATE AND TIME:27-DEC-2012 10:30:00

BUYER: Hill, Lisa
PHONE #: 401-574-8118

BILL TO
DOA CONTROLLER
ONE CAPITOL HILL, 4TH FLOOR
SMITH ST
PROVIDENCE, RI 02908
US

SHIP TO
DOA-CS STATE FLEET
ONE CAPITOL HILL, 2ND FLOOR
SMITH ST
PROVIDENCE, RI 02908
US

Requistion Number: 1294516

Line	Description	Quantity	Unit	Unit Price	Total
1	REQ.1294516 - DUMP TRUCK - 10 WHEEL - DIESEL, PER ATTACHED SPECIFICATIONS YEAR:_____ MANUFACTURER:_____ ANTICIPATED DELIVERY DATE:_____	1.00	Each		

Delivery: _____

Terms of Payment: _____

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
TEN WHEEL DUMP TRUCK
BID NO. 7458322

Instructions to Bidders:

The entire bid must be returned,. All exceptions must be specifically identified. Failure to identify any exceptions will be interpreted to be as specified.

Bidder must be an authorized manufacturer's representative/dealer.

Bidder must submit a detailed specification of the model offered including vehicle confirmation.

Order Confirmation: vendor is to provide written confirmation of order to the Office of State Fleet Operations/Connie Resendes within 15 days of order placement/award.

Vehicle Color: Manufacturer's standard color selection is acceptable, and will be identified upon order placement.

Keys: Each vehicle is to be delivered with two (2) sets of keys.

Color: Standard Manufacturer's Color will be acceptable.

Warranty: Standard manufacturer's warranty and operator's manual shall accompany each vehicle. All written warranties and warranty cards are to be furnished in the glove compartment of each vehicle delivered.

Bidders located beyond a 150 mile radius of the delivery destination must include a written plan for delivery. Vehicles will odometer reading in excess of 150miles will not be accepted without prior approval from the Division of Purchases.

DELIVERY SITE FOR ALL VEHICLES WILL BE THE FOLLOWING:

STATE FLEET PARKING LOT
SPRING BROOK ROAD
SCITUATE, RI

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
TEN WHEEL DUMP TRUCK
BID NO. 7458322

DELIVERY INFORMATION:

SUCCESSFUL VENDOR(S) MUST CONTACT CONNIE RESENDES AT STATE FLEET OPERATIONS, (401-222-6227) AT LEAST (2) TWO DAYS PRIOR TO DELIVERY

THE FOLLOWING ADDITIONAL TERMS AND CONDITIONS APPLY TO THIS INVITATION TO BID:

1. Bids must be predicated on the basis of the bidder's full and unencumbered title to the vehicle(s) as of the date of delivery to the State. Bids subject to lien or assignment at the time of delivery to the State, or which stipulate third party or joint payment, will be rejected.

2. All vehicles must be delivered without dealer's name or advertising of any type visible on the body.

3. Preparation for Delivery: At time of delivery, the vehicle will be inspection to ensure that all specifications have been met. The cooling system of each vehicle is to be protected with permanent type anti-freeze to a temperature of at least thirty-four degrees below zero (F). Vehicles must be delivered with all equipment in place, cleaned, lubricated, serviced and ready for operation.

4. A certificate of origin/window sticker must accompany each vehicle at the time of delivery. In additional, completed registration paperwork must be provided by the vendor. For instructions on title assignment and instruction of delivery schedule arrangements, contact Connie Resendes at the Office of State Fleet Operations (401-222-6227)

5. Title certificates must be provided at the time of delivery to the State.

6. To insure timely deliveries, vendor is required to supply confirmation of order to Connie Resendes, State Fleet Operations, 1 Capitol Hill, Providence, RI 02908 indicating anticipated delivery date. This must be received within 30 days of award.

7. All vehicles must be delivered with less than 150 miles on the odometer. Dealers located outside a 150 mile radius from Providence, Rhode Island must include a

written plan of their proposed delivery method, including information regarding required dealer preparation.

8. All deliveries must include a full tank of fuel. Vehicle will not be accepted without full fuel tank.

Questions relative to the solicitation may be directed by email only to lisa.hill@purchasing.ri.gov until December 20, 2012 at 12:00 p.m.(noon).

END

REQ #: 1294516

STANDARD FEATURES 2013 10-WHEEL DUMP TRUCK RIDEM: Parks & Recreation	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE ↓ ↓ ↓	
75,280 GVWR (MINIMUM) **75,280 GVWR (MAXIMUM)**	**Yes/No**	**Specify Alternative (if responding no)**
208 INCH = WHEEL BASE 121 INCH = CAB TO CENTER OF TANDEM AXLE PLATFORM 183 INCH = BACK OF CAB TO END OF FRAME RAIL 62 INCH = FORM CENTER OF TANDEM TO END OF FRAME		
ENGINE * 11 LITER 395 HP DIESEL MOTOR (MINIMUM) UTILIZE SCR EMISSION TECHNOLOGY * ENGINE BLOCK HEATER 120 VOLT/ 1500 WATT TO INCLUDE BLOCK HEATER AOCKET RECEPTABLE * AIR COMPRESSOR 18.7 CFM * DIESEL PARTICULATE FILTER, RH SIDE UNDER CAB W/ SCR FRAME MOUNTED RH SIDE * STAINLESS STEEL BRIGHT FINISH HEAT SHIELD FOR DPF * EXHAUST AFTER TREATMENT SYSTEM DIESEL PARTIC FILTER CERAMIC PASSIVE REGEN * ENGINE SHUTDOWN WITH 30 SECOND DELAY, AUTOMATIC, WITH WARNING LIGHT AND BUZZERFOR LOW ENGINE OIL PRESSURE, HIGH COOLANT TEMPERARURE, LOW COOLANT LEVEL, INCLUDING AUTOMATI OVERRIDE * FUEL-WATER SEPERATOR-W/ MANUAL DRAIN VALVE * HAND PRIMER PUMP * ENGINE COMPRESSION BRAKE WITH SELECTOR SWITCH * EXHAUST, RIGHT SIDE SINGLE VERTICAL W/ BRIGHT FINISH HEAT SHIELD AND STACK		
TRANSMISSION 6 –SPEED AUTOMATIC TRANSMISSION (ALLISON 4500DS-6) SIX SPEED AUTOMATIC WITH PTO GEAR, OIL LEVEL SENSOR * DRIVELINE, MAIN MERITOR 18N W/ COATED INTERAXLE		

STANDARD FEATURES 2013 10-WHEEL DUMP TRUCK	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE ↓ ↓ ↓	
75,280 GVWR (MINIMUM) 75,280 GVWR (MAXIMUM)	Yes/No	Specify Alternative (if responding no)
FUEL TANK * FUEL TANK LEFT HAND SIDE 88 GALLON ALUMINUM "D" SHAPE W/INTERGRAL DEF TANK * STAINLESS FUEL TANK STRAPS/STEPS		
CAB * CONVENTIONAL CAB, AIR SUSPENDED (WELDED STEEL GALVANIZED SHELL) TO INCLUDE RUSTPREVENTATIVE PROCEDURES * GLASS-HEATED TINTED WINDSHIELD- SIDED AND REAR TINTED ONLY * GRAB HANDLES, STAINLESS STEEL, RH HANDLE & LT HANLDE BEHIND DOOR * BRIGHT FINISH GRILL AND SURROUND * BUG SCREEN, RADIATOR MOUNTED * IDENTIFICATION/CLEARANCE LIGHTS (5) LED CHROME BULLET TYPE * MIRRORS, EXTERIOR WEST COAST RH & LH BRIGHT FINISH- HEATED WITH STAINLESS STEEL ARMS AND BRACKETS * HEATED CONVEX SPOT MIRRORS * EXTERIOR SUN VISOR * INTERIOR SHALL BE CUSTOM QUIET TO REDUCE ENGINE NOISE AND VIBRATION, PADDINGON HEAD LINER, BACK OF CAB AND INTERIOR DOOR PANEL * STEERING WHEEL, TILT/TELESCOPIC * INSTRUMENT CLUSTER DISPLAY *AM/FM RADIO WITH WEATHER BAND * ARM REST (2) * SEAT DRIVER, AIR SUSPENSION, INTERMEDIATE BACK ISOLATED, WITH TWO POSITION FRONT CUSHION ADJUSTABLE. INCLUDES SEATBELT THREE-POINT, LAP AND SHOULDER BELT TYPES PASSENGER SEAT NON-SUSPENSION LOW BACK, VINYL,FLODINF BACKWITH SEAT BELT		

STANDARD FEATURES 2013 10-WHEEL DUMP TRUCK	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE ↓ ↓ ↓	
75,280 GVWR (MINIMUM) 75,280 GVWR (MAXIMUM)	Yes/No	Specify Alternative (if responding no)
* AIR CONDITIONER WITH INTEGRAL HEATER AND DEFROSTER, INCLUDES REFIGERANT HYDROFLOUROCARBON HFC-134A		
AXLES * FRONT AXLE-18,000 LB I-BEAM TYPE * REAR AXLE- 58,000 LB DUAL REDUCTION SINGLE DRIVE W/POWER DIVIDER LOCK OUT * RATIO 4.80		
SUSPENSION * FRONT, TAPER LEAF 18,000 LB * REAR, 58,000 LB MULTI-LEAF W/ANTI-SWAY TYPE SPRINGS AND BRONZE TRUNION BUSHING * 54 INCH TANDEM REAR AXLE SPACING		
ELECTRICAL * TWELVE- VOLT NEGATIVE GROUND ELECTRICAL SYSTEM CONSISTING OF THE FOLLOWING COMPONETS: • ALTERNATOR SHALL BE 13-AMP CAPACITY • BATTERY BOX COVERS ALUMINUM • WIRING SCHEMATIC SHALL BE SUPPLIED ILLUSTRATING THE WIRING SYSTEM • STOP,TURN,TAIL AND BACKUP LIGHTS • THREE MAINTENCE FREE BATTERIES 1950 CCA TOTAL • BODYLINK INTERFACE (ELECTRICAL CONNECTION ALONG FRAME RAIL FOR COMMONLY USED BODYBUILDER CONNECTIONS)		
BRAKES * FRONT S-CAM16.5 INCH X 6 INCH CAST SPIDER * REAR S-CAM 18.0 INCH X 7 INCH BRONZE BUSHING CAST SPIDER * BRAKE SYSTEM TO INCLUDE: • HEATED AIR DRYER • BRAKE CHAMBERS, TYPE 30/30 REAR • DUST SHIELDS FRONT AND REAR • BRAKE LINES COLOR-CODED NYLON • SLACK ADJUSTERS AUOMATIC FRONT AND REAR • ANTI-LOCK BRAKE SYSTEMS • FULL TRAILER CONNECTIONS INCLUDING AIR		

STANDARD FEATURES 2013 10-WHEEL DUMP TRUCK	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE ↓ ↓ ↓	
75,280 GVWR (MINIMUM) **75,280 GVWR (MAXIMUM)**	**Yes/No**	**Specify Alternative (if responding no)**
LINES AND 7 WIRE CABLEAND PLUG W/11-761 PROTECTIVE BOOT ROUTED TO REAR OF CHASIS • HAND CONTROL VALVE FOR TRAILER BRAKES • AIR RESERVOIRS ALUMINUM		
TIRES *FRONT – (2) 315/80R22.5 20L BRIDGESTONE M860 *REAR (8) 12R24.5 H BRIDGESTONE M843		
WHEELS * FRONT- POLISHED ALUMINUM DISC HUB PILOTED (2) 22.5 X 9.0 * REAR- STEEL DISC HUB PILOTED (8) 24.5 X 8.25 RIMS PAINTED GRAY		
PAINT * CAB- DARK GREEN * CHASSIS - BLACK		
DUMP BODY * STEEL DUMP BODY 15 FEET LONG W/48 INCH SIDES AND 54 INCH GATE * ¼ INCH AR-250 FLOOR * ¼ INCH AR-250 TWO PANEL GATE * 3/16 INCH 44 – W SIDES W/VERTICAL BOX BRACING * 42 INCH CAB PROTECTOR * 45 TON HOIST * STEEL WEAR STRIPS * P.T.O. FOR ALLISON TRANSMISSION * HIGH LIFT TAIL GATE * 30TON PINTLE HOOK ON ¾ STEEL PLATE * ELECTRIC COVER W/MESH TARP * DC 3500-3500 BODY VIBRATOR		

Contract Terms and Conditions

Table of Contents

Terms and Conditions.....VI
BID STANDARD TERMS AND CONDITIONS VI
TERMS AND CONDITIONS FOR THIS BID VI
DELIVERY PER AGENCY VI

Terms and Conditions

BID STANDARD TERMS AND CONDITIONS

TERMS AND CONDITIONS FOR THIS BID

DELIVERY PER AGENCY

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.