



**State of Rhode Island  
Department of Administration / Division of Purchases  
One Capitol Hill, Providence, Rhode Island 02908-5855  
Tel: (401) 574-8100 Fax: (401) 574-8387**

**ADDENDUM #1**

**RFP #7461257**

**TITLE: BUCKET TRUCK – 2013 URI**

**OPENING DATE AND TIME: 3/18/13 – 10:00 AM**

---

**ATTACHED ARE 7 PAGES OF ADDITIONAL SPECIFICATIONS THAT WERE  
INADVERTENTLY OMITTED.**

**GARY MOSCA  
BUYER I**

Quantity:	ONE (1)			Vendor Indicate Compliance Yes/No
Department:	URI	Fuel Type:	Gasoline	
Division:	ITS	Color:	White	
RI-FANS Requisition Number:		1304905		

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	Yes/No	Specify Alternative (if responding no)
<b>CHASSIS</b>		
2013 Model Year		
Regular Van Install van partition between cargo area and driver/passenger area of chassis or equivalent to		
Chassis Color- White or equivalent to		
Chassis Cab to Axle/Trunion Length Not Applicable For This Chassis Mnke/Model or equivalent to		
Chassis Wheelbase Length- 138 or equivalent to		
GVWR 9,5000 LBS or equivalent to		
4,600 LBS Front Axle Rating or equivalent to		
6,084 LBS Rear Axle Rating or equivalent to		
245/75R16 Front Tire or equivalent to		
245/75R16 Rear Tire or equivalent to		
Gas 5.4L V8 or equivalent to		
4-Speed Automatic Transmission (without PTO Provyision) or equivalent to		
Single Horizontal Exhaust Right Hand or equivalent to		
Hydraulic Brakes or equivalent to		
No Idle Engine Shut-Down Required or equivalent to		
4x2 Drivetrain or equivalent to		
Cargo Van or equivalent to		
Other Interior Cab Options Quiet Plex Composite Racks & Bins Package: Fully installed. Includes dual, driver-side, 3-shelf modules (46"x37"x16") with dividers and hardboard back panel, single passenger-side 2-shelf module (46"x37"x16") with lower locking storage door, removable 2-drawer toolbox, dividers, triple-hook bar and hardboard back panel. Shelves are constructed of high densit composite material and ends are constructed of steel with scratch-resistant finish, composite snap-on shelf dividers (12 total) and composite bulkhead with lockable door and 4" of seat recline for the driver-side seat or equivalent to		
Vinyl Bucket Seat or equivalent to		
<b>ADDITIONAL PRICING</b>		
Stock Unit or equivalent to		
<b>ELECTRICAL ACCESSORIES</b>		
Cargo van lighting kit with a single grommet mounted stop lamp in the rear platform access step. The light will work in conjunction with		

*[Handwritten signature]*  
1/25/13

1304905

the chassis brake lights or equivalent to		
Two amber strobe lights, mounted on the turntable of the unit, visible above the chassis cab with brush guards installed on beacon light mounting bracket with master control switch in rocker switch panel or equivalent to		
Single tone back up alarm installed between the chassis frame rails at the rear of the chassis. To work in conjunction with chassis reverse drive system or equivalent to		
1800 Watt Pure-Sine Wave Inverter or equivalent to		
Dash panel rocker switches supplied with Ford Chassis, 4 auxiliary switches supplied in up fitting package from Ford or equivalent to		
Battery Protection Device Installed To Turn Off Accessory Loads To Protect The Chassis Battery Wire Inverter & strobes in "hot" mode and install a protection device in-line to cut off power just before battery gets too low to start the chassis. Device will monitor battery voltage or equivalent to		
<b>UNIT</b>		
Telescopic, van mounted aerial device with side mounted, hydraulically leveled platform. To include the following features:		
Ground to bottom of platform height: 30.1 feet or equivalent to		
Working height: 35.1 feet or equivalent to		
Maximum reach to edge of platform: 20.7 feet (at 7.5 foot platform height) or equivalent to		
Telescopic boom extension: 10 feet or equivalent to		
Noncontinuous rotation: 370 degrees or equivalent to		
Non- Insulating Aerial Device or equivalent to		
Platform Capacity: 350 lbs. or equivalent to		
Boom Articulation: -13.5 to 80 degrees or equivalent to		
Master/ Slave Leveling: Platform automatically maintains level during boom articulation through a lifetime master/slave hydraulic leveling system that requires no major preventative maintenance or equivalent to		
110 VAC GFCI outlet with waterproof duplex receptacle installed at the platform or equivalent to		
Engine Start/Stop located at upper and lower controls or equivalent to		
Controls: 12 VDC Electric toggle switch controls for aerial device operation or equivalent to		
Hydraulic System: Open-center system operating at 2.5 gpm and 2,200 psi or equivalent to		
Slugged extension cylinder installed in telescoping boom of unit to prevent boom from retracting into van rear door, or equivalent to		
Unit is painted with a powder coat paint process which provides a finish-painted surface that is highly resistant to chipping, scratching, abrasion and corrosion, or equivalent to		
Structural Warranty on the following major components is to be warranted for so long as the initial purchaser owns the product: Booms, boom articulation links, hydraulic cylinder structures, pedestals, and turntables, or equivalent to		
<b>UNIT MODEL</b>		
Post mount pedestal for Van Installation or equivalent to		
Poly Reservoir, Pedestal Mounted, 7 Gallon; includes Sight Gauge or equivalent to		
Single One (1) Man, Fiberglass Walk-In Platform; fixed position with door. 26 x 26 x 42 inches; includes safety chain and latch for		

1304905

door or equivalent to		
Soft vinyl platform cover with retention strap or equivalent to		
Two-Speed Electric controls at the platform include toggle switch controls for boom functions, an emergency stop switch, and a high/low speed selector that is integral with the master engage switch. Lower controls are on a pendant mounted box and include electric toggle switches and a 'push to operate' master engage switch. Lower controls are installed in a body compartments unless otherwise specified or equivalent to		
Manual lowering valve located at the boom tip. For use in emergency situations to allow the operator to lower the boom to the ground or equivalent to		
Start/Stop 12VDC Module installed behind the drivers seat, inside the cab. (PN: 650-40211) or equivalent to		
<b>UNIT &amp; HYDRAULIC ACC.</b>		
HVI-22 Hydraulic Oil (Standard) or equivalent to		
Deweze fan belt driven pump with magnetic clutch installed in conjunction with chassis engine or equivalent to		
<b>BODY AND CHASSIS ACCESSORIES</b>		
75.50" Wide x 33" Long van style tailshelf, with Dovetail, installed at the rear of the van chassis or equivalent to		
Install below rotation extension ladder rack on drip rail of van roof. Ladder rack to accommodate an 18" wide extension ladder, with no interference to ladder during rotation of turn table while ladder is in the rack or equivalent to		
Cable Step Installed At Rear, Single Step or equivalent to		
Small Grab Handle Installed At Rear or equivalent to		
Wheel Chocks, Rubber with Metal Hairpin Style Handle, 9.75" L X 7.75" W X 5.00" H (Pair) or equivalent to		
Lower control holder Holder for lower control mounted on curbside of pedestal. Holder for lower control cable installed below control holder on curbside of pedestal or equivalent to		
Safety Harness & 6 FT Lanyard (Fits Medium To X-large) or equivalent to		
5 LB Fire Extinguisher With Light Duty Bracket, Installed to be mounted in cab floorboard between driver and passenger seats or equivalent to		
Triangular Reflector Kit, Installed Mounted in the floorboard between driver and passenger seat of van or equivalent to		
Master rack poly bin package installed in cargo area of van. Streetside module includes two (2) shelves and storage compartment at bottom. Curbside module includes two (2) shelves with dividers on middle shelf and a storage compartment at bottom with two (2) slide out drawers on the left side and open storage on the right side. Bulkhead with lockable door included or equivalent to		
Platform Access Step With Rear Grommet Mounted Brake Light (Holds Two Wheel Chocks) Access step installed on rear of tailshelf. Access step is off set to curbside, to allow easy access to platform and to allow curbside rear door to open without interference or equivalent to		
Slope Indicator Assembly For Machine Without Outriggers or equivalent to		
Soft Vinyl Lanyard Pouch or equivalent to		
Vinyl Manual pouch for storage of all operator and parts manuals or equivalent to		







