

# Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS  
 ONE CAPITOL HILL  
 PROVIDENCE RI 02908

BUYER: Mosca, Gary  
 PHONE #: 401-574-8124

CREATION DATE : 22-FEB-13  
 BID NUMBER: 7461266  
 TITLE: BUCKET TRUCK  
 BID CLOSING DATE AND TIME: 28-FEB-2013 10:00:00

**B  
I  
L  
L  
T  
O**  
 URI ACCOUNTS PAYABLE  
 CARLOTTI ADMINISTRATION BLDG  
 75 LOWER COLLEGE ROAD, SUITE 1  
 KINGSTON, RI 02881  
 US

**S  
H  
I  
P  
T  
O**  
 URI SPECIAL INSTRUCTIONS  
 SEE BELOW  
 SEE BELOW, RI N/A  
 US

Requisition Number: 1305595


Note to Bidders: Questions concerning this solicitation may be emailed to gary.mosca@purchasing.ri.gov no later than 3/11/13 @ 8:00 AM (EST). Questions should be submitted in a Microsoft word attachment. Please reference the RFQ # on all correspondence. Questions received if any, will be posted on the internet as an addendum to this solicitation. It is the responsibility of all interested parties to download this information.

Line	Description	Quantity	Unit	Unit Price	Total
1	<p>Req. 1305595 - NEW - NEWEST MODEL Bucket Truck - URI</p> <p>All Bidders are to be in compliance with Rhode Island General Law Chapter 31-4 Transfer of Vehicles Section 31-4-11.</p> <p>All Bidders MUST fill out and submit written vehicle order confirmation within 30 days of issuance of Purchase Order to:</p> <p>University of Rhode Island            Purchasing Department            581 Plains Road            Kingston, RI 02881</p> <p>DELIVER TO:            University of Rhode Island            URI Automotive            9 Rhody Way            Kingston, RI 02881</p> <p>REQ. #1304905 - BUCKET TRUCK            YEAR _____</p> <p>MAKE _____</p> <p>MODEL _____</p> <p>AERIAL DEVICE _____</p> <p>ANTICIPATED DELIVERY _____</p>	1.00	Each		

Delivery: \_\_\_\_\_

Terms of Payment: \_\_\_\_\_

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS

Department of Administration  
DIVISION OF PURCHASES  
One Capitol Hill  
Providence, RI 02908-5855

Tel: (401) 574-8100  
Fax: (401) 574-8387  
Website:  
[www.purchasing.ri.gov](http://www.purchasing.ri.gov)

**Bid #7461266**

**Opening Date & Time: 3/28/13 @ 10:00 AM (EST)**

- A copy of the bid specifications must be returned with the bid and must indicate compliance or exception to each aspect of the specifications.
- All exceptions must be specifically identified.
- Bidder must be an authorized manufacturer's representative/dealer.
- Bidder must submit a detailed specification of the model offered including vehicle confirmation.
- Bidders located beyond a 100 mile radius of delivery destination must include a written plan for delivery.
- Vehicles with odometer reading in excess of 100 miles will not be accepted without prior approval from the division of Purchases.
- The State of Rhode Island reserves the right to mandate the replacement of all vehicles in accordance with Rhode Island State Lemon Law 31-5.2-1 to 31-5.2-13.
- Replacement equipment must be like or superior specifications to the vehicle in question. Costs associated with the removal of problematic equipment and the delivery and installation of replacement equipment will be solely at the vendor's expense.

**Instructions for Bid Submission**

**Bidders are instructed to submit their responses in the following manner:**

- For each item bid, return the original bid specification completed by indicating compliance or exception and the proposed vehicle specification, numerically marked to correspond with the bid item number. If there are exceptions, however minor, they must be indicated. If there are no exceptions noted, it will be assumed there are none.
- If bidding on multiple items, place the proposed specifications in ascending numerical order, preferably in a binder marked with bidders name, address, bid number and opening date and time.

End Document

<b>Quantity:</b>	One			<b>Vendor Indicate Compliance Yes/No</b>
<b>Department:</b>	University of Rhode Island	<b>Fuel Type:</b>	Diesel	
<b>Division:</b>	Facilities Services	<b>Color:</b>	White	
<b>RI-FANS Requisition Number:</b>		1305595		

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	Yes/No	Specify Alternative (if responding no)
The equipment and vehicle purchased shall be of New:		
The equipment shall be delivered to the University no earlier than July 1st 2013. However, the University may elect to change the delivery date to no later than June 30th 2013.		
<b>Base Bid Unit Specifications</b>		
Articulating Over center Aerial Device with an insulating lower boom, insulating upper boom and insulating system at the boom tip installed behind the cab to include the following features:		
1. Ground to Bottom of Platform Height: approximately 60 feet (18.4 meters).		
2. Working Height: minimum 65 feet (19.9 meters).		
3. Maximum reach to edge of platform with Upper Boom Non- over center (working position): minimum 44 feet (13.6 meters) at platform height of 28 feet (8.7 meters)		
4. Maximum reach to edge of platform with Upper Boom Over center: minimum 48 feet (14.8 meters) at platform height of 9 feet (3.0 meters)		
5. Continuous rotation.		
6. Lower Boom Articulation: 0 to 125 degrees.		
7. Lower Boom Insulator provides 15 inches (38.1 centimeters) of Isolation.		
8. Upper Boom Articulation: 0 to 270 degrees.		
9. Platform capacity: minimum 350 lbs (181.44 kilograms)		
10. Platform leveling: achieved by a single leveling chain and 3/4" fiberglass rods in the upper and lower booms.		
11. Hydraulic system: Open center (full pressure), maximum flow of 6.0 to 6.5 gpm (22.7 to 24.6 lpm), and maximum operating pressure of 3,000 psi.		
12. Side-by-Side Boom Stow.		
13. Small Boom Tip Profile.		
14. Unit is painted with a powder coat paint process which provides a finish-painted surface that is highly resistant to chipping, scratching, abrasion and corrosion.		
15. Unit meets or exceeds ANSI 92.2 standards.		
16. Manual Upper Boom Stow Securing System with support cradle and tie down strap.		
17. Hydraulic Reservoir 30 Gallon Tank with Sight Gauge with guard and ball valves.		
18. Single, One (1) Man, Fiberglass Platform; fixed side		

*[Handwritten Signature]*  
11/22/13

mounted. 24 x 24 x 39 inches.		
19. Insulating, Proportional Speed, Upper Control Handle - with safety interlock and interlock guard. Located on the side of the platform nearest the upper boom, mounted on the shaft.		
20. One (1) Platform Step - located on the side of the platform nearest the elbow in the stowed position		
21. Platform Cover - Soft vinyl 24 x 24 Inch (610 x 610 mm)		
22. Platform Liner 50 kV - 24 x 24 x 39 Inches (610 x 610 x 991 mm)		
23. Platform Floor Liner - 24 x 24 inches with safety tread (610 x 610 mm)		
24. Hydraulic Tool Circuit at Platform: Two (2) sets of tool couplers, located on the side of the platform nearest the elbow in the stowed position.		
25. Slip Ring: Required for engine start/stop, secondary stowage system, and throttle control options		
26. Primary A-Frame Outriggers with 5-degree swivel shoe. Installed on a 36 to 40 inch chassis frame height. With hose cover, to support cab guard:		
a. Maximum Spread: 140 inches to the outer edge of shoes		
b. Ground Penetration: 7 to 11 Inches depending on chassis frame height		
c. Outrigger/Unit Selector Valve		
d. Outrigger Control Valves: located on the outrigger legs		
e. Outrigger Motion Alarms		
f. Outrigger Interlocks: will not allow the unit to be operated until the outriggers have been at least partially deployed		
27. Hydraulic Outrigger Control Valves		
28. Insulating Aerial Device, ANSI Category C, 48kV and Below		
29. Fall Protection System to include one body harness and decelerating type lanyard.		
30. Harness has adjustable slide buckle on shoulder straps, Velcro chest strap, interlocking buckles on leg straps and nylon web loop fall arrest attachment on back. Lanyard has built in shock absorber that allows 28 inches (711 mm) of automatic adjustability Mounted per DEPS		
31. Bolt On Grab Handle for Turntable		
<b>Unit Hydraulic Acc.</b>		
1. HVI-22 Hydraulic Oil (Standard).		
2. Standard Pump For PTO		
3. Hot shift PTO for automatic transmission		
<b>Body</b>		
Box tool compartment 48 inches wide x 50 inches high x 93 inches long (1219 x 1270 x 2362 mm) with 26.5 inch (673 mm) deep curb and street side compartments with the following compartmentation		
1. Streetside: Single compartment with two vertical barn-style doors. Left side has two (2) fixed shelves. Right side has four (4) unequal transverse compartments open to curbside.		

Compartment bottom has 0.125 inch (3.175 mm) rubber liner partitioned for chainsaw gas can and wedge storage. Security chain for chainsaw provided in bottom.		
2. Curbside: Single compartment with two (2) vertical barn-style doors. Left side has four (4) unequal transverse compartments open to streetside. All compartments have 0.125 inch (3.175 mm) rubber shelf liners. Top center has two (2) fixed shelves. Top right has six (6) swivel rope hooks (3-0-3).		
3. Standard features: Bolt-on rotary slam door locks. Gas shock door holders. Door locks are single point with locking cylinders. Finish paint interior compartments the same as exterior. Integrated locking system installed.		
<b>Body and Chassis Accessories</b>		
1. Cab Guard, 140" L, 12 GA Sheet Metal With Non-Skid Surface And Expanded Metal Section At Front, Black Lexzar Coating		
a. Cab Guard Mounting Kit		
b. Front Supports For Cab Guard		
2. Cab Guard Access Stirrup Step(s) With Grab Handle		
3. Cab Guard Access Ladder		
4. ICC (Underride Protection) Bumper Installed At Rear		
5. T-100 Style Pintle Hitch (30,000 LB)		
6. Set of Safety Chain Loops, Fixed Mounting (Forestry Applications)		
7. Cone Holder, Horizontal Style with Vertical Pivot (Unfolds Upwards), For Mounting On Front Bumper		
8. Platform Rest, Rigid with Rubber Tube		
9. Outrigger Pad Holder, 20" L x 20" W x 3" H, Fits 19" x 19" x 2" And Smaller Pads, Bolt-On, Bottom Washout Holes, 3/4" Lip Retainer		
10. Wheel Chocks (Pair), Rubber with Metal Hairpin Style Handle, 9.75" L X 7.75" W X 5.00" H		
11. Wheel Chock Holders (Pair), For Installation Under Flatbed Or Dump Body		
12. Mud Flaps With Altec Logo (Pair)		
13. Driveaway Safety Kit Mounted per DEPS		
14. Slope Indicator Assembly For Machine With Outriggers		
<b>Electrical Accessories</b>		
1. Outrigger Interlock System		
2. Lights and reflectors in accordance with FMVSS #108 lighting package. (Complete LED, including LED reverse lights)		
3. 4-Corner Strobe Lighting, Amber LED, Front And Rear Grommet Mounted Lights, Front Lights Mounted At Front Corners Of Cab Guard Wired Batt hot, with guarded switch		
4. Dual Tone Back-Up With Outrigger Motion Alarm		
5. 6-Way Trailer Receptacle (Pin Type) Installed At Rear Cole Hersee		
6. Electric Trailer Brake Controller (Tekonsha Voyager #9030)		
<b>Finishing Details</b>		
1. Focus Factory Build		

2. Delivery Of Completed Unit		
3. Powder Coated		
4. Finish Paint Body Accessories		
5. All interior body compartments to remain primed		
6. Apply Non-Skid Paint (Ferrox) to all walking surfaces		
7. English Safety And Instructional Decals		
8. Vehicle Height Placard - Installed In Cab		
<b>Chassis</b>		
1. International 4300 Set Back Axle		
2. Chassis Cab To Axle/Trunion Length - 121 inch		
3. Chassis Wheelbase Length - 189		
4. GVWR 33,000 LBS		
5. 12,000 LBS Front Axle Rating		
6. 21,000 LBS Rear Axle Rating		
7. Automatic Transmission		
8. Navistar Exhaust ( Right-Horizontal-Behind Cab-Horizontal)		
9. International PTO Throttle Wiring		
10. International Heavy Duty Taillight Wiring (08HAB)		
11. International Transmission Dipstick Relocated to RH Side Of Transmission (13WGH)		
12. No Prewire Chassis		
13. Air Brakes		
14. No Idle Engine Shut-Down Required		
15. 4x2 Drivetrain		
16. Conventional Cab		
<b>Standard Warranty</b>		
• One (1) year parts warranty		
• One (1) year labor warranty		
• Limited Lifetime Structural Warranty		
<b>Add/Alternate Specifications</b>		
The following add-on specifications shall be priced per-item and separate of the Base Bid Unit as specified hereto:		
1. An elevator or lift unit installed below the boom to achieve additional working height no less than 75 feet.		
2. A Chip Dump Body 14.5 cubic yard capacity (minimum), 93 inches wide x 60 inches high x 132 inches long (2362 x 1524 x 3353 mm) with ladder box on curb side of body and single piece tailgate, and to include the following:		
1. Structural Channel stringers and floor channel.		
2. 12 gauge minimum floor plate.		
3. 14 gauge minimum sides and front with full length die-formed reinforcing ribs.		
4. 14 gauge roof.		
5. Rear top and sides of body reinforced for lower boom support.		
6. 22-1/2 inches (571 mm) high tailgate, hinged curb		

side with provision to hold open for dumping.		
7. 12 gauge minimum rear under body skirt panel.		
8. Class "C" Hydraulic hoist, installed, with 45 degree dump angle and body prop.		
9. LED lighting package with wiring harness in automotive type loom.		
10. Two(2) LED strobes mounted in the upper rear corners of the dump body.		
11. Curb side built-in ladder compartment, 12 inches wide x 25 inches high (305 x 635 mm) with rear roller and internal security chain.		
12. Pole pruner compartment and ladder compartment with dual shelves and rear locking door.		
13. Interior of chip body finished with scratch and corrosion resistant liner		
14. Underside of chip body undercoated (except stringer channels).		

**Contract Terms and Conditions**

**Table of Contents**

Terms and Conditions.....II  
    BID STANDARD TERMS AND CONDITIONS .....II  
    TERMS AND CONDITIONS FOR THIS BID .....II  
    RIVIP INFO - BID SUBMISSION REQUIREMENTS .....II  
    VENDOR SPECIFICATIONS .....II  
    VEHICLE / AUTO BID .....II

## **Terms and Conditions**

### **BID STANDARD TERMS AND CONDITIONS**

### **TERMS AND CONDITIONS FOR THIS BID**

### **RIVIP INFO - BID SUBMISSION REQUIREMENTS**

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

### **VENDOR SPECIFICATIONS**

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.

### **VEHICLE / AUTO BID**

THE FOLLOWING ADDITIONAL TERMS AND CONDITIONS APPLY TO THIS INVITATION FOR BIDS: 1. ALL VEHICLES MUST BE DELIVERED WITHOUT DEALER'S NAME OR ADVERTISING OF ANY TYPE VISIBLE ON THE BODY. 2. EACH VEHICLE DELIVERED TO THE STATE MUST BE ACCOMPANIED BY A "CERTIFICATE OF ORIGIN" CONTAINING THE MANUFACTURER'S VEHICLE IDENTIFICATION NUMBER (VIN), THE NUMBER OF ENGINE CYLINDERS AND ENGINE TYPE, A GENERAL DESCRIPTION OF THE BODY, AND THE MODEL NAME OR NUMBER. CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO STATE OF RI/FLEET OPERATIONS, ONE CAPITOL HILL, PROVIDENCE, RI 02908, UNLESS THE VEHICLE IS BEING PURCHASED BY THE RHODE ISLAND STATE POLICE. IF SO, CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO RHODE ISLAND STATE POLICE, 311 DANIELSON PIKE, NORTH SCITUATE, RI 02857. 3. BIDS MUST BE PREDICATED ON THE BASIS OF THE BIDDER'S FULL AND UNENCUMBERED TITLE TO THE VEHICLE(S) AS OF THE DATE OF DELIVERY TO THE STATE. BIDS SUBJECT TO LIEN OR ASSIGNMENT AT THE TIME OF DELIVERY TO THE STATE, OR WHICH STIPULATE THIRD PARTY OR JOINT PAYMENT, WILL BE REJECTED. 4. TITLE CERTIFICATES MUST BE PROVIDED AT THE TIME OF DELIVERY TO THE STATE. 5. WHERE THE FIRM SUBMITTING THE BID IS ACTING AS AN AGENT FOR ANOTHER CORPORATE ENTITY, (SPECIFICALLY WITH RESPECT TO LEASE ARRANGEMENTS), THE BID MUST IDENTIFY THE CORPORATION WHO WILL BE NAMED IN ANY SUBSEQUENT AWARD AS THE BIDDER OF RECORD. 6. UNLESS OTHERWISE INDICATED, ALL VEHICLES WILL BE DELIVERED TO STATE FLEET OPERATIONS AT ONE CAPITOL HILL, PROVIDENCE, R.I. THE STATE OF RHODE ISLAND RESERVES THE RIGHT TO MANDATE THE REPLACEMENT OF ALL VEHICLES IN ACCORDANCE WITH RHODE ISLAND STATE LEMON LAW 31-5.2-1 TO 31-5.2-13. REPLACEMENT EQUIPMENT MUST BE OF LIKE OR SUPERIOR SPECIFICATIONS TO THE VEHICLE IN QUESTION. COSTS ASSOCIATED WITH THE REMOVAL OF PROBLEMATIC EQUIPMENT AND DELIVERY AND INSTALLATION OF REPLACEMENT EQUIPMENT WILL BE SOLELY AT THE VENDOR'S EXPENSE.

## BID STANDARD TERMS AND CONDITIONS

### TERMS AND CONDITIONS FOR THIS BID

#### **DELIVERY PER AGENCY**

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.

#### **RIVIP INFO - BID SUBMISSION REQUIREMENTS**

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

#### **AWARD**

THE STATE, AT ITS SOLE DISCRETION, SHALL RESERVE THE RIGHT TO MAKE ONE OR MULTIPLE AWARDS FOR THIS REQUIREMENT AND/OR TO REJECT ANY OR ALL BIDS.

#### **AUTO / VEHICLE PURCHASE ORDER**

THE FOLLOWING ADDITIONAL TERMS AND CONDITIONS APPLY TO THIS PURCHASE ORDER: 1. ALL VEHICLES MUST BE DELIVERED WITHOUT DEALER'S NAME OR ADVERTISING OF ANY TYPE VISIBLE ON THE BODY. 2. EACH VEHICLE DELIVERED TO THE STATE MUST BE ACCOMPANIED BY A "CERTIFICATE OF ORIGIN" CONTAINING THE MANUFACTURER'S VEHICLE IDENTIFICATION NUMBER (VIN), THE NUMBER OF ENGINE CYLINDERS AND ENGINE TYPE, A GENERAL DESCRIPTION OF THE BODY, AND THE MODEL NAME OR NUMBER. CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO STATE OF RI/FLEET OPERATIONS, ONE CAPITOL HILL, PROVIDENCE, RI 02908 UNLESS THE VEHICLE IS BEING PURCHASED BY THE RHODE ISLAND STATE POLICE. IF SO, CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO RHODE ISLAND STATE POLICE, 311 DANIELSON PIKE, NORTH SCITUATE, RI 02857. 3. THE VENDOR MUST WARRANT FULL AND UNENCUMBERED TITLE TO THE VEHICLE(S) AS OF THE DATE OF DELIVERY TO THE STATE. 4. TITLE CERTIFICATES MUST BE PROVIDED AT THE TIME OF DELIVERY TO THE STATE.

#### **VENDOR SPECIFICATIONS**

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.

END DOCUMENT