August 16, 2013

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATION
DEPARTMENT OF ADMINISTRATION

DIVISION OF PURCHASES BID NO. 7484377

RHODE ISLAND DEPARTMENT OF TRANSPORTATION

RHODE ISLAND CONTRACT NO.2013-CR-090

FEDERAL-AID PROJECT NO. FAP Nos: STP-RESF(264)

2013 Crack Sealing North & East

North & East Regions

CITY/TOWN OF Burrillville, Cumberland, East Providence, Foster, Glocester, Jamestown, Johnston, Lincoln, Middletown, North Providence, Portsmouth, Providence, Scituate, Smithfield

COUNTY OF PROVIDENCE, NEWPORT

NOTICE TO PROSPECTIVE BIDDERS

ADDENDUM NO. 1 Prospective bidders and all concerned are hereby notified of the following changes in the Plans, Specifications, Proposal and Distribution of Quantities for this contract. These changes shall be incorporated in the Plans, Specifications, Proposal and Distribution of Quantities, and shall become an integral part of the Contract Documents.

A. Specification Change/Addition

1. Job Specific

Delete page JS-3 and replace with the revised page JS-3 (R-1) attached to this addendum. The Modified Asphalt Binder paragraph has been revised.

Robert Kochis

For: RI Department of Transportation
Chief Engineer

408.9901

CLEANING AND SEALING CRACKS IN BITUMINOUS CONCRETE PAVEMENT: CRACKS LESS THAN ONE INCH IN WIDTH

408.9902

CLEANING AND SEALING CRACKS IN BITUMINOUS CONCRETE PAVEMENT: CRACKS ONE INCH AND OVER IN WIDTH

Section 408.02.1 b. 1. Modified Asphalt Binder - This shall consist of a blend of modified binder and crumb rubber, which are chemically bonded to produce a modified asphalt binder. The original modified binder, before being blended with rubber, shall meet the requirements of PG 64-28, Grade E as specified in AASHTO M 320 and MP 19. The non-recoverable creep compliance versus percent recovery of the binder shall fall above the curve in Figure X2.1 in Appendix X2 of TP-70 when plotted. The modified asphalt binder shall not contain any particles of rubber or elastomeric material when tested in accordance with AASHTO T 44. The modified asphalt binder shall at a minimum consist of 7% crumb rubber from tires. The supplier of the modified asphalt binder shall certify the composition and PG grade of the material.

Section 408.02.1 b. 2. Asphalt Cement Delete "(AASHTO MP1)" and replace with "(AASHTO M320)".

Section 408.02.3 Blotter Material. Delete "black beauty" and replace with "3060 granulated coal slag abrasive (Black Beauty)"

Section 408.04.1. Change section title from "**Cracks Less than One Inch in Width**" to "**Cracks 1/16" to Less than One Inch in Width**". Under the first sentence change "Cracks Less than…" to "Cracks 1/16" to Less than…"

Section 408.05.1. Change section title from "**Cracks Less than…**" to "**Cracks 1/16" to Less than…**" Change last sentence to "**Initial sweeping of the pavement will be incidental**".

Section 408.05.2. Change last sentence to "**Initial sweeping of the pavement will be incidental**".

Addendum No. 1 **(R-1)**