



Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
ONE CAPITOL HILL
PROVIDENCE RI 02908

CREATION DATE : 18-OCT-13
BID NUMBER: 7527365
TITLE: FURNISH AND INSTALL VEHICLE LIFTS - DOT

BID CLOSING DATE AND TIME:08-NOV-2013 10:30:00

BUYER: Hill, Lisa
PHONE #: 401-574-8118

**B
I
L
L

T
O**
DOT ACCOUNTS PAYABLE
TWO CAPITOL HILL, RM 243
SMITH ST
PROVIDENCE, RI 02903
US

**S
H
I
P

T
O**
DOT MAINTENANCE BUSINESS OFFICE
360 LINCOLN AVE
WARWICK, RI 02888
US


Requisition Number: 1319786

Line	Description	Quantity	Unit	Unit Price	Total
1	DOT; FURNISH AND INSTALL ONE VEHICLE LIFT @ DOT EAST PROVIDENCE FACILITY	1.00	Each		
2	DOT; FURNISH AND INSTALL ONE VEHICLE LIFT @ DOT BELLEVILLE FACILITY	1.00	Each		
3	DOT; FURNISH AND INSTALL ONE VEHICLE LIFT @ DOT HOPE VALLEY FACILITY	1.00	Each		
4	DOT; FURNISH AND INSTALL ONE VEHICLE LIFT @ DOT GLOCESTER FACILITY	1.00	Each		
5	DOT; FURNISH AND INSTALL ONE VEHICLE LIFT @ DOT SMITHFIELD FACILITY	1.00	Each		

Delivery: _____

Terms of Payment: _____

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer



STATE OF RHODE ISLAND
DIVISION OF PURCHASES
BID NO. 7527365 - VEHICLE LIFTS

The State of Rhode Island Division of Purchases, on behalf of the Department of Transportation, is soliciting bids for the purchase and installation of five (5) 18,000 lb. four-post surface mounted vehicle lifts which are to be installed at five different facility locations throughout the state. It is the intent to issue one award for all five locations, however the State reserves the right to issue awards for separate locations, whichever is in its best interest.

The awarded vendor must be responsible for a turnkey installation. If subcontracting of installation is intended, the installer must be an authorized representative of the manufacturer, and evidence of such must be disclosed in the bid response.

Bid surety from each bidder, in the amount of 5% (five percent) of the total bid must be submitted with the vendor's bid response. The surety must be submitted in the form of a bid bond, or a certified check payable to the State of Rhode Island and must be attached to the bid form. The successful bidder will also be required to furnish 100% performance and labor and payment bonds at time of tentative award.

LOCATIONS:

DOT SMITHFIELD FACILITY
395 GEORGE WASHINGTON HIGHWAY
SMITHFIELD, RI

DOT GLOCESTER FACILITY
648 PUTNAM PIKE
GLOCESTER, RI

DOT HOPE VALLEY FACILITY
51 BANK STREET
HOPE VALLEY, RI

DOT EAST PROVIDENCE FACILITY
691 WARREN AVENUE
EAST PROVIDENCE, RI

DOT BELLEVILLE FACILITY
439 TOWER HILL ROAD
NORTH KINGSTOWN, RI

RHODE ISLAND DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAY AND BRIDGE MAINTENANCE
VEHICLE LIFT SPECIFICATIONS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Vehicle lifts including safety equipment, controls and accessories.
- B. The Rhode Island Department of Transportation (RIDOT) Division of Highway and Bridge Maintenance seeks to purchase five (5) vehicle lifts including all items listed in this solicitation and installation at five (5) different facilities located statewide.

1.2 REFERENCES

- A. ALI: Automotive Lift Institute.
- B. ANSI/ALI ALCTV: Safety Requirements for the Construction, Testing, and Validation of Automotive Lifts.
- C. International Standards Organization (ISO): ISO 9001 Quality management systems - Requirements.
- D. Underwriters Laboratories Inc. (UL): UL201 - These requirements cover garage equipment, rated not more than 600 volts, for use in accordance with the National Electrical Code, NFPA 70.

1.3 REQUIRED SUBMITTALS

- A. Product Data: Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation manual.
 - 4. Operations manual.
 - 5. Maintenance manual.
 - 6. Safety manual.
- B. Shop Drawings: Template drawings and load reactions for lift application.

1.4 QUALITY ASSURANCE

- A. Installer Qualifications:
 - 1. The installer shall be a factory trained and authorized company.
 - 2. The installer shall be insured for completed operations of installing lift.

- B. In addition to the other requirements outlined herein, the lifts, shall comply with all applicable requirements of ANSI standards. "Safety Requirements for the Construction, Care and Use of Automotive Lifts" as published by the American national Standards Institute. The lift company Quality Management System shall be ISO9001 certified.

1.5 PROJECT CONDITIONS

- A. Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's absolute limits.

1.6 WARRANTY

- A. Contractor/manufacturer/installer has responsibility for an extended Corrective Period for work of this Section for the period stated from date of Substantial Completion against deficiencies as stated in the manufacturer's standard warranty. This period shall not be less than one (1) year.
- B. Contractor/manufacturer/installer shall promptly and without inconvenience and cost to Owner correct said deficiencies:
 - 1. Failure due to defective materials and workmanship.
- C. Contractor/manufacturer/installer shall be notified immediately of defective products, and be given a reasonable opportunity to inspect the goods prior to return. Manufacturer will not assume responsibility, or compensation, for unauthorized repairs or labor.

PART 2 PRODUCTS

2.1 18,000 LB. FOUR POST SURFACE MOUNTED; DRIVE ON GENERAL SERVICE LIFTS

(2) 18,000 LB.
ROLLING JACKS

- A. Capacity: 18,000 lb (8165 kg); 9,000 lb (4082 kg) per runway.
- B. Single Point Manual Controls - Pneumatic 100 psi - 120 psi Air Required, Lock Release Electric Power Unit, UL201 Compliant, Over Hydraulic Cylinder Drive: All models bio-fluid compatible.
 - 1. 2hp 208-230V 1 phase Motor 60Hz.
- C. Minimum Bay Requirements:
 - 1. Floor space 16 feet x 27 feet (4877mm x 8230 mm).
 - 2. Floor slab concrete 3000 psi - 4-1/4 inch (108 mm) minimum; 5 inch - 6 inch (127 mm - 152 mm).
- D. Rise: 68 inches (1727 mm) from floor to top of runway.
- E. Overall Length:
 - 1. 275-3/16 inches (6990 mm) ramp to runway.
- F. Overall Width: 137-3/4 inches (3499 mm).

- G. Inside of Columns: 121-1/2 inches (3086 mm).
- H. Between Front and Rear Columns:
 - 1. 212 inches (5385 mm).
- I. Height of Columns: 77-3/4 inches (1975 mm).
- J. Width of Runways: 22 inches (559 mm).
- K. Height of Runways: 7-1/2 inches (191 mm).
- L. Width Between Runways: 43 to 46 inches (1092 to 1168 mm).
- M. Maximum Wheelbase:
 - 1. 194 inches (4928 mm).
- N. Finishes:
 - 1. Blue, Standard RAL5005.
- O. Additional Required Accessories:
 - 1. Rolling Jacks 9000 LB (4082 kg) capacity (each) 100 psi minimum - 120 psi maximum required.
 - 2. Internal Air Line Kit 100 psi minimum - 120 psi maximum required.
- P. Lift shall be 3rd party certified by ETL testing laboratory and labeled with the ETL/Automotive Lift Institute (ALI) label that affirms the lifts meet conformance to all applicable provisions of American National Standard ANSI/ALI ALCTV-2006 and in compliance with IBC 2003, IBC 2006 chapter 30 section 3001.2.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until supporting structures have been properly prepared.
- B. If supporting structure preparation is the responsibility of another installer, notify RIDOT of unsatisfactory preparation before proceeding.

3.2 INSTALLATION

- A. Install in accordance with manufacturer instructions.
- B. Installer shall provide RIDOT with the electrical requirement specifications immediately upon notification of award and prior to shipping.

3.3 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

Contract Terms and Conditions

Table of Contents

Terms and Conditions.....VIII
 BID STANDARD TERMS AND CONDITIONSVIII
 TERMS AND CONDITIONS FOR THIS BIDVIII
 SURETY REQUIREMENTSVIII
 BOND REQUIRED (PERFORMANCE & LABOR/PYT)VIII
 INSURANCE REQUIREMENTSVIII
 DELIVERY PER AGENCYVIII

Terms and Conditions

BID STANDARD TERMS AND CONDITIONS

TERMS AND CONDITIONS FOR THIS BID

SURETY REQUIREMENTS

BIDDER IS REQUIRED TO PROVIDE A BID SURETY IN THE FORM OF A BID BOND, OR A CERTIFIED CHECK PAYABLE TO THE STATE OF RHODE ISLAND, IN THE AMOUNT OF A SUM NOT LESS THAN FIVE PERCENT (5%) OF THE BID PRICE. BID SURETY MUST BE ATTACHED TO THE BID FORM. THE SUCCESSFUL BIDDER WILL ALSO BE REQUIRED TO FURNISH PERFORMANCE AND LABOR AND PAYMENT BONDS AT TIME OF TENTATIVE CONTRACT AWARD.

BOND REQUIRED (PERFORMANCE & LABOR/PYT)

NO BID SURETY REQUIRED TO BE SUBMITTED WITH BID. HOWEVER, THE SUCCESSFUL BIDDER WILL BE REQUIRED TO FURNISH PERFORMANCE AND LABOR AND PAYMENT BONDS AT TIME OF TENTATIVE CONTRACT AWARD.

INSURANCE REQUIREMENTS

AN INSURANCE CERTIFICATE IN COMPLIANCE WITH PROVISIONS OF ITEM 31 (INSURANCE) OF THE GENERAL CONDITIONS OF PURCHASE IS REQUIRED FOR COMPREHENSIVE GENERAL LIABILITY, AUTOMOBILE LIABILITY, AND WORKERS' COMPENSATION AND MUST BE SUBMITTED BY THE SUCCESSFUL BIDDER(S) TO THE DIVISION OF PURCHASES PRIOR TO AWARD. THE INSURANCE CERTIFICATE MUST NAME THE STATE OF RHODE ISLAND AS CERTIFICATE HOLDER AND AS AN ADDITIONAL INSURED. FAILURE TO COMPLY WITH THESE PROVISIONS MAY RESULT IN REJECTION OF THE OFFEROR'S BID. ANNUAL RENEWAL CERTIFICATES MUST BE SUBMITTED TO THE AGENCY IDENTIFIED ON THE PURCHASE ORDER. FAILURE TO DO SO MAY BE GROUNDS FOR CANCELLATION OF CONTRACT.

NOTE: IF THIS BID COVERS CONSTRUCTION, SCHOOL BUSING, HAZARDOUS WASTE, OR VESSEL OPERATION, APPLICABLE COVERAGES FROM THE FOLLOWING LIST MUST ALSO BE SUBMITTED TO THE DIVISION OF PURCHASES PRIOR TO AWARD: * PROFESSIONAL LIABILITY INSURANCE (AKA ERRORS & OMISSIONS) - \$1 MILLION OR 5% OF ESTIMATED PROJECT COST, WHICHEVER IS GREATER. * BUILDER'S RISK INSURANCE - COVERAGE EQUAL TO FACE AMOUNT OF CONTRACT FOR CONSTRUCTION. * SCHOOL BUSING - AUTO LIABILITY COVERAGE IN THE AMOUNT OF \$5 MILLION. * ENVIRONMENTAL IMPAIRMENT (AKA POLLUTION CONTROL) - \$1 MILLION OR 5% OF FACE AMOUNT OF CONTRACT, WHICHEVER IS GREATER. * VESSEL OPERATION - (MARINE OR AIRCRAFT) - PROTECTION & INDEMNITY COVERAGE REQUIRED IN THE AMOUNT OF \$1 MILLION.

DELIVERY PER AGENCY

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.