



State of Rhode Island
Department of Administration / Division of Purchases
One Capitol Hill, Providence, Rhode Island 02908-5855
Tel: (401) 574-8100 Fax: (401) 574-8387

ADDENDUM #1

RFP # 7548845

TITLE: AERIAL BUCKET LIFT TRUCK

SUBMISSION DEADLINE: 7/18/14 – 10:00 A.M.

Prospective bidders and all concerned are hereby advised of the attached changes/modifications for the above referenced RFQ and are hereby requested to change their copies accordingly.

- ATTACHED ARE THE SPECIFICATIONS WHICH WERE INADVERTENTLY OMITTED FROM THE SOLICITATION PACKAGE. THESE SPECIFICATIONS MUST BE COMPLETED AND RETURNED WITH THE BID.



Lisa Hill
Chief Buyer

Bidders must include a signed copy of this addendum with their proposal submission as acknowledgement.

Company Name (print)

Signature of Authorized Representative

DESCRIPTION: _____

Quantity:	1		Vendor Indicate Compliance Yes/No
Department:	DOT	Fuel Type:	Diesel
Division:	BRIDGE INSPECTION	Color: <small>*if not offered may be changed at award</small>	White
RI-FANS Requisition Number:			

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	Yes/No	Specify Alternative (if responding no)
ENGINE 6.7L V8 OHV		
ALTERNATOR Dual alternator 357 amps		
BATTERY dual batteries 750 amp total 78Ah with run down protection		
BRAKES power assisted ABS 4 wheel disk		
HUB CAPS MANUFACTURERS STANDARD		
BUMPERS Front bumper w/tow hooks with rear step bumper		
COOLING SYSTEM heavy duty		
FLOOR vinyl/rubber flooring covering		
FUEL TANK 40 gallon minimum		
GW 19,500lbs		
GAUGES Analog display w/tach, oil pressure, engine temp, turbo boost and trans temp		
GLASS Tinted		
LIGHTS Headlights, stoplights and directionals		
HEATER/DEFROSTER including AC		
MIRRORS Folding manual extendable outside mirrors		
RADIO MANUFACTURERS STANDARD AM/FM		
AIR CONDITIONING		
SEATING 2 front bucket seats		
WINDSHIELD WIPERS variable intermittent		
HUB CAPS/WHEEL COVER		
STEERING		

RI-FANS Requisition Number: _____

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	↓ Yes/No	↓ Specify Alternative (if responding no)
Fiberglass service body 60" cab to axle 108" overall length		
Overall width: 94"		
Pack depth: 20"		
Floor width: 54"		
Pack height: 42"		
Mounting height: 25"		
Steel understructure		
Aluminum tread plate floor		
Smooth aluminum bulkhead		
Aluminum 6" tailskirt		
Standard bright white gelcoat		
Stainless steel rotary latch		
Type 304 stainless steel hardware		
Type 304 stainless steel door hinge		
Vinyl covered s/s cable door stops		
Gas prop door retainers (verticals)		
Clear vinyl rock guards		
Black plastic fuel bezel		
Automotive grade bubble gasket		
One piece molded doors with automotive finish		
Recessed door jambs		
Flow through ventillation system		
Removable wheel well panels		
White compartment interiors		
Steel rear mounting brackets		
Recessed door seal system		
Light adaptor for specified chassis		
Full LED lighting package: stop/tail/turn/ marker and back up light in rear of body		
Flexglo compartment lighting top and sides of door (all compartments)		
Loadwall liner, aluminum in loadbed		
Compartment tops to be aluminum treadplate		
Curbside front compartment: 2 adj. shelves		
Curbside horizontal compartment: 1 adj. shelf		
Curbside rear compartment: 2 adj. shelves		
Streetside front compartment: 2 adj. shelves		
Streetside horizontal compartment: 1 adj. shelf		
Streetside rear compartment: 2 adj. shelves		

RI-FANS Requisition Number: _____

STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE	
	Yes/No	Specify Alternative (if responding no)
PTO and Pump (3GPM)		
30" tread plate tailshelf with curbside access step		
Frame extension to accept tailshelf, painted		
Trailer plug 7 way RV type with adaptor for 4-7"		
Combo hitch		
Two (2) mudflaps		
Ladder rack-aluminum angled above cab, able locking		
Non skid rubberized coating		
Back up alarm		
Two (2) recessed LED load bed lights, switched		
Biodegradable environmentally safe hydraulic fluid		
Required ANSI safety and warning decals		
Fabric control cover for upper controls		
Stability test of completed unit		
Dielectric test of completed unit		
DOT kit: first aid kit, fire extinguisher and flare kits		
Two (2) wheel chocks, grip strut w/brackets under tailshelf		
Wire compartment light switches to upfitter switches		
Remove center console		
Install and supply traffic advisor on light troth of tailshelf, control in cab		
Custom steel cab guard formed to bumep of chassis		
Two (2) 4" round LED strobes in rear of compartments		
Four (4) 3" mini strobes (2 in front, 2 in rear)		
Eight (8) LED amber warning lights		
Eight (8) mounting flanges		
Console enclosure		
Book pocket		
Switch panel, switches, console mounted		
Radio bezel		
Computer/tablet docking station		
Install DOT supplied radio into centerconsole and mount DOT antenna		
Mount antenna for computer/lap top		
Stream lite charger		
Removable bucket mounting bracket		
3000 watt pure sine wave inverter with support package: 2 deep cycle batteries, battery boxes, fuses, cables, isolator/in power and boost		
Electrical rewind cord reel with 150-200ft extension		
Two (2) LED flood lights		
Graphics, Z stripe Rhode Island blue		
Cone holder		