


STATE OF RHODE ISLAND  
DIVISION OF PURCHASES



Solicitation Information  
2/6/15

RFP#7549322

TITLE: HEAVY DUTY TANDEM DUMP TRUCKS (SIX-WHEELERS)

Submission Deadline: Tuesday, March 10, 2015 at 2:00 p.m.  
Mandatory Pre-Bid Conference: Friday, February 20, 2015 at 10:00 a.m.  
Location: RIDOT Maintenance Headquarters, 360 Lincoln Ave, Warwick, RI

Questions concerning this solicitation must be received by the Division of Purchases at [@purchasing.ri.gov](mailto:@purchasing.ri.gov) no later than DATE (EST). Questions should be submitted in a *Microsoft Word attachment*. Please reference the RFP# on all correspondence. Questions received, if any, will be posted on the Internet as an addendum to this solicitation. It is the responsibility of all interested parties to download this information.

SURETY REQUIRED: No

BOND REQUIRED: No

Lisa Hill  
Chief Buyer

Applicants must register on-line at the State Purchasing Website at [www.purchasing.ri.gov](http://www.purchasing.ri.gov)

**Note to Applicants:**

Offers received without the entire completed three-page RIVP Generated Offerer Certification Form attached may result in disqualification.

**THIS PAGE IS NOT A OFFERER CERTIFICATION FORM**

**TABLE OF CONTENTS**

Section 1 – Introduction	3
Section 2 - Background and Purpose	5
Section 3 - Scope of Work (Specifications)	5
Section 4 - Technical Proposal	21
Section 5 - Cost Proposal	21
Section 6 - Evaluation and Selection	21
Section 7 - Proposal Submission	23

## SECTION 1: INTRODUCTION

The Rhode Island Department of Administration/Division of Purchases, on behalf of the Rhode Island Department of Transportation (TRANSPORTATION), is soliciting proposals from qualified firms for the purchase of **Five (5) Six-Wheel Dump Trucks** as described elsewhere herein, in accordance with the terms of this Request for Proposals and the State's General Conditions of Purchase, which may be obtained at the Rhode Island Division of Purchases Home Page by Internet at [www.purchasing.ri.gov](http://www.purchasing.ri.gov). The successful offerer must be an Authorized Manufacturer or Authorized Manufacturer Representative.

The Authorized Manufacturer or Authorized Manufacturer Representative will be responsible for the maintenance of the entire vehicle and all optional equipment.

No alternatives to the specifications will be accepted. All proposals must meet or exceed specifications. Only one (1) set of specifications will be accepted per offerer.

Delivery must be completed within one hundred eighty (180) days of the successful proposal.

This is a Request for Proposals, not an Invitation for Proposal. Responses will be evaluated on the basis of the relative merits of the proposal, in addition to price; there will be no public opening and reading of responses received by the Division of Purchases pursuant to this Request, other than to name those offerors who have submitted proposals.

### **INSTRUCTIONS AND NOTIFICATIONS TO OFFERORS:**

1. Potential vendors are advised to review all sections of this RFP carefully and to follow instructions completely, as failure to make a complete submission as described elsewhere herein may result in rejection of the proposal.
2. Alternative approaches and/or methodologies to accomplish the desired or intended results of this procurement are solicited. However, proposals which depart from or materially alter the terms, requirements, or scope of work defined by this RFP will be rejected as being non-responsive.
3. All costs associated with developing or submitting a proposal in response to this RFP, or to provide oral or written clarification of its content shall be borne by the vendor. The State assumes no responsibility for these costs.
4. Proposals are considered to be irrevocable for a period of not less than **60** days following the opening date, and may not be withdrawn, except with the express written permission of the State Purchasing Agent.
5. All pricing submitted will be considered to be firm and fixed unless otherwise indicated herein.

6. Proposals misdirected to other state locations, or which are otherwise not present in the Division at the time of opening for any cause will be determined to be late and will not be considered. For the purposes of this requirement, the official time and date shall be that of the time clock in the reception area of the Division.
7. It is intended that an award pursuant to this RFP will be made to a prime vendor, who will assume responsibility for all aspects of the work. Joint venture and cooperative proposals will not be considered. Subcontracts are permitted, provided that their use is clearly indicated in the vendor's proposal and the subcontractor(s) to be used is identified in the proposal.
8. All proposals should include the vendor's FEIN or Social Security number as evidenced by a W9, downloadable from the Division's website at [www.purchasing.ri.gov](http://www.purchasing.ri.gov).
9. The purchase of goods/services under an award made pursuant to this RFP will be contingent on the availability of funds.
10. Vendors are advised that all materials submitted to the State for consideration in response to this RFP will be considered to be Public Records as defined in Title 38, Chapter 2 of the General Laws of Rhode Island, without exception, and will be released for inspection immediately upon request once an award has been made.
11. Interested parties are instructed to peruse the Division of Purchases website on a regular basis, as additional information relating to this solicitation may be released in the form of an addendum to this RFP.
12. Equal Employment Opportunity (G.L. 1956 § 28-5.1-1, et seq.) – § 28-5.1-1 Declaration of policy – (a) Equal opportunity and affirmative action toward its achievement is the policy of all units of Rhode Island state government, including all public and quasi-public agencies, commissions, boards and authorities, and in the classified, unclassified, and non-classified services of state employment. This policy applies to all areas where State dollars are spent, in employment, public services, grants and financial assistance, and in state licensing and regulation. For further information, contact the Rhode Island Equal Opportunity Office at (401) 222-3090.
13. In accordance with Title 7, Chapter 1.2 of the General Laws of Rhode Island, no foreign corporation, a corporation without a Rhode Island business address, shall have the right to transact business in the State until it shall have procured a Certificate of Authority to do so from the Rhode Island Secretary of State (401-222-3040). This is a requirement only of the successful vendor(s).

## **SECTION 2: BACKGROUND**

The Rhode Island Department of Transportation is seeking to contract with a vendor with demonstrated proficiency in Six-Wheel Dump Trucks.

The Department expects to contract for a minimum of five (5) units. The vendor cost proposal will represent one total cost, not itemized.

Although cost is a significant consideration, warranty/warranty resolution; availability of parts; delivery schedule/significant milestones and overall quality of the work plan; and experience, capability, capacity, and qualifications of the offeror are also critical to the procurement of the six-wheel dump trucks.

## **SECTION 3: SCOPE OF WORK (SPECIFICATIONS)**

### **General Scope of Work**

The following specifications and dimensions shall apply to purchases of HEAVY DUTY TRUCK (6-WHEELER) for the Rhode Island Department of Transportation. The State reserves the right to waive minor technicalities under this specification. Federal and State laws supersede any conflicting part of this specification.

RIDOT desires to purchase five (5) units through this RFP, subject to availability of funds.

The unit shall be a current model, new and unused, under standard production by the manufacturer, and of which parts are stocked at one or more locations in Rhode Island and/or Southern New England region. All parts utilized on the unit shall be new and unused.

The bidder agrees, if his proposal is accepted, to guarantee the design, material and workmanship of the unit bid according to the standard factory warranty, or detailed in the following specification, whichever is greater. A copy of the warranty shall accompany the bid. Warranty coverage shall include costs of transporting the unit to and from servicing shop, when outside a 50 mile radius of the delivery point. The bidder shall be responsible for pickup and delivery (including fuel) of any units that are found to have defects within the first three (3) weeks of delivery to RIDOT and have to return to dealer for repairs.

Complete specifications and literature on the unit bid shall accompany the bid. Any exceptions to these specifications shall be indicated on the bid or on a separate attachment to the bid, labeled as such.

Any "or equal" or "equivalent" items for brand specified components shall be listed with the bid package. Complete description and literature on the "or equal" components shall be supplied for consideration by the RIDOT. The burden of proof regarding "or equal" items will be upon the vendor.

**GENERAL:** This specification is intended to allow competitive bids on the following manufacturers or approved equal: International Workstar, Freightliner 114SD, Peterbilt 348, and Mack Granite.

**PRIMARY PURPOSE:** Units are utilized primarily for Winter Operations and must be suitable to be outfitted with Dump Body, V- Sander, saddle tanks, front plow, and wing plow.

**MANDATORY PRE-BID CONFERENCE** Friday, 2/20/15 – 10:00 a.m.  
DOT Maintenance, 360 Lincoln Avenue  
Warwick, RI

**PRE-DELIVERY SERVICE:** The unit shall be delivered complete and fully operational. It shall be properly serviced, free of leaks, with all mechanical adjustments made prior to delivery. A copy of the line set ticket shall accompany the vehicles. A minimum of three days notice prior to delivery shall be given to the person to whom the unit is to be shipped. Upon award of the bid the successful bidder shall supply a completed RIDOT “Equipment Information” sheet listing all the pertinent details that are specific to the units being purchased. Failure to do so will result in 2% retention of the total order.

All units must be inspected prior to delivery with a focus on functionality, consistency, and quality assurance. **The body installation company must develop an inspection check sheet that is detailed and includes all major components of each dump truck.** Each inspection item must be initialed and a copy of the inspection sheet shall be placed in the document holder of the truck prior to delivery. The inspection check sheet shall be developed and presented at the body company prototype meeting for review and input from RIDOT. The inspection check sheet shall be developed and presented at the final prototype meeting for review and input from RIDOT.

All units must be inspected prior to delivery with a focus on functionality, consistency, and quality assurance just before final delivery. **The bidder must develop an inspection check sheet that is detailed and includes all required pre delivery inspection and service items required by the chassis supplier.** This inspection check list should also include checking items that may have loosened or have been missed by the body company such as hydraulic leaks and body components shaking loose. Each inspection item must be initialed and a copy of the inspection sheet shall be placed in the document holder of the truck prior to delivery.

#### **TRUCK DELIVERY SCHEDULE**

All bidders shall provide as part of their bid a schedule for the delivery of all trucks to RIDOT. This date shall be listed as the number of days following issuance of a Notice to Proceed, that the bidder shall successfully deliver all units to the Rhode Island Department of Transportation. Failure to submit a schedule will result in the bid being considered non-responsive. Failure to meet the schedule will result in 3% retention on the total order.

## **2015 MODEL YEAR CAB & CHASSIS 6-WHEEL TRUCK**

### **A. Dimensions/G.V.W**

GVW rating 47,000 lbs minimum  
Wheelbase 177" minimum  
CA dimension 110"- to be verified by body builder  
Platform 159" LP with 49" AF to be verified by body builder

### **B. Frames**

Single rail 120,000 psi steel  
Section Modulus 22.12  
REM 2,654,400  
20" integral frame extension (not bolted)  
Swept back bumper  
Two front tow hooks  
Two rear tow hooks

### **C. Engine Diesel/Engine Equipment**

Minimum 360, HP @ 1700 rpm minimum  
1450 ft/lbs torque minimum  
Inside/outside air intake with in-cab controls  
120V/1500W engine block heater w/receptacle under driver door  
15.9 CFM compressor;  
Bug screen mounted behind grille  
Silicone engine hoses  
DPF regeneration control  
Engine shut down for low engine oil pressure, high coolant temperature and low coolant level  
Davco FuelPro 382 fuel/water separator with thermostat control  
Engine compression brake (Jake Brake) with on/off switch  
Exhaust-single RH vertical with muffler guard and turn back tailpipe  
2015 OBD compliant  
2015 Federal emission compliant

### **D. Transmission and Equipment/Drivelines**

Allison 4000-RDS six speed automatic transmission with PTO gear  
Synthetic transmission fluid  
Dash mounted PTO control  
Transmission oil cooler  
Push button shift control

### **E. Axles**

Front axle  
I-beam 20,000 lb capacity  
20,000 lb multi-leaf shackle type springs  
Front RH spring build-up for wing plow to level chassis  
Shock absorbers  
RH auxiliary air bag with driver control for wing plow application  
Synthetic: lube

Rear axle  
30,000 lb single reduction rear axle

Driver controlled locking differential  
31,000 multi-leaf springs with 4,500 lb auxiliary springs  
synthetic lube  
Driveshaft  
Heavy Duty SP1170XL

**F. Brakes**

Front S-cam 16.5x6"  
Rear S-cam 16.5x7" with cast brake drums  
Brake chambers 36"/36" on rear  
Heated air dryer  
Dust shields -front and rear  
Automatic slack adjusters - front and rear  
Anti-lock brake system with traction control  
Full trailer package with air and light lines

**G. Tires**

Front 315/80R22.5 Goodyear G287 load range L/20 ply 10,000 lb weight rating  
Rear 12R24.5 Goodyear G177 Load range H/16 ply  
One front and two rear spare tires and rims matching above  
Front and rear - Wheels shall be powder coated white.

**H. Wheels**

Front steel disc-hub piloted 22.5x9.0" rims  
Rear steel disc-hub piloted 24.5x8.25" rims

**I. Electrical System**

Twelve volt negative ground electrical system  
160 amp alternator  
Three maintenance free batteries - total 1950 CCA  
Stop, turn, tail and backup lights  
Body builder wiring for body installation

All lights and reflectors shall conform to the motor vehicle laws of the State of Rhode Island.

**J. Fuel System**

100 gallon aluminum fuel tank  
9.5 gallon DEF tank

**K. Cab**

Conventional steel cab includes rust prevention  
Tinted windshield and glass  
LH & RH interior cab access grab handles with additional driver side outside handle  
Fiberglass tilt hood and fenders with frame mounted splash shields  
Engine access hatch  
ICC clearance, lights  
Long life Halogen headlights that turn on when windshield wipers are 'turned on  
Chrome stationary grille  
Sound abatement-extra insulation under hood and splash panels  
Heated LH &'RH west coast mirrors with integral convex mirrors  
Frame mounted air' horn  
Radio AM/FM/CD with weather  
band

Winter wiper blades  
Power windows/ Power Locks

#### **L. Paint**

Cab shall be White over proper primer for cab and sheet metal. No other color will be accepted by RIDOT, chassis and running gear shall be black. Wheels shall be powder coated white.

#### **M. Accessories**

Two wheel chocks  
Fire extinguisher - #5 ABC  
Three safety triangles  
Three sets keys  
Fender extensions for front tires  
Textured Poly Single Axle Fenders  
Back-up alarm  
In cab power source  
Air conditioning  
Driver side air ride seat  
One First-Aid Kit  
One Spill Response Kit  
800 MHz digital radio (See attached specifications for ONLY ACCEPTABLE Motorola Astro XTL 1500)  
Ignition keyed synonymously with all vehicles  
Floor Mats  
Heated Mirrors

#### **: Note all hoses and wiring have to be water tight and loomed:**

An infrared pavement temperature sensor shall be properly mounted per the manufacturer's recommendations. The gauge shall be mounted in a visible location integrated into the dash layout or as part of spreader control and shall display both air and pavement temperature simultaneously. To be a Sprague Roadwatch (800 441-2048) or Quixote Transportation Technologies Surface Patrol or approved equal.

A lockable weatherproof toolbox with T-handle latches shall be mounted to the frame on the curb side, under the body. The toolbox shall be approximately 36 inches long by 18 inches high by 18 inches wide. To be constructed of 12 gauge 201 Stainless Steel minimum, with curbside opening steel door with stainless steel piano hinge. Front panel shall have exterior jam lip designed to deflect water away from the door opening. Edges of door shall seal tightly against weather stripping and chain door retainer. Two keys shall be provided with each unit. The unit shall be bolted to the frame using cradle type mounting brackets.

#### **N. Warranties**

Engine – Please provide warranty information (complete engine including injectors, turbocharger, electrical harnesses, lines and tubes – 100% parts and labor). Exceptions are: aftertreatment system components and related sensors and EA harnesses which shall be covered under separate warranties.

Engine Aftertreatment system and EA Harness and sensors – 60 months/100,000 miles – 100% parts and labor

Chassis - "Bumper to bumper" - 60 months/100,000 miles – 100% parts and labor - including components (but not limited to) such as radiators, cab, suspension, and electrical.

Transmission – 60 months/no mileage limits – 100% parts and labor

No engine hour limitation in above warranties

A breakdown of the standard manufacturer's warranty when it is in excess of the 2 years requested shall be listed for each component of the cab and chassis and included in the manual set.

### **O. Training**

A 3 day, "hands on" technician training session shall be provided at RIDOT Division of Highway & Bridge Maintenance Headquarters. The training session topics will be coordinated through RIDOT Motor Pool section and may include but are not limited to diesel engine tune-up and maintenance, multiplex systems, and use of purchased software. The training session shall accommodate at least 12 RIDOT employees at each session. Training shall be provided approximately 3 weeks after delivery of the first unit.

There shall be a one day (1) seminar, to instruct RIDOT personnel on the operation, servicing and repair of the hydraulic system, at each delivery location. 1/2 of the day shall be for operator training and the other ½ for mechanics. This seminar is separate from the training required on above covering the truck package excluding the hydraulics. A web broadcast shall be an allowed method of conducting this seminar.

A follow up session is required for operators after the trucks have been used one winter season. These sessions are to be held Division of Highway & Bridge Maintenance Headquarters. The operator's session is to be approximately 4 to 6 hours.

All training sessions shall be scheduled on a date mutually agreed upon by RIDOT and the hydraulics supplier. All training sessions shall be performed by competent technician thoroughly trained in the use, service, and operation of the unit.

### **P. Hydraulics**

If the hydraulic component supplier is different than the supplier of the spreader controller, the truck equipment company (body installer) shall take responsibility for coordinating efforts of the two suppliers. It will be the responsibility of the truck equipment company to ensure that the total hydraulic package functions as intended.

The control valve system shall be enclosed in a stainless steel box with side opening weather resistant lid, mounted behind the cab on the left side frame rail in a location where the manual overrides can be accessed. The lid shall be removable without the use of tools and shall

provide for maximum access to the valve. A legend describing each valves operation shall be stuck on the inside of the lid. Enclosure shall be integrated with the hydraulic reservoir.

**Q. Software, Manuals, Laptop**

Vendor shall provide current editions of all relevant cab and chassis manuals. This must include but not be limited to overhaul and tune-up manuals, diagnostic, wiring, troubleshooting, and parts manuals for engine, transmission, differential and all components.

One (1) Panasonic "Toughbook" lap-top/tablet computer, Windows 7 compatible shall be provided with the capability to interface with the vehicle.

Chassis manufacturer's diagnostic software shall be loaded in computer and licensed to the Rhode Island Department of Transportation. Electronic media shall include annual subscription renewals for five (5) year. Electronic media shall be capable of being moved to new computer or reloaded in the event of hard drive crash without additional charges. An example of engine software required would be Cummins Insite Lite, Navistar Service Maxx Fleet Pro, or approved equal.

One operator's manual detailing the recommended operating procedure shall be delivered with each unit.

Sets shall consist of the following: shop manual, parts manual including exploded views of major components with their part numbers, wiring diagram, operator's manual, and a summary of warranties offered in excess of the standard one year.

The manuals shall fully and clearly cover all components of the unit, including the pump, valves, controls, tanks, etc. Manuals shall also include comprehensive trouble shooting and diagnosis information for all functions.

Shop manual shall explain, in detail, procedures for overhauling all major components. Failure to provide manuals may result in 5 percent of total bid.

The content of the set will be evaluated for approval at the prototype approval meeting.

Complete shop drawings for the hydraulic oil supply, control valve box, and control box in the cab, and a complete system schematic shall be submitted to the RIDOT Division of Highway & Bridge Maintenance Administrator for review and approval prior to construction of any of the units.

Manuals shall also cover all allied equipment and components installed on chassis provided by body installer.

Any deviations from this system must be noted on the bid and approved by the RIDOT Division of Highway & Bridge Maintenance Administration. A complete system description and product literature for major components shall accompany the bid.

### **POWER TILT CUSTOM TRUCK PLOW ATTACHMENT SPECIFICATIONS**

The custom truck/plow attachment shall be manufactured by a recognized snowplow manufacturer and shall include 1/2" side plates reinforced and bolted as far back on the truck frame as feasible.

The upper and lower horizontal support members shall be fabricated from not less than 7" x 4" x 3/8" (upper) and 4" x 4" x 3/8" (lower) wall square and rectangular structural tubing. The cylinder base angle shall be fabricated from 4" x 4" x 3/8" tube with 1/2" cylinder connecting lugs. The attachment shall provide a selection of four (4) push heights, two on 30 1/2" and two on 21" hole centers for connection of the plow.

The plow lift cylinder shall be double acting with a 4" bore, 10" stroke, chrome plated piston rod and a polypack seal with a rubber return wiper to clean the piston as it retracts into the cylinder barrel. The base of the cylinder shall attach to the aforementioned horizontal member, while the cylinder rod attaches to a horizontal pivoting lift yoke weldment.

It shall be possible to lockout plow lift action and instead hydraulically tilt the entire center portion of the plow attachment (and any applicable side wing appurtenances) forward so to accommodate a tilt hood truck chassis. This function shall utilize the same cylinder noted above.

In addition, it shall be possible with the removal of four (4) pins to expediently detach the plow lift device (and any applicable side wing appurtenances) from the custom truck attachment for summer truck application.

**HARDWARE PLATING:** All nuts, bolts and chain shall be zinc plated.

**PAINT:** All snowplow components shall be shot blasted and painted with one (1) coat of primer and one (1) coat of finish paint.

**CYLINDER RODS:** All snow plow hydraulic cylinder rods shall be induction hardened and chrome plate to a minimum of 1.0 mm thickness.

**PLOW LIGHTS:** The upper horizontal member shall be fitted with a set of standard elevated 12 volt, hi-low beam plow lights, with quick-disconnect harness.

**BACK UP and WING CAMERAS:** Provide rear view camera that can be incorporated with spreader control monitor. Monitor shall give priority to backup camera when truck is in reverse. **Wing camera strictly to see wing in operational conditions.**

**HEAVY DUTY TRIP EDGE WING:**

Wing: Shall have an overall length of 12 feet, a nose height of 29" and a discharge height of 40 1/4". The moldboard shall be fabricated from 8 gauge HRMS, the top of which shall incorporate an integral channel shaped continuation of the same so to enhance rigidity. The bottom moldboard reinforcement shall be from not less than 5" x 5" x 1/2" structural angle.

Moldboard: Shall be provided with not less than five vertical reinforcing ribs from 1/2" thick plate. Located between the two (2) outside vertical ribs, at the discharge end of the moldboard, shall be four (4) horizontal ribs also from 1/2" thick plate (two upper and two lower): all with a series of vertically punched holes so to provide a selection of attachment points for the upper and lower stand-off arms.

Additionally, the front nose portion of the wing shall include a selection of two (2) 1-9/16" diameter holes for attachment with an 1 1/2" hex head bolt at the front mast hinge.

Carbide Cutting Edge: It shall be (3) piece 3/4" x 6" carbide sections, and shall be bolted to the plow for easy replacement with 5/8" x 2 1/2" Grade 5 carriage bolts and locknuts on 12" centers. Included at the discharge end shall be 10 degree moldboard shoe and shall include a carbon steel backer blade.

The cutting edge reinforcement shall not be less than 4" x 4" x 3/4" angle with 1/2" steel plate reinforcing gussets, welded along its entire length.

The trip mechanism shall be of the single section trip edge type. It shall consist of five (5) 7/8" alloy wire torsion springs with sixteen (16) active coils 17 3/8" long. It shall have two (2) hinge rods made from 1/2" HR steel which slide through the springs and hinge lugs to support the trip edge mechanism. Each spring shall have provision for pre-load adjustment.

Standoff Arm: The standoff arms shall be ruggedly designed with the inner arms fabricated from 2 1/8" solid bar stock, and the outer arms fabricated from 2 1/2" schedule 80 pipe.

The upper arm shall be equipped with a swivel with grease fitting so to prevent damage to the arms when the wing is lifted to the carry position. The lower arm shall be equipped with a compression spring so to provide a shock absorber. Both arms shall be adjustable in length from 61" to 76", offering three (3) positions of adjustment.

Hardware Plating: All nuts, bolts and chain shall be zinc plated.

Paint: All wing components shall be shot blasted and painted with one (1) coat of primer and one (1) coat of finish paint.

## **SPECIFICATIONS FOR RIGHT HAND MOUNT AND POWER HYDRAULIC CONTROLS**

General: The rear mast arrangement shall be located behind the cab and in front of the dump body.

Rear Mast Arrangement: The rear mast vertical beam shall be fabricated from a 10" channel. This vertical beam shall be integrally welded to and supported by a second horizontal 10" channel, which spans the width of the frame. A 1/2" frame plate, two vertical stabilizing ribs and a diagonal member from 10" channel shall further connect these vertical and horizontal members. In addition, there shall be two (2) cylinders provided to control the rear of the wing.

Rear of Wing Cylinder: Shall not be less than a 3" diameter x 14 7/8" stroke double acting type. It shall attach between the rear mast slide and a sliding collar at the upper stand off arm. Adjustable flow restrictors shall be installed between the hydraulic control valve and this cylinder to provide for variation of speed. The cylinder shall be fitted with an integral counter-balance valve at its base to protect against impact load and the possibility of the wing dropping due to pressure line failure.

Rear Slide Cylinder: Shall not be less than a 3" diameter x 33" stroke double acting, which shall be located at the outside of the rear mast vertical support beam.

Wing plow must not interfere with the functionality of the side view mirror.

Front of Wing Cylinder: Shall not be less than a 3" diameter x 33" stroke double acting type, which shall be located integrally at the front post, the travel of the front slide shall be 66". All cylinders shall have chrome-plated piston rods, or nitride cylinder, packing and a rod wiper to clean its piston rod as it retracts into the cylinder tube.

The front mast shall be bolted to and supported by a lower 7" x 4" x 3/8" rectangular structural tube member extending from the truck hitch.

**Must have a Minimum 10" Round Mirror mounted to the front mast for driver visibility of wing plow during lowering operation.**

## **TRIP EDGE POWER REVERSIBLE PLOW SPECIFICATIONS**

**Moldboard:** Shall be 11" long, 42" high inside and shall extend at least 12" out over the cutting edge. The moldboard shall be formed from one piece of 3/8" thick UHMV polymer sheet. The upper portion of the polymer sheet shall be bolted to and sandwiched between 3" x 3" x 1/4" and 3 1/2" x 3 1/2" x 1/4" angles to form a rigid structure at the top. The bottom of the moldboard shall be reinforced by not less than a 5" x 5" x 1/2" angle. It shall be provided with eight one piece 1/2" plate vertical ribs, and shall be equipped with two 10-degree moldboard shoes.

The moldboard shall be equipped with a 1/2" x 18" rubber flap bolted across the top of the moldboard to prevent snow from blowing over.

**Carbide Cutting Edge:** It shall be (3) piece 3/4" x 6" carbide sections, and shall be bolted to the plow for easy replacement with 5/8" Grade 5 carriage bolts and locknuts on 12" centers. Shall be equipped with a carbon steel backer blade.

**Cutting Edge Reinforcement:** Shall be at least 4" x 4" x 3/4" steel angle with 1/2" steel plate gussets electrically welded to the framework.

**Shoes:** Replaceable wear parts shall include two (2) moldboard shoes and two (2) cast chilled malleable iron curb shoes.

**Trip Mechanism:** The trip mechanism shall be of the single section trip edge type. It shall consist of five (5) 7/8" alloy wire torsion springs with sixteen coils 17 3/8" long. It shall have two hinge rods made from 1 1/2" HR steel which slide through springs and hinge lugs to support the trip edge mechanism. Each spring shall have provision for pre-load adjustment.

**Reversing Frame:** The reversing frame shall be fabricated from 4" x 4" x 3/8" square tubing and 4" x 3" x 1/4" rectangular structural tubing gusseted at key stress points. Three (3) sets of 1/2" thick reinforced connecting lugs spanning 80" shall be welded to the 4" x 4" x 3/8" member of the reversing circle. These lugs shall serve as connection points to the moldboard.

**"A" Frame:** Shall include a weldment consisting of two (2) pieces of 4" x 3" x 1/4" rectangular tubing spaced so to accommodate a sliding member from 7" x 4" x 3/8" rectangular tubing. This weldment shall have top and bottom members from 3/8" thick plate, and rear plate not less than 1" thick x 10" wide. The rear plate shall be fitted with an oscillating bar from 3/4" plate, which incorporates 1 1/4" drive ears on 30 1/2" centers.

The oscillating bar shall revolve about an 1 1/2" Grade 5 bolt so to allow the plow to follow road contour.

The sliding member, as noted above in the "A" Frame section, shall include a 1-15/16" diameter CRS pivot pin for attachment to the Reversing Frame. It shall sit inside the "A" Frame weldment where it shall be secured in position by a 9/16" diameter wire extension spring.

This spring retained sliding member shall provide moldboard locking/unlocking action when the Reversing cylinders are activated.

Reversing & Locking Mechanism **NO EXCEPTIONS**: The hydraulic reversible push frame shall offer nine (9) plowing positions: four (4) on either side of center to a maximum of 37 degrees for discharge to the right or left Reversing actuation shall be via two (2) 3" diameter x 18" stroke single acting cylinders.

Cylinder protection shall be provided by the aforementioned spring retained sliding mechanism, which pulls a 1 ¼" Nicroloy locking pin located at the rear underside of the "A" Frame into a ¾" thick indexed locking plate at the Reversing Frame .

Locking force is provided by the combination of spring tension and forward plows movement, while unlocking force is provided by the reversing cylinders.

Hardware Plating: All nuts, bolts and chain shall be zinc plated

Plow lift to include dead sheave leveling device with stainless steel cable.

Paint: All snowplow components shall be shot blasted and painted with one (1) coat of primer and one (1) coat of finish paint.

Cylinder Rods: All snow plow hydraulic cylinder rods shall be induction hardened and chrome plated to a minimum of 04" (1 mm) thickness.

Wrap-A-Round Bumper: An additional bumper shall be supplied at each end of the moldboard (quantity 2). They shall be from a minimum of 5/8" thick steel, shall bolt at the cutting edge face and shall project outward beyond the cutting edge where they shall terminate with a 2 1/8" diameter round bar.

**DUMP BODY AND HOIST PACKAGE:**

**General:** The specifications describe a “Heavy Duty” conventional dump with a monoshell design, the material used for the floor/sides and gate will be HARDOX 450, Finish paint will be white to match the truck cab. Must be equipped with side boards rough cut 2x10x10 painted Black.

Body length: 11’  
Side Height: 30”  
Tailgate Height: 39”

**Floor:** One piece ¼” material with 45 degree ramps to the sides and front.

**Sides:** 3/16” Smooth side with dirt shedding lower rub rails, boxed top rail with inverted angle the full length for dirt shedding, board pockets capped.( See General side Boards )

**Gate:** ¼” two panel with air controlled tailgate latch, two manual asphalt chute doors installed in the left and right of the gate.

**Cab Shield:** 42” Full seam welded

**Lift Cylinder:** 20 Ton Capacity designed for salt application, cylinder shall not protrude past the front body panel, and cylinder shall not protrude more than 14” into the load space area.

**Flaps:** Installed front and rear of the rear axle. (On Poly Fenders)

**Reflective Tape:** Installed on body sides and tailgate.

**Tool box:** An aluminum tool box, approximately 18"x 18" x 36” shall be installed.

**Lighting:**

Betts LED ICC and rear light modules #A5ROJ0139 mounted to body per RIDOT direction

Two sanding lights mounted to the spreader per RIDOT direction

One wing spot light installed per RIDOT direction (LED preferred)

One wing strobe light Whelen model WPLOWIA installed per RIDOT direction (LED preferred)

Two Whelen model L-31 lights mounted to the front of the body cab shield per RIDOT direction

Two oval grommet mounted LED flashers and two LED S/T/T mounted in the body rear corner post

All wiring will be sealed and run thru junction boxes, PVC pipe routed inside chassis frame.

**Towing:**

Chassis mounted ¾” pintle plate with a 25-ton swivel hook, Two “D” rings, electrical socket, pintle.

Hook height and electrical socket type per RIDOT direction.

## **MATERIAL SPREADER**

Length: 10'

Width: 82"

Height: 56"

12 gauge stainless steel sides and ends with a 45degree side slope, 7 Gauge stainless steel longitudinal with slotted ends for gearbox and drive shaft removal, 25:1 gearbox with 1 ½" drive shaft and 1 ¼" idler shaft, spring loaded chain take up, 6 tooth sprockets, pintle type. Conveyor chain with 1 ½"x ¼" double welded cross bars; tip up style spinner assembly with Poly disc, Top screen, stainless steel light bar with flashers/ICC and S/T/T mounted to the top rear of the spreader, installed in the dump body with a tailgate latch bar and four tie downs.

**Must come with 2x6 pressure treated board mounted on bottom of sander.**

Pre-Wetting System: (2) 90 gallon poly tanks mounted to the spreader with stainless steel hardware, Hydraulic powered calcium pump mounted in a stainless steel enclosure, all required hoses/spray bar and nozzles to make the system fully functional and controlled by the CS550 controller. **Must have 1" Banjo nozzle with Cap for filling of tanks.**

## **GROUND SPEED ORIENTED CENTRAL HYDRAULIC SYSTEM NO EXCEPTIONS**

Power take off will be transmission mounted and will be hot shift design with no less than 100% of engine speed, the PTO will accept a variable displacement pump via direct mount. Controls for engage/disengage of the PTO shall be a CS 105. The CS 105 controller shall monitor hydraulic reservoir oil level via the reservoir oil level float switch, once the oil level drops below a safe operating level, this switch will disengage the PTO. The controller shall be compatible with CS550 design.

The direct PTO mounted hydraulic pump shall be a piston type, variable displacement, pressure compensating design.

The pump shall be a Rexroth A 10V060 52 series.

Hydraulic valves shall be Rexroth load sense M4-12 series to control all hydraulic functions. The valve shall be installed in a frame mounted stainless steel enclosure.

Controls for all valves shall be Del pneumatic equipped with an adjustable filter/lubricator/regulator assembly plumbed inline with all controls mounted in the cab per RIDOT direction.

The spreader control shall be a Compu-Spread CS550 with all the latest updates and shall be compatible with RIDOT existing units. This unit shall control the pre-wet and application rate of all materials and monitor the road and air temperature. Shall include software required to transfer data to RIDOT account with Interfleet Inc. a division of Webtech Wireless in the same manner as RIDOT existing trucks.

The location and mounting of all controls shall be pre-approved by RIDOT.

All hose ends and fittings shall be compatible with the hose on which they are used. Suction and return lines shall meet or exceed a rating of SAE100R4. Pressure lines shall meet or exceed a rating of 100R2 and shall be of double wire braid construction.

All hoses shall be sized to pump and cylinder requirements and shall be routed in such a way as to avoid contact with the exhaust system, driveshaft, and/or the chassis. Hoses shall be wrapped with protective hose wrap in potential wear spots and shall be securely anchored to the frame rails. All hydraulic lines from the control valve area to the front of the truck shall be custom formed. Stainless steel tubing, bulkhead mounted at both ends and supported by cushion type clamps. All hydraulic lines from the control valve area to the rear of the chassis shall be stainless steel tubing supported by cushion type clamps.

The spreader control shall be constructed with a "digital" type electronic circuit. Features will include night time vision display for viewing by the operator and used in calibration. Display shall also inform operator of service problems. The light shall illuminate when spreader is in operating mode. The display shall indicate if the spreader is in operating mode or stand-by

mode. A backlit minimum 7" color LCD shall be mounted in clear view of the operator, location in cab to be approved by RIDOT. Display shall show granular set rate, actual spread rate, spinner spread width, and pre-wet set rate. For Anti-Icing application, display shall show set rate, actual rate, and lanes that are active. Controller shall be able to switch from pre-wet to anti-ice with a flip of a switch and without going into set-up or calibration mode.

Controller shall be capable of adjusting granular material rates, pre-wet rates, and anti-icing rates on the fly without pause or interruption of spreader output while driving. Adjustment shall be accomplished with a straightforward, single hand operation without entering setup or calibration mode.

It shall not be possible for an operator to select manual mode unless the proper clearance password has been entered into calibration. If a feedback error occurs, the controller shall default into Open Loop Mode.

There shall be a ground speed sensor that will signal the control box to speed up or slow down the conveyor as the truck ground speed changes. All spreader functions shall stop when the truck stops, and shall resume immediately when the truck starts to move. There shall be a programmable jump start feature to provide immediate material flow at one MPH.

Spreader speed sensor wire cable shall be of the same material and integral to the main spreader control cable. Spreader cable wire shall be 18 gauge, minimum.

The system shall include all necessary wiring and switching required to be fully operational.

The electrical harness from the control console to connector #1 and from the control console to the valve bank box shall be shielded and be solvent and oil resistant. Wiring from the control console to connector #1 and from the control console to the valve solenoids shall be enclosed in a sealed, dry system with no external splices.

## **COVER SYSTEM SPECIFICATIONS MODEL DT-2000 CH**

·1/2" STEEL POWER MOUNTS WITH Teflon sealed spherical bearing  
Grade 8 bolts and nuts

The in-cab power cover control lever shall be in line with other control levers

- A spool sectional valve is stacked with the existing sectional valves. A built -in check valve in the sectional valve safety locks the system in both directions. 25/3000 PSI hydraulic hose with #4 JIC fitting

Hydraulic cylinders have a W-bore 16, stroke with an 1" chrome plated piston rod

Side arm wall tubing (2" x 1 1/2"x 11 gauge) with steel welded ends and cylinder mounts

- 3 1/2" galvanized steel tube roll assembly

- 18 oz Armor Guard Cover (wear resistant and asphalt approved) (UHMW) self-lubricating wedges (high density polypropylene)

- Full 100% warranty on parts and labor for one year (excludes cover)

#### **SECTION 4: TECHNICAL PROPOSAL**

Each offerer must include a separately sealed Technical Proposal, so marked, appropriately labeled with the RFP # and vendor name and must address the following which will be the basis for the technical evaluation:

Warranty/Warranty Resolution – Specify the period of time that the manufacturer will make any repairs or replace defective parts free of charge. Please provide a detailed description regarding the process for resolution of product issues.

Availability of Parts – Please describe the logistics regarding the availability of parts and the time frame for delivery.

Quality of Work Plan/Delivery Schedule/Significant Milestones - Please describe in detail, the framework within which the requested trucks will be produced. The following elements must be included: 1) Date when significant milestones are achieved 2) Specifically, the date when delivery can be expected. Anticipated delivery of trucks must be included (see Truck Delivery schedule on Page 6).

Experience, Capability, Capacity, and Qualifications – Please provide a detailed description of the Vendor's experience as a heavy equipment provider. A list of relevant client references must be provided, to include client names, addresses, phone numbers, dates of service and type(s) of service(s) provided.

#### **SECTION 5: COST PROPOSAL**

Each proposal must include a separately sealed cost proposal, so marked, appropriately labeled with RFP # and vendor name and must include both a per unit cost and a total cost for the required Six-Wheel Dump Trucks outlined in this proposal.

#### **SECTION 6: EVALUATION AND SELECTION**

Proposals will be reviewed by a Technical Review Committee comprised of staff from The Department of Transportation. To advance to the Cost Evaluation phase, the Technical Proposal must receive a minimum of 60 (85.7%) out of a maximum of 70 technical points. Any technical proposals scoring less than 60 points will not have the cost component opened and evaluated. The proposal will be dropped from further consideration.

Proposals scoring 60 technical points or higher will be evaluated for cost and assigned up to a maximum of 30 points in cost category, bringing the potential maximum score to 100 points.

The Department of Transportation reserves the exclusive right to select the vendor that it deems to be in its best interest to accomplish the project as specified herein; and conversely, reserves the right not to fund any proposal(s).

Proposals will be reviewed and scored based upon the following criteria:

Criteria	Possible Points
Warranty/Warranty Resolution	5 Points
Availability of Parts	10 Points
Quality of the Work plan/Schedule/Milestones	25 Points
Experience, Capability, Capacity, and Qualifications of the Offeror	30 Points
Total Possible Technical Points	70 Points
Cost calculated as lowest responsive cost proposal divided by (this cost proposal) times 30 points *	30 Points
Total Possible Points	100 Points

\*The respondent offering the lowest cost proposal will receive one hundred percent (100%) of the available points for cost. All other offerers will be awarded cost points based upon the following formula:

$(\text{Low proposal} / \text{vendor's proposal}) * \text{available points}$

For example: If the low offerer (Vendor A) proposals \$65,000 and Vendor B proposals \$100,000 for monthly cost and service fee and the total points available are Thirty (30), vendor B's cost points are calculated as follows:

$$\$65,000 / \$100,000 * 30 = 19.5$$

Points will be assigned based on the offeror's clear demonstration of his/her abilities to complete the work, apply appropriate methods to complete the work, create innovative solutions and quality of past performance in similar projects.

Applicants may be required to submit additional written information or be asked to make an oral presentation before the technical review committee to clarify statements made in their proposal. Applicants may be required to submit additional

written information or be asked to make an oral presentation before the Technical Review Committee to clarify statements made in their proposal.

### **SECTION 7: PROPOSAL SUBMISSION**

Questions concerning this solicitation may be e-mailed to the Division of Purchases to Lisa Hill [lisa.hill@purchasing.ri.gov] no later than the date and time indicated on page one of this solicitation. Please reference RFP # on all correspondence. Questions should be submitted in a Microsoft Word attachment. Answers to questions received, if any, will be posted on the Internet as an addendum to this solicitation. It is the responsibility of all interested parties to download this information. If technical assistance is required to download, call the Help Desk at (401) 574-9709.

Offerors are encouraged to submit written questions to the Division of Purchases. No other contact with State parties will be permitted. Interested offerors may submit proposals to provide the services covered by this Request on or before the date and time listed on the cover page of this solicitation. Responses received after this date and time, as registered by the official time clock in the reception area of the Division of Purchases will not be considered.

Responses (an original plus three (3) copies) should be mailed or hand-delivered in a sealed envelope marked "RFP#" to:

RI Dept. of Administration  
Division of Purchases, 2nd floor  
One Capitol Hill  
Providence, RI 02908-5855

NOTE: Proposals received after the above-referenced due date and time will not be considered. Proposals misdirected to other State locations or those not presented to the Division of Purchases by the scheduled due date and time will be determined to be late and will not be considered. Proposals faxed, or emailed, to the Division of Purchases will not be considered. The official time clock is in the reception area of the Division of Purchases.

#### **RESPONSE CONTENTS**

Responses shall include the following:

1. A completed and signed three-page R.I.V.I.P generated offerer certification cover sheet downloaded from the RI Division of Purchases Internet home page at [www.purchasing.ri.gov](http://www.purchasing.ri.gov).
2. A completed and signed W-9 downloaded from the RI Division of Purchases Internet home page at [www.purchasing.ri.gov](http://www.purchasing.ri.gov).

3. **A separate Technical Proposal** describing the, warranty/warranty resolution; availability of parts; delivery schedule/significant milestones and overall quality of the work plan; and experience, capability, capacity, and qualifications of the offeror and background of the applicant and experience with similar projects, and all information described earlier in this solicitation. The Technical Proposal is limited to six (6) pages (this excludes any appendices).
4. **A separate, signed and sealed Cost Proposal** reflecting the total cost of this procurement.
5. In addition to the multiple hard copies of proposals required, Respondents are requested to provide their proposal in **electronic format (CD-Rom, disc, or flash drive)**. Microsoft Word / Excel OR PDF format is preferable. Only 1 electronic copy is requested and it should be placed in the proposal marked "original".

### **CONCLUDING STATEMENTS**

Notwithstanding the above, the State reserves the right not to award this contract or to award on the basis of cost alone, to accept or reject any or all proposals, and to award in its best interest.

Proposals found to be technically or substantially non-responsive at any point in the evaluation process will be rejected and not considered further.

The State may, at its sole option, elect to require presentation(s) by offerors clearly in consideration for award.