



State of Rhode Island
Department of Administration / Division of Purchases
One Capitol Hill, Providence, Rhode Island 02908-5855
Tel: (401) 574-8100 Fax: (401) 574-8387

ADDENDUM #2

RFP #7549323

TITLE: HEAVY DUTY TANDEM DUMP TRUCKS (TEN WHEEL)

SUBMISSION DEADLINE: March 11, 2015 – 3:00 p.m.

Please note the following clarifications/changes:

1. Warranty

N. Warranties-

All Warranties proposed shall be in addition to any statutory remedies or factory warranties imposed by the manufacturer. Final scoring on each bidders warranty portion submitted will be based on the following offerings;

- Transmission; duration or length of the warranty and the components covered.
- Engine; duration or length of the warranty and the components covered.
- After treatment; The engine aftertreatment system and EA Harness and sensors shall come with a 60 months/100,000 miles, **no exemptions**
- Chassis (including components, but not limited to items such as radiators, coolers, cab, suspension, axels, electrical); duration or length of the warranty and the components covered.

Please keep in mind; RIDOT is looking to receive warranty coverage lasting no longer than five (5) years/100,000 miles with no hour limitation.

2. Material Spreader

Each material spreader shall be equipped and installed with material spill over protection rubber on either side as well as spill shields front and rear.

- The rubber utilized for side spill protection shall be rugged enough to withstand harsh conditions with a minimum thickness of 3/8". All rubber shall be situated in a manner as to prevent material from falling into the vehicles dump body.
- The front and rear spill shielding shall be constructed of stainless steel, and must be situated in a manner not to interfere with body or truck components. The front and rear spill shielding shall not block or interfere with the view of the cab shield mounted strobe lights, or protrude higher than the vehicles highest point.
- All hardware utilized for mounting of the aforementioned shielding shall be high grade stainless steel.
- All spill over protection shall be easily removable/installable when loading/unloading the material spreader.

3. Whelen Lighting System

Each material spreader shall be equipped and installed with material spill over protection rubber on either side as well as spill shields front and rear.

- The rubber utilized for side spill protection shall be rugged enough to withstand harsh conditions with a minimum thickness of 3/8". All rubber shall be situated in a manner as to prevent material from falling into the vehicles dump body.
- The front and rear spill shielding shall be constructed of stainless steel, and must be situated in a manner not to interfere with body or truck components. The front and rear spill shielding shall not block or interfere with the view of the cab shield mounted strobe lights, or protrude higher than the vehicles highest point.
- All hardware utilized for mounting of the aforementioned shielding shall be high grade stainless steel.
- All spill over protection shall be easily removable/installable when loading/unloading the material spreader.

4. Radio shall be Motorola Model APX 1500 and shall include the following:

APX 1500, Software P25 Conventional, 9600 trunking Baud Single System, Control Head (Grey), Dash Mount, control head software, palm microphone, Auxiliary speaker 13W(3.2 OHM), 2 year maintenance, advanced system key-software, and Ant3Db low-profile 762-8700.



Company Name

Signature/Date

Printed Name



Lisa Hill
Chief Buyer



WORK SAFER WHEREVER THE MISSION TAKES YOU

APX™ 1500 PROJECT 25 MOBILE RADIO

Whether a marathon race is passing through the streets of downtown or a water main breaks in the city's largest pipeline, you need the ability to interoperate seamlessly and securely with other agencies and responders. You need to instantly connect and be informed to make better decisions to keep your responders and the community safe. While the advanced technology of APX radios expertly equips you for your day to day operations and the unexpected, your organization may be challenged to improve operating expenses.

The APX 1500 P25 mobile radio is equipped with all the features you need at a price you can afford. It delivers all the benefits of TDMA technology in the most compact P25 capable mobile in the industry. The APX 1500 brings together powerful technology in an easy-to-use radio that's easy on your budget. It seamlessly unifies public works, utility, rural public safety and transportation users to first responders so they can interoperate effectively in the moments that matter.

BE UP TO THE MINUTE INFORMED

Keeping your crew safe is your number one priority. Like all our APX P25 radios trusted by responders worldwide, the APX 1500 mobile redefines safety. Your crews can count on quick, seamless interoperability and extended range wherever the mission may take them. You can depend on ADP software encryption for secure, tamperproof voice and data communications every time they connect.

The O2 Control Head with color display is easy to read and operate in all lighting conditions, from bright sunlight to dark streets. The intelligent lighting on the O2 Control Head notifies your workers when a call is received, an emergency arises, or when they are out of range. Plus, an enlarged multifunction knob makes it easy to use talk-group and volume settings when they're wearing gloves.

SIZED RIGHT FOR YOUR BUDGET

The APX 1500 gives you the ruggedibility and reliability you need at an affordable price. Since the APX 1500 is P25 Phase 2 capable for twice the voice capacity, you can add more users without adding more frequencies or infrastructure. Count on APX quality for years to come. The APX 1500 can withstand wet, dusty and hazardous conditions.

PRODUCT SPEC SHEET.
APX™ 1500 MOBILE RADIO



APX 1500 SPECIFICATIONS

FEATURES AND BENEFITS:

Available in 700/800 MHz, VHF, UHF R1 and UHF R2 frequency bands

Channels: Standard 512

Trunking Standards supported:

- Clear or digital private Trunked Operation

Analog MDC-1200 and Digital APCO P25 Conventional System Configurations

Narrow and wide bandwidth digital receiver (6.25kHz/12.5kHz/20kHz/25 kHz)

Embedded digital signaling (ASTRO and ASTRO 25)

Intelligent lighting

Radio profiles

Unified Call List

Meets applicable MIL-STD 810C, D, E, F, G

Ships standard IP56

Utilizes Windows XP, Vista and Windows 7 Customer Programming Software (CPS)

- Supports USB Communications
- Built in FLASHport™ support

Uses standard Dash mounted APX accessories

ADP Privacy

OPTIONAL FEATURES:

Integrated GPS Capable

Programming over Project 25 (POP25)

Text Messaging

12 character RF ID asset tracking

APX 1500 CONTROL HEAD PORTFOLIO



02 RUGGED CONTROL HEAD

- Large color display with intelligent lighting
- 3 lines of text 14 characters max / 1 line of icons / 1 line of menus
- Built in 7.5 watt speaker
- Multifunction volume/channel knob
- Night/day mode button

PRODUCT SPEC SHEET
APX™ 1500 MOBILE RADIO

TRANSMITTER - TYPICAL PERFORMANCE SPECIFICATIONS										
	700 MHz		800 MHz		VHF		UHF Range 1		UHF Range 2	
Frequency Range/Bandsplits	764-776 MHz 794-806 MHz		806-824 MHz 851-870 MHz		136-174 MHz		380-470 MHz		450-520 MHz	
Channel Spacing	25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz	
Maximum Frequency Separation	Full Bandsplit		Full Bandsplit		Full Bandsplit		Full Bandsplit		Full Bandsplit	
Rated RF Output Power Adj*	3-30 Watts (2-3 Watts Itinerant)		3-35 Watts		1-50 Watts		1-40 Watts		1-45 Watts	
Frequency Stability* (-30°C to +60°C; +25°C Ref.)	±0.8 PPM		±0.8 PPM		±0.8 PPM		±0.8 PPM		±0.8 PPM	
Modulation Limiting*	±5 kHz / ±2.5 kHz		±5 kHz/±4 kHz (NPSAPC) /±2.5 kHz		±5 kHz / ±2.5 kHz		±5 kHz / ±2.5 kHz		±5 kHz / ±2.5 kHz	
Modulation Fidelity (C4FM) 12.5kHz Digital Channel	1.5%		1.5%		2.5%		1.1%		1.1%	
Emissions*	Conducted+ -75/-85 dBc	Radiated+ -20/-40 dBm	Conducted -75 dBc	Radiated -20 dBm	Conducted -85 dBc	Radiated -20 dBm	Conducted -85 dBc	Radiated -20 dBm	Conducted -85 dBc	Radiated -20 dBm
Audio Response*	+1, -3 dB (EIA)		+1, -3 dB (EIA)		+1, -3 dB (EIA)		+1, -3 dB (EIA)		+1, -3 dB (EIA)	
FM Hum & Noise	25 & 20 kHz 12.5 kHz	-50 dB -48 dB	-50 dB -48 dB	-50 dB -48 dB	-52 dB -51 dB	-52 dB -48 dB	-51 dB -48 dB	-51 dB -48 dB	-51 dB -48 dB	-51 dB -48 dB
Audio Distortion*	25 & 20 kHz 12.5 kHz	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%	0.50% 0.50%

RECEIVER - TYPICAL PERFORMANCE SPECIFICATIONS										
	700 MHz		800 MHz		VHF		UHF Range 1		UHF Range 2	
Frequency Range/Bandsplits	764-776 MHz		851-870 MHz		136-174 MHz		380-470 MHz		450-520 MHz	
Channel Spacing	25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz		25/20/12.5 kHz	
Maximum Frequency Separation	Full Bandsplit		Full Bandsplit		Full Bandsplit		Full Bandsplit		Full Bandsplit	
Audio Output Power at 3% distortion*	7.5 W or 15 W ++		7.5 W or 15 W ++		7.5 W or 15 W ++		7.5 W or 15 W ++		7.5 W or 15 W ++	
Frequency Stability* (-30°C to +60°C; +25°C Ref.)	±0.8 PPM		±0.8 PPM		±0.8 PPM		±0.8 PPM		±0.8 PPM	
Analog Sensitivity*	12 dB SINAD	-120 dBm	-120 dBm	-120 dBm	Pre-Amp -123 dBm	Standard -119 dBm	Pre-Amp -123 dBm	Standard -119 dBm	Pre-Amp -123 dBm	Standard -119 dBm
Digital Sensitivity	5% BER	-121 dBm	-121 dBm	-121 dBm	-123 dBm	-119 dBm	-123 dBm	-119 dBm	-123 dBm	-119 dBm
Intermodulation Rejection	25 kHz 12.5 kHz	82 dB 82 dB	82 dB 82 dB	82 dB 85 dB	84 dB 85 dB	86 dB 86 dB	82 dB 83 dB	86 dB 85 dB	82 dB 83 dB	86 dB 85 dB
Spurious Rejection		91 dB	91 dB	91 dB	95 dB	91 dB	91 dB	91 dB	91 dB	91 dB
Audio Distortion at rated*		2%	2%	2%	2%	2%	2%	2%	2%	2%
Selectivity*	25 kHz 12.5 kHz 30 kHz	85 dB 75 dB —	85 dB 75 dB —	85 dB 75 dB —	89 dB 77 dB 90 dB	89 dB 77 dB 90 dB	83 dB 72 dB —	83 dB 72 dB —	83 dB 72 dB —	83 dB 72 dB —

DIMENSIONS		
	Inches	Millimeters
Mid Power Radio Transceiver	2 x 7 x 6.4	50.8 x 178 x 163
O2 Control Head	2.7 x 8.1 x 2.1	69 x 207 x 53
Mid Power Radio Transceiver and O2 Control Head - Dash Mount	2.7 x 8.1 x 8.8	69 x 207 x 223
Mid Power Radio Transceiver and O2 Control Head Weight	5.28 lbs	2.45 kg

RADIO MODELS	
700/800 (763-870 MHz)	M36URS9PW1AN
VHF (136-174 MHz)	M36KSS9PW1AN
UHF Range 1 (380-470 MHz)	M36QSS9PW1AN
UHF Range 2 (450-520 MHz)	M36SSS9PW1AN

SIGNALING (ASTRO MODE)	
Signaling Rate	9.6 kbps
Digital ID Capacity	10,000,000 Conventional / 48,000 Trunking
Digital Network Access Codes	4,096 network site addresses
ASTRO® Digital User Group Addresses	4,096 network site addresses
Project 25 - CAI Digital User Group Addresses	65,000 Conventional / 4,094 Trunking
Error Correction Techniques	Golay, BCH, Reed-Solomon codes
Data Access Control	Slotted CSMA: Utilizes infrastructure-sourced data status bits embedded in both voice and data transmissions.

PRODUCT SPEC SHEET
APX™ 1500 MOBILE RADIO

POWER AND BATTERY DRAIN				
Model Type	136-174 MHz, 380-470 MHz, 450-520 MHz, 764-870 MHz			
Minimum RF Power Output	2***-25 Watts (764-776 MHz), 2***-25 Watts (794-806 MHz), 2***-25 Watts (806-824 MHz), 2***-25 Watts (851-870 MHz), 1-25 Watts (136-174 MHz), 1-25 Watts (380-470 MHz), 1-25 Watts (450-520 MHz)			
Operation	13.8V DC ±20% Negative Ground			
Standby at 13.8V	0.85A (764-870 MHz), 0.85A (136-174 MHz), 0.85A (380-470 MHz), 0.85A (450-520 MHz)			
Receive Current at Rated Audio at 13.8V	3.2A (764-870 MHz), 3.2A (136-174 MHz), 3.2A (380-470 MHz), 3.2A (450-520 MHz)			
Transmit Current (A) at Rated Power	136-174 MHz (1-25 Watt) 380-470 MHz (1-25 Watt) 450-520 MHz (1-25 Watt)	9.5A (25W) 9.5A (25W) 9.5A (25W)	764-870 MHz (10-35 Watt) (2***-25 Watts)	9.5A (25W)

MOBILE MILITARY STANDARDS 810 C, D, E, F, G										
	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature Storage	501.1	I	501.2	I/A1	501.3	I/A1	501.4	I/Hot	501.5	I/A1
High Temperature Operation	501.1	II	501.2	II/A1	501.3	II/A1	501.4	II/Hot	501.5	II
Low Temperature Storage	502.1	I	502.2	I/C3	502.3	I/C3	502.4	I/C3	502.5	I/C3
Low Temperature Operation	502.1	I	502.2	II/C1	502.3	II/C1	502.4	II/C1	502.5	II
Temperature Shock	503.1	-	503.2	I/A1-C3	503.3	I/A1-C3	503.4	I/Hot-C3	503.5	I/C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain Blowing	506.1	I	506.2	I	506.3	I	506.4	I	506.5	I
Rain Steady	506.1	II	506.2	II	506.3	II	506.4	III	506.5	III
Humidity	507.1	II	507.2	II	507.3	II	507.4	-	507.5	II-Aggravated
Salt Fog	509.1	-	509.2	-	509.3	-	509.4	-	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Blowing Sand	-	-	510.2	II	510.3	II	510.4	II	510.5	II
Vibration Min. Integrity	514.2	VIII/F, Curve-W	514.3	I/10	514.4	I/10	514.5	I/24	514.6	I-Cat.24
Vibration Loose Cargo	514.2	XI	514.3	II/3	514.4	II/3	514.5	II/5	514.6	-
Shock Functional	516.2	I	516.3	I	516.4	I	516.5	I	516.6	I, V, VI

ENCRYPTION	
Supported Encryption Algorithms	ADP SW
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command

* Measured in the analog mode per TIA/EIA 603 under nominal conditions
 ** Accuracy specs are for long-term tracking (95th percentile values >5 satellites visible at a nominal -130 dBm signal strength)
 + Specs includes performance for the non-GNSS/GNSS bands
 ++ Output power in to 8 and 3.2 Ohm external speakers respectively

Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements.

Version 2, Dec 14

ENVIRONMENTAL SPECIFICATIONS	
Operating Temperature	-30°C / +60°C
Storage Temperature	-40°C / +85°C
Humidity	Per MIL-STD
ESD	IEC 801-2 KV
Water and Dust Intrusion	IP56, MIL-STD

TRANSMITTER CERTIFICATION	
700/800 (764-775, 793-805, 806-824, 851-869 MHz)	AZ492FT7055
VHF (136-174 MHz)	AZ492FT4916
UHF R1 (380-470 MHz)	AZ492FT3826
UHF R2 (450-520 MHz)	AZ492FT4915

FCC EMISSIONS DESIGNATORS	
FCC Emissions Designators	8K10F1D, 8K10F1E, 8K10F1W, 11K0F3E, 16K0F3E, 20K0F1E

Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. www.motorolasolutions.com

MOTOROLA, MOTOROLA SOLUTIONS, and the stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © Motorola Solutions, Inc. 2014 R3-1-5000A

