

May 21, 2015

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATION
DEPARTMENT OF ADMINISTRATION

DIVISION OF PURCHASES BID NO. 7549579

RHODE ISLAND DEPARTMENT OF TRANSPORTATION

RHODE ISLAND CONTRACT NO.2015-CR-053

FEDERAL-AID PROJECT NO. FAP Nos: STP-RESF(290)

Crack Sealing South and Central

Statewide, South and Central Regions

CITY/TOWN OF Charlestown, Coventry, Hopkinton, Richmond, Warwick

COUNTY OF WASHINGTON, KENT

NOTICE TO PROSPECTIVE BIDDERS

ADDENDUM NO. 1 Prospective bidders and all concerned are hereby notified of the following changes in the Plans, Specifications, Proposal and Distribution of Quantities for this contract. These changes shall be incorporated in the Plans, Specifications, Proposal and Distribution of Quantities, and shall become an integral part of the Contract Documents.

A. Specification Change/Addition

1. Job Specific

Delete page JS-3 in its' entirety and replace with revised page JS-3 (R-1) attached to this addendum. The modified asphalt binder was changed from PG 64E-34 to PG 64E-28.



RI Department of Transportation
Chief Engineer

408.9901

**CLEANING AND SEALING CRACKS IN BITUMINOUS CONCRETE PAVEMENT:
CRACKS LESS THAN ONE INCH IN WIDTH**

408.9902

**CLEANING AND SEALING CRACKS IN BITUMINOUS CONCRETE PAVEMENT:
CRACKS ONE INCH AND OVER IN WIDTH**

Section 408.02.1 b. 1. Modified Asphalt Binder - This shall consist of a blend of modified PGAB and crumb rubber, which are chemically bonded to produce a modified PGAB.

Modified PGAB shall conform to AASHTO M 320 and R 29 and shall meet the requirements of PG 64E-28. The nonrecoverable creep compliance versus percent recovery of the binder shall be plotted and must fall above the curve in Figure X1.1 in Appendix XI of AASHTO M 332. The elastic recovery at 10°C (AASHTO T 301) shall be not less than 70%.

The modified PGAB shall not contain any particles of rubber or elastomeric material when tested in accordance with AASHTO T 44. The modified PGAB shall at a minimum consist of 7% crumb rubber from tires. The supplier of the modified PGAB shall certify the composition and PG grade of the material.

Section 408.02.1 b. 2. Asphalt Cement Delete “(AASHTO MP1)” and replace with “(AASHTO M320)”.

Section 408.02.3 Blotter Material. Delete “black beauty” and replace with “3060 granulated coal slag abrasive (Black Beauty)”

Section 408.04.1. Change section title from “Cracks Less than One Inch in Width” to “Cracks 1/16” to Less than One Inch in Width”. Under the first sentence change “Cracks Less than...” to “Cracks 1/16” to Less than...”

Section 408.05.1. Change section title from “Cracks Less than...” to “Cracks 1/16” to Less than...” Change last sentence to “Initial sweeping of the pavement will be incidental”.

Section 408.05.2. Change last sentence to “Initial sweeping of the pavement will be incidental”.