



Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 ONE CAPITOL HILL
 PROVIDENCE RI 02908

BUYER: Hill, Lisa
 PHONE #: 401-574-8118

CREATION DATE : 29-OCT-15
 BID NUMBER: 7550014
 TITLE: SCARIFIER (SURFACE PREPATOR DELUXE HIGH PERFORMANCE REMOVER) - DOT
 BID CLOSING DATE AND TIME: 20-NOV-2015 11:00:00

**B
I
L
L
T
O**
 DOT MAINTENANCE BUSINESS OFFICE
 360 LINCOLN AVE
 WARWICK, RI 02888
 US

**S
H
I
P
T
O**
 DOT MAINTENANCE BUSINESS OFFICE
 360 LINCOLN AVE
 WARWICK, RI 02888
 US

Requisition Number: 1437103

Line	Description	Quantity	Unit	Unit Price	Total
1	SCARIFIER (SURFACE PREPARATOR DELUXE HIGH PERFORMANCE REMOVER) UNIT PER ATTACHED SPECIFICATIONS UNIT TO BE UTILIZED IN ASSOCIATION WITH HIGHWAY LANE STRIPING OPERATIONS. QUESTIONS CONCERNING THIS SOLICITATION MAY BE ADDRESSED TO LISA HILL AT LISA.HILL@PURCHASING.RI.GOV NO LATER THAN NOVEMBER 13, 2015 AT 4:00 P.M. MAKE/MANUFACTURER: _____ -- MODEL: _____ ANTICIPATED DELIVERY: _____	1.00	Each		

Delivery: _____

Terms of Payment: _____

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

Equipment Bid Specifications – Scarifier

		Meets Specification	
		Yes	No
GENERAL			
	Surface Preparator Deluxe high performance remover (Scarifier) - 13HP Gas-Powered includes the following standard and upgraded purchased accessories to increase removal performance and service-life of cutters, parts, engine and machine.	<input type="checkbox"/>	<input type="checkbox"/>
1	All-steel unitized heavy duty construction c/w industrial powder coat safety-yellow with safety-red belt guard with Grade-8 fasteners	<input type="checkbox"/>	<input type="checkbox"/>
2	Power: 13 HP engine manual start with oil alert and air-cleaner with manual shut-off and exclusive emergency safety stop lanyard.	<input type="checkbox"/>	<input type="checkbox"/>
3	Front control handlebar setting with reversible-rear-ready micro depth control with engage/disengage cam lever c/w deluxe 10-setting exclusive micro depth knob.	<input type="checkbox"/>	<input type="checkbox"/>
4	Heavy-duty wide HTD drive belt with safety belt guard tensioned without moving motor.	<input type="checkbox"/>	<input type="checkbox"/>
5	Push/pull twist lock dashboard mounted throttle control.	<input type="checkbox"/>	<input type="checkbox"/>
6	Dual vacuum dust collection port with caps	<input type="checkbox"/>	<input type="checkbox"/>
7	Twin maintenance-free triple sealed bearing assembly - no greasing required	<input type="checkbox"/>	<input type="checkbox"/>
8	All-surround under carriage brush and chip shrouded brush guard for dust and debris control	<input type="checkbox"/>	<input type="checkbox"/>
9	Balanced all-steel rear wheel carrier for precise in-line removal control c/w twin 5in OD X 2in heavy duty, non-marking, wheels with serviceable bearings	<input type="checkbox"/>	<input type="checkbox"/>
10	Twin 4in OD X 2in heavy duty, non-marking, in-line front wheels with serviceable bearings	<input type="checkbox"/>	<input type="checkbox"/>
11	Removable sideplate for side-loading drum with no exposed parts	<input type="checkbox"/>	<input type="checkbox"/>
12	Height adjustable multi-positional anti-vibration ergonomic comfort grip handlebar extension for better performance control and reduce fatiguing	<input type="checkbox"/>	<input type="checkbox"/>
DRUM SET UP IN A 10" MEDIUM FINISH			
13	Carbide 10" Width Medium Finish Drum Assembly includes: Heavy-duty DELUXE 3/4" OD 6 shafted bushed heat-treated hex drum assembly c/w spider center support outfitted with set of CF2128, ultra-premium grade (extended-life) 8 spike tungsten carbide (MEDIUM finish) - 1 cutter / 1 spacer offset pattern - 10" Width center drum set-up)	<input type="checkbox"/>	<input type="checkbox"/>
FLAIL REBUILD KIT			
14	Rebuild Kit - 10" Medium Removal Finish. Kit includes set of 6-(3/4" hardened tool-steel plated shafts), 12-(3/4" hardened bushings), 180- hardened spacers, 156- ultra-premium grade 8 spike tungsten carbide flail cutters, 1-LT242 (Loctite). (For installation on Drum Assembly, approx. 10" wide, 1 cutter / 1 spacer offset pattern set-up) (NO DRUM)	<input type="checkbox"/>	<input type="checkbox"/>
BASIC WEAR PARTS KIT			
15	Flail Basic Wear parts kit. include: 1 drive belt, 1 outside maintenance-free bearing assembly complete, 1 inside maintenance-free bearing assembly complete, 1 engine filter (gas only)	<input type="checkbox"/>	<input type="checkbox"/>

Drum Rotation and Power Options

Cutter Rotation (Down)	<input type="checkbox"/>	<input type="checkbox"/>
Gas (HP) + (Drive HP) 13	<input type="checkbox"/>	<input type="checkbox"/>
Electric (HP) + (Drive HP) 7.5	<input type="checkbox"/>	<input type="checkbox"/>
Cutter Drum / Tool Choices Diamond Shavers, Groovers	<input type="checkbox"/>	<input type="checkbox"/>
Tungsten Carbide Milling Picks	<input type="checkbox"/>	<input type="checkbox"/>
Carbide Scrapers, Millers	<input type="checkbox"/>	<input type="checkbox"/>
4N1 Carbide	<input type="checkbox"/>	<input type="checkbox"/>
Carbide Flails	<input type="checkbox"/>	<input type="checkbox"/>
Steel Flails (Beam or Stars)	<input type="checkbox"/>	<input type="checkbox"/>
Wire Brush	<input type="checkbox"/>	<input type="checkbox"/>
Standard Specifications		
Removal width / pass (inches - mm) up to 10" (254mm)	<input type="checkbox"/>	<input type="checkbox"/>
Removal depth / pass (inches - mm) up to 1/4" (6.35mm)	<input type="checkbox"/>	<input type="checkbox"/>
Hourly Production Rate (LF) (approx. 2250)	<input type="checkbox"/>	<input type="checkbox"/>
Height (inches - mm) 44" (1117.6mm)	<input type="checkbox"/>	<input type="checkbox"/>
Width (inches - mm) 19" (482.6mm)	<input type="checkbox"/>	<input type="checkbox"/>
Length (inches - mm) 38" (965.2mm)	<input type="checkbox"/>	<input type="checkbox"/>
Weight (lbs.) (without drum, attachments) 250	<input type="checkbox"/>	<input type="checkbox"/>
Variable depth adjustment	<input type="checkbox"/>	<input type="checkbox"/>
Engage Cam Lever (Shock Dampened)	<input type="checkbox"/>	<input type="checkbox"/>
Dual Vacuum Port with Containment Shroud	<input type="checkbox"/>	<input type="checkbox"/>
Cutter Shaft OD 3/4"	<input type="checkbox"/>	<input type="checkbox"/>
Bushed Drums	<input type="checkbox"/>	<input type="checkbox"/>
Quantity Wheels 4	<input type="checkbox"/>	<input type="checkbox"/>
Remote Power Shut-Off	<input type="checkbox"/>	<input type="checkbox"/>
Ergonomic (Vibration Dampening) Handlebar	<input type="checkbox"/>	<input type="checkbox"/>
Side-Loading Cutter Drums	<input type="checkbox"/>	<input type="checkbox"/>

7540014

Drive System (# of belts) 1	<input type="checkbox"/>	<input type="checkbox"/>
Bearings Sealed	<input type="checkbox"/>	<input type="checkbox"/>
Manual, NOT Self-Propel or Ride-On	<input type="checkbox"/>	<input type="checkbox"/>

Contract Terms and Conditions

Table of Contents

Terms and Conditions.....VI
 BID STANDARD TERMS AND CONDITIONSVI
 TERMS AND CONDITIONS FOR THIS BIDVI
 RIVIP INFO - BID SUBMISSION REQUIREMENTSVI
 VENDOR SPECIFICATIONSVI
 DELIVERY PER AGENCYVI

Terms and Conditions

BID STANDARD TERMS AND CONDITIONS

TERMS AND CONDITIONS FOR THIS BID

RIVIP INFO - BID SUBMISSION REQUIREMENTS

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

MAILING ADDRESS FOR BID PROPOSALS ISSUED BY THE STATE OF RHODE ISLAND,
DIVISION OF PURCHASES

All Bid Proposals must be submitted by mail or hand delivered to:

- State of Rhode Island
- Department of Administration
- Division of Purchases, Second floor
- One Capitol Hill
- Providence, RI 02908-5855

DIVESTITURE OF INVESTMENTS IN IRAN REQUIREMENT:

No vendor engaged in investment activities in Iran as described in R.I. Gen. Laws §37-2.5-2(b) may submit a bid proposal to, or renew a contract with, the Division of Purchases. Each vendor submitting a bid proposal or entering into a renewal of a contract is required to certify that the vendor does not appear on the list maintained by the General Treasurer pursuant to R.I. Gen. Laws §37-2.5-3.

VENDOR SPECIFICATIONS

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.

DELIVERY PER AGENCY

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.