



Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
ONE CAPITOL HILL
PROVIDENCE RI 02908

CREATION DATE : 20-JAN-16
BID NUMBER: 7550200
TITLE: KNUCKLE CRANE TRUCK - DOT

BID CLOSING DATE AND TIME: 11-FEB-2016 10:30:00

BUYER: Hill, Lisa
PHONE #: 401-574-8118

**B
I
L
L

T
O**
DOT MAINTENANCE BUSINESS OFFICE
360 LINCOLN AVE
WARWICK, RI 02888
US

**S
H
I
P

T
O**
DOT MAINTENANCE BUSINESS OFFICE
360 LINCOLN AVE
WARWICK, RI 02888
US

Requisition Number: 1445816

Note to Bidders: QUESTIONS CONCERNING THIS SOLICITATION MAY BE ADDRESSED TO LISA HILL AT LISA.HILL@PURCHASING.RI.GOV NO LATER THAN FEBRUARY 4, 2016 AT 4:00 P.M.

Line	Description	Quantity	Unit	Unit Price	Total
1	2016 KNUCKLE CRANE TRUCK PER ATTACHED SPECIFICATIONS	1.00	Each		

Delivery: _____

Terms of Payment: _____

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

State of Rhode Island
Division of Purchases
Solicitation #7550200

2016 Knuckle Crane Truck

Instructions for Bidders:

- Bidders are required to return the bid specifications (Pages 1-21) **in duplicate** along with their Request For Quote (Cost Page) and Bidder Certification Cover Form.
- Any exceptions to any aspect of the required specifications are to be clearly and legibly noted in the right margin on each of the specification pages, as applicable.
- Additionally, bidders are required to submit manufacturer specifications/catalog cuts of the unit proposed.
- Questions relative to this solicitation may be addressed to Lisa Hill, Chief Buyer at lisa.hill@purchasing.ri.gov no later than February 4, 2016 at 4:00 p.m.
No telephone inquiries will be entertained.

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

APPLICATION: Utility/Service (Other)

MISSION: Requested GVWR: 25500. Calc. GVWR: 25999
Calc. Start / Grade Ability: 27.40% / 1.69% @ 55MPH
Calc. Geared Speed: 83.4 MPH

DIMENSION: Wheelbase: 169.00, CA: 101.90, Axle to Frame: 63.00

ENGINE, DIESEL: {Cummins ISB 240} EPA 2010, 240 HP @ 2400 RPM, 560 lb-ft Torque
@ 1600 RPM, 2600 RPM Governed Speed, 240 Peak HP (Max)

TRANSMISSION, AUTOMATIC: {Allison 2100_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, with
Double Overdrive; with PTO Provision. Less Retarder, with 26,000-lb GVW &
GCW Max, on/off highway

CLUTCH: Omit item (Clutch & Control)

AXLE, FRONT NON-DRIVING: I-Beam Type, 10,000-lb Capacity

AXLE, REAR, SINGLE: {Dana Spicer 19060D} Single Reduction, 19,000-lb Capacity, 190 Wheel Ends,
Driver Controlled Locking Differential Gear Ratio: 6.17

CAB: Conventional

TIRE, FRONT: (2) 11R22.5 G661 HSA (GOODYEAR) 497 rev/mile, load range G, 14 ply

TIRE, REAR: (4) 11R22.5 G182 (GOODYEAR) 497 rev/mile, load range H, 16 ply

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

SUSPENSION, RR, SPRING, SINGLE:

Vari-Rate; 20,000-lb Capacity; With 4500 lb. Auxiliary Rubber Spring

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200

2016 Knuckle Crane Truck

Vehicle Specifications

2016 Knuckle Crane Truck

Description:

Base Chassis, 101.90 CA and 63.00 Axle to Frame.

TOW HOOK, FRONT (2) Frame Mounted

FRAME RAILS High Strength Low Alloy Steel (80,000 PSI Yield); 10.250" x 3.092" x 0.375"
(260.4mm x 78.5mm x 9.5mm); 427.0" (10846mm) Maximum OAL

LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper

BUMPER, FRONT Full Width, Aerodynamic, Steel; 0.142" Material Thickness

Includes:

- : BUMPER, FRONT Powder Coated Gray (Argent) Color
- : WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)
- : AXLE, FRONT I-Beam Type, 10,000-lb Capacity
- : SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf, 10,000-lb Capacity; With Shock Absorbers

Includes:

- : SPRING PINS Rubber Bushings, Maintenance-Free

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

Notes:

- : The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.
- BRAKE SYSTEM, HYDRAULIC {Meritor Wabco} Split System, Full Power, With Automatic Adjustment And With Four Channel ABS
- BRAKE, PARKING {Bosch} DSSA Type, 12" x 3"; for Hydraulic Brake Chassis; Activated by Lever in Cab; Differential Mounted or Equal To.

Includes:

- PARKING BRAKE CONTROL Lever, Floor Mounted, Located Right of Driver
- BRAKES, FRONT, HYDRAULIC DISC Quadratic; four 70mm Diameter Pistons
- BRAKES, REAR, HYDRAULIC DISC Quadratic; four 70mm Diameter Pistons
- AIR COMPRESSOR {Cummins} 18.7 CFM Capacity, with Tank for Air Source on Hydraulic Chassis, without Gauge
- STEERING COLUMN Tilting
- STEERING WHEEL 2-Spoke, 18" Diam., Black
- STEERING GEAR: Power
- EXHAUST SYSTEM Switchback Horizontal After-Treatment Device, Frame Mounted Right Side under Cab; Includes Single Short Horizontal Tail Pipe, Frame Mounted Right Side Back of Cab.

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

ENGINE EXHAUST BRAKE with Variable Vane Turbo Charger

SWITCH, FOR EXHAUST 2 Position, Lighted, & Latching, ON/OFF Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as long as switch is in ON Position.
ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes:

- : BATTERY BOX Steel
- : DATA LINK CONNECTOR for Vehicle Programming and Diagnostics In Cab
- : FUSES, ELECTRICAL SAE Blade-Type
- : HAZARD SWITCH Push On/ Push Off, Located on Top of Steering Column Cover
- : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
- : JUMP START STUD Located on Positive Terminal of Outermost Battery
- : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
- : STARTER SWITCH Electric, Key Operated
- : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector
- : TURN SIGNAL SWITCH Self – Canceling for Trucks, Manual Canceling for Tractors, with Lane Change Feature
- : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted
- : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
- : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
- : WIRING CHASSIS Color Coded and Continuously Numbered
- : Power Door Locks and Power Windows

ALTERNATOR: {Leece-Neville AV7160P2007} Brush Type; 12 Volt 210 Amp. Capacity, Pad Mount, With Remote Sense

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

BODY BUILDER WIRING Back of Standard Cab at Left Frame or Under Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn.

BATTERY SYSTEM: Maintenance-Free, (3) 12 Volt 1950CCA Total

RADIO {Panasonic CQ 120} AM/FM, Includes Multiple Speakers, Includes Auxiliary Input

Includes:

- : SPEAKERS IN CAB (2) Dual-Cone with Deluxe Interior
- : SPEAKERS IN CAB (4) Coaxial with Premium Interior

BACK-UP ALARM Electric, 102 DBA

HORN, ELECTRIC Disc Style

HEADLIGHTS ON W/WIPERS Headlights will automatically turn on if windshield wipers are turned on

STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection

INDICATOR, LOW COOLANT LEVEL with Audible Alarm

HEADLIGHTS Halogen; Composite Aero Design for Two Light System

CIRCUIT BRAKEERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses Except for 5-Amp Fuses

GRILLE Chrome

FRONT END Tilting, Fiberglass, with Three Piece Construction

PAINT SCHEMATIC, PT-1 Single Color, Design 100

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200

2016 Knuckle Crane Truck

Includes:

PAINT SCHEMATIC ID LETTERS "GA"

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

PAINT CLASS Premium Color

SPECIAL RATING, GVWR Limited to 25,999-lb GVWR

CLUTCH Omit Item (Clutch & Control)

BLOCK HEATER; ENGINE 120 Volt/1000 Watt, for ISB Engine

ENGINE DIESEL {Cummins ISB 240} EPA 2010, 240 HP @ 2400 RPM, 560 lb-ft Torque @ 1600 RPM, 2600 RPM

Governed Speed, 240 Peak HP (Max)

Includes:

: ANTI-FREEZE Red Shell Rotella Extended Life Coolant; - 40 Degrees F/ -40 Degrees C; for Cummins ISB Engines

: FUEL/WATER SEPARATOR Fuel/Water/Separator; Heated; with Water-in-Fuel Sensor; Engine Mounted

: FAN DRIVE {Borg-Warner SA85} Viscous Type; Screw On

Includes:

: FAN Nylon

RADIATOR Aluminum; 2-Row, Cross Flow, Over under System, 717 SqIn Charge Air Cooler. With In-Tank Transmission Cooler

Includes:

: DEARATION SYSTEM with Surge Tank

: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200

2016 Knuckle Crane Truck

: RADIATOR HOSES Premium, Rubber
AIR CLEANER With Service Protection Element

Includes:

GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

ENGINE CONTROL, REMOVE MOUNTED – No Provision Furnished for Remote Mounted Engine Control

OIL PAN 15 Quart Capacity, For Cummins ISB Engines

EMISSIONS COMPLIANCE Federal, Does Not Comply With California Clean Air Idle Regulations

FEDERAL EMISSIONS EPA, OBD and GHG Certified for Calendar Year 2015; ISB Engines

TRANSMISSION, AUTOMATIC {Allison 2100_RDS_P} 5th Generation Controls; Close Ratio, 6-Speed, with Double
Overdrive; with PTO Provision, Less Retarder, With 26,000-lb GVW & GCW Max, on/off highway

Includes:

: OIL FILTER, TRANSMISSION Mounted on Transmission

: TRANSMISSION OIL PAN Magnet in Oil Pan

TRANSMISSION OIL Synthetic; 20 through 28 Pints

SHIFT CONTROL PARAMETERS Allison 1000 or 2000 Series Transmissions, 5th Generation Controls,
Performance Programming

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

AXLE, REAR, SINGLE {Dana Spicer 19060D} Single Reduction, 19,000-lb Capacity, 190 Wheel Ends,
Driver Controlled Locking Differential. Gear Ratio 6.17

Includes:

- : REAR AXLE DRAIN PLUG (1) Magnetic, for Single Rear Axle

Notes:

- : The following features should be considered when calculating Rear GAWR: Rear Axles, Rear Suspension;
 - : Brake System; Brakes; Rear Air Cam; Brake Shoes, Rear, Special Rating, GAWR; Wheels; Tires.
 - : When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Stability and Performance
- SUSPENSION, RR, SPRING, SINGLE Vari-Rate; 20,000-lb Capacity, with 4500 lb. Auxiliary Rubber Spring

Notes:

- : The following features should be considered when calculating Rear GAWR: Rear Axles, Rear Suspension ; Brake System; Brakes; Rear Air Cam; Brake Shoes, Rear, Special Rating, GAWR; Wheels; Tires.

SHOCK ABSORBERS, REAR (2)

FUEL TANK Top Draw; D style, Non Polished Aluminum, 19" Deep, 70 U.S. Gal., 265 L Capacity, with Quick Connect Outlet, Mounted Left Side, Under Cab

Notes:

- : DEF TANK 7 U.S. Gal. 26.5L Capacity, Frame Mounted Outside Left Rail, Under Cab
- : CAB Conventional

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

Includes:

- : ARM REST (2) Molded Plastic; One Each Door
- : CLEARANCE/MARKER LIGHTS (5) Flush Mounted

Description:

- : COAT HOOK, CAB Located on Rear Wall, Centered Above Right Rear Window
 - : CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel
 - : DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted
 - : GLASS, ALL WINDOWS Tinted
 - : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side
 - : GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side
 - : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color
- GAUGE CLUSTER English with English Electronic Speedometer

Includes:

- : GAUGE CLUSTER (5) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter
- : ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Fault Code Readout
- : WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200

2016 Knuckle Crane Truck

GAUGE, DEF FLUID LEVEL

SEAT, DRIVER: Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 1 Chamber Lumbar, with 2 Position Front Cushion Adjust, -3 to +14 Degree Back Adjust

Includes:

: SEAT BELT 3-Point, Lap and Shoulder Belt Type
SEAT, TWO-MAIN PASSENGER {National} Fixed Back, Integrated Headrest in Both Occupant Positions, Vinyl, Less under Seat Storage Compartment

MIRRORS (2) {Lang Mekra} Rectangular, 7.55" x 14.1" Integral Convex Both Sides 102" Inside Spacing, Breakaway Type, Thermostatically Controlled Heated Seats, Black Heads, Brackets and Arms

AIR CONDITIONER {Blend-Air} with Integral Heater and Defroster

Includes:

: HEATER HOSES Premium
: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps
: REFRIGERANT Hydrofluorocarbon HFC-134A
INSTRUMENT PANEL Center Section, Flat Panel
CAB INTERIOR TRIM Deluxe

STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200

2016 Knuckle Crane Truck

Includes:

- : "A" PILLAR COVER Molded Plastic
- : CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering
- : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets with Retainer Nets and CB Radio Pocket
- : DOOR TRIM PANELS Molded Plastic; Driver and Passenger Doors
- : FLOOR COVERING Rubber, Black
- : HEADLINER Soft Padded Cloth
- : INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section
- : STORAGE POUCH, DOOR (1) Molded Plastic, Full-Length; Driver Door
- : SUN VISOR (2) Padded Vinyl with Driver Side Toll Ticket Strap, Integral to Console
- : **INSTALL STATE SUPPLIED TWO WAY RADIO (See attached)**

WHEELS, FRONT {Accuride} DISC; 22.5" Painted Steel, 10-Stud (285.75MM BC) Hub Piloted, 5 Hand Hole, Flanged Nut, Metric Mount, 7.50DC Rims; With Steel Hubs.

Includes:

PAINT IDENTITY, FRONT & REAR WHEELS White

Description:

- : Expectable Tire Sizes: 11R22.5

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

WHEELS, REAR {Accuride} DUAL DISC; 22.5 Painted Steel, 10-Stud (285.75MM BC) Hub Piloted, 5 Hand Hole,
Flanged Nut, Metric Mount, 7.50 DC Rims; with Steel Hubs

Notes:

: Expectable Tire Size: 11R22.5

PAINT IDENTITY, FRONT WHEELS Disc Front Wheels; With Vendor Applied White Powder Coat Paint

PAINT IDENTITY, REAR WHEELS Disc Rear Wheels; With Vendor Applied White Powder Coat Paint

Knuckle Crane Device

Hydraulic Extension to 28' 11" @ 1720 lbs.

High tensile strength steel construction

Cast base

Hexagon booms

Dual side controls

EMC Load limiting device

Self-lubricating bushings

SAE JIC 15141 Fittings

Swivel and Load Hook

Stabilizers:

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

Hydraulic out

Hydraulic down

Articulated feet

Slewing angle 400 degrees with mechanical limiter

35L Hydraulic tank

Remote Control:

Radio operated

Multi-Function

Hetronic

Winch:

Winch kit with rope

Top roller

Pull limiter device

Double pull kit

2300# capacity, 1000 kg

Performance:

3'3" 16,360#

8.4" 6,420#

13'7" 3,960#

18'8" 2,770#

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

23'9"	2,110#
28'11"	1,720#

Model: Heavy Duty Series

Body Dimensions:

161" long x 96" wide
120" CA with dual rear wheels

Standard Features:

Heavy duty .125" treadplate floor
Outside rub rails with stake pockets
Gas fill cutouts
Radiused Tube Bulkhead with full width slotted window
LED Bulkhead lights, 2 stop/turn/tail and center mounted backup lamp
Treadplate Tail Skirt w/recessed LED stop/turn/tail and back-up lights
7 Way Trailer Plug
Tapered front and rear corners
3" structural channel cross sills, 16" on centers

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

6" structural channel long rails

Bulkhead to be reinforced to long sills

Reinforced wheel well compartments

Bolt on mud flap brackets

Asphalt undercoating

FMVSS-108 lighting complaint

Modular wiring harness with recess shock mounted sealed lamps

Finish

Shot blasted, Zirconium Phosphate pre-treatment

Hi-Temp Wash

High Gloss PPG Black Powder Coat Finish

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

ELECTRICAL:

Warning lights as follows:

- Two (2) Whelen # M7AC, 3" x 7", wide angle, amber LED's installed on front cab grille
- Two (2) Whelen # M7AC, 3" x 7", wide angle, amber LED's installed on rear of flatbed body
- Two (2) Whelen # M7AC, 3" x 7", wide angle, amber LED's installed on midship area of flatbed body
- Two (2) Whelen # L31LAF, amber, Class 1, 2.5" x 7.5", LED multi-diffuser beacons with rotating pattern, installed on forward riser.

SWITCHING:

The chassis supplied upfitter switches shall operate the following:

- Knuckle Crane PTO
- Load Bed Lights
- All Warning Lights

ADDITIONAL:

- Two (2) 4" round, rubber cased, adjustable LED load bed lights, switched from cab. Lights to be mounted on body front bulkhead
- Back-up alarm

ADDITIONAL EQUIPMENT:

- Install "RIDDOT" supplied seal on cab doors

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

- Mud flaps
- Inclinometer, installed on outrigger control stations
- Fire extinguisher
- Reflector kit
- First Aid kit
- Two (2) "Gripstrut" wheel chocks with slide in brackets

GPS unit with telematics to be installed and operational with each vehicle. GPS components, mapping, and data service shall be provided by Web Tech Wireless and installed by their respective installers. GPS data functioning shall include advanced reporting, telematics, real time mapping with a minimum of 10 second update intervals for a one year period.

DELIVERY AND TRAINING

The customer should be able to review the completed vehicle for the compliance to the specifications at the manufacturer's upfit center. There are no limitations in place for these "in production" inspections.

The upfitting and service center shall provide qualified personnel to "in service" the completed unit and instruct personnel in the proper operation and maintenance. The training shall take place at the customers designated location.

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

The training format shall be as follows:

1. Aerial Operator's Safety Review
2. Completed vehicle walk-around and review
3. Actual operation by all intended operator's

Additionally this training shall comply with ANSI A92.2 2009 Edition accepted March 10, 1010. This shall include "hands on" recognition and avoidance of hazards associated with their operation of the aerial device.

Such items that will be covered will include the following:

- Purpose and use of the manuals
- Operating manuals are an integral part of the aerial device and must be stored on the unit when not in use.
- Pre-start/pre-flight of the aerial device
- Responsibilities associated with problems or malfunctions affecting the aerial equipment.
- Factor affecting stability
- The purpose of placards and safety decals
- Workplace inspection
- Authorization to operate
- Operator warnings and instructions

Actual operation of the aerial device which will be conducted at the direction of a qualified manufacture's agent. The use

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

of computer generated models or training will not be an allowable substitute. The trainees shall operate the actual delivered device for a sufficient period and demonstrate proficiency and actual operation.

Proper use of personal fall protection equipment. Fall protection systems criteria and practices are covered in 29 CFR 1926.502.

PROOF OF TRAINING:

Proof of Training will be provided and include the following:

Name of the trainee(s)

Name of the entity providing training

Name of the trainer(s)

Clear identification of the make and model of the unit

INFORMATION PROVIDED AT COMPLETION:

- : Copies of complete two (2) operation and maintenance manuals covering the completed aerial device.
- : Complete and certified actual vehicle weights
- : Copy of the completed "Di-electric Test", if applicable
- : Copy of the completed "Stability Test"

WIRING DIAGRAMS

A wiring diagram showing the manufacture's complete electrical system, circuit breaker panel layouts, and individual schematics for each separate circuit, shall be submitted at the time of delivery. The diagrams shall include the circuit

**STATE OF RHODE ISLAND
DIVISION OF PURCHASES
SOLICITATION #7550200**

2016 Knuckle Crane Truck

breaker panel layouts, primary electrical system, and individual schematics for each separate circuit.

WARRANTY:

One (1) Year General Warranty
All other Manufacturer's prevail

SERVICE:

Service and Warranty work for the proposed vehicle will take place at designated customer's location-whether in the field or at the customer's office.

All work to be performed by certified technician's not untrained sub-contractors.

CERTIFICATE OF ORIGIN: The Contractor shall furnish a Certificate of Origin to RIDOT

The Certificate shall be completed as follows:

Name of Purchaser: State of RI/Fleet Operations
Address of Purchaser: One Capitol Hill Providence, RI 02908

Contract Terms and Conditions

Table of Contents

Terms and Conditions.....VI
 BID STANDARD TERMS AND CONDITIONSVI
 TERMS AND CONDITIONS FOR THIS BIDVI
 PURCHASE AGREEMENT BIDVI
 VENDOR SPECIFICATIONSVI
 DELIVERY PER AGENCYVI

Terms and Conditions

BID STANDARD TERMS AND CONDITIONS

TERMS AND CONDITIONS FOR THIS BID

PURCHASE AGREEMENT BID

BIDDING (a) A single price shall be quoted for each item against which a proposal is submitted. This price will be the maximum in effect during the agreement period. Any price decline at the manufacturer's level shall be reflected in a reduction of the agreement price to the State. (b) Quantities, if any, are estimated only. The agreement shall cover the actual quantities ordered during the period. Deliveries will be billed at the single, firm, awarded unit price quoted regardless of the quantities ordered. (c) Bid price is net F.O.B. destination and shall include inside delivery at no extra cost. (d) Bids for single items and/or a small percentage of total items listed, may, at the State's sole option, be rejected as being non-responsive to the intent of this request. **ORDERING** (a) The User Agency(s) will submit individual orders for the various items and various quantities as may be required during the agreement period. (b) Exception - Regardless of any agreement resulting from this bid, the State reserves the right to solicit prices separately for any extra large requirements for delivery to specific destinations.

Mailing Address for Bid Proposals issued by the State of Rhode Island, Division of Purchases:

All Bid Proposals must be submitted to the following address:

State of Rhode Island
Department of Administration
Division of Purchases, 2nd Floor
One Capitol Hill
Providence, RI 02908

VENDOR SPECIFICATIONS

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.

DELIVERY PER AGENCY

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.