



# Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS  
 ONE CAPITOL HILL  
 PROVIDENCE RI 02908

BUYER: Hill, Lisa  
 PHONE #: 401-574-8118

CREATION DATE : 26-AUG-16  
 BID NUMBER: 7550915  
 TITLE: WESTERLY STATION CROSSWALK REPAIR - DOT  
 BID CLOSING DATE AND TIME: 21-SEP-2016 10:30:00

**B  
I  
L  
L  
T  
O**  
 DOT ACCOUNTS PAYABLE  
 TWO CAPITOL HILL, RM 230  
 SMITH ST  
 PROVIDENCE, RI 02903  
 US

**S  
H  
I  
P  
T  
O**  
 DOT PROPERTY & MANAGEMENT  
 360 LINCOLN AVENUE  
 WARWICK, RI 02888  
 US

Requisition Number: 1463041

Line	Description	Quantity	Unit	Unit Price	Total
1	TOTAL COST INCLUDING ALL LABOR AND MATERIALS TO REPAIR SIDEWALKS AT WESTERLY TRAIN STATION IN ACCORDANCE WITH THE ATTACHED SPECIFICATIONS / REPAIR CROSSWALK AT WESTERLY STATION THERE WILL BE AN ON-SITE PRE-BID CONFERENCE HELD AS FOLLOWS:  DATE: SEPTEMBER 7, 2016 TIME: 9:00 A.M. LOCATION: WESTERLY TRAIN STATION 10 RAILROAD STREET WESTERLY, RI	1.00	Each		

Delivery: \_\_\_\_\_

Terms of Payment: \_\_\_\_\_

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

**STATE OF RHODE ISLAND**

**DIVISION OF PURCHASES**

**BID NO. 7550915**

**Scope of Work**

**Location:** Westerly Train Station

10 Railroad Ave. Westerly RI

**Description:** The Rhode Island Department of Transportation is seeking the services of a qualified contractor to replace in kind, and in accordance with RIDOT standard specifications 601.99xx (attached), the stamped concrete crosswalk measuring 28' x 35' approx. located at the entranceway to the Station in accordance with the attached plan.

The contractor will also provide a price per linear foot for ancillary crack sealing for the adjacent pedestrian crosswalk.

In addition the contractor will:

Legally dispose of all excess concrete.

Saw cut, remove and replace in kind 3 inches of abutting asphalt potentially damaged during concrete removal.

Re-compact all subbase materials.

Use a Class XX concrete.

**Bid Submission:** In addition to the bid price, the contractor must provide evidence (photos) and contact information (Project location, contact name, address and phone number) for at least three recent jobs similar in size and scope to Westerly Station.

**Pre-Bid Meeting:** There will be a pre-bid conference on site at 9:00 a.m. on September 7, 2016

**601.99xx**  
**INTEGRALLY COLORED / TEXTURED CONCRETE**

**DESCRIPTION:** Work under this item will consist of furnishing an integrally colored, and/or stamped and/or exposed aggregate Portland cement concrete complete and in place, as shown on the plans and as directed by the Engineer. The concrete shall be of the class, color and texture specified in the plans and as approved by the Engineer. All work shall be performed in accordance with Section 600, 800 and 900 of the Rhode Island Standard Specifications and latest revisions and as specified in this specification.

**MATERIALS:** All concrete material components shall be in accordance with Section M.02 of the Rhode Island Standard Specifications for Road and Bridge Construction except as modified under this specification.

**Aggregates.** The coarse aggregates for exposed aggregate finishes must be approved by the Engineer as to color and texture.

**Coloring Agent.** Coloring agents for integrally colored concrete shall meet the requirements of ASTM C979 and be approved by the Engineer. Coloring agents shall be used in accordance with manufacturer's recommendations. Coloring agents shall not contain chlorides.

**Surface Penetrating Sealer.** When specified the penetrating sealer shall meet the requirements of Section M.12 and used as recommended by the manufacturer of the coloring agent.

**Form Release Agent.** The Contractor shall use a method/material in accordance with the manufacturer's recommendations for facilitating form release that will not cause discoloration, staining, etc. of the concrete, subject to the approval by the Engineer.

**Color Hardener.** Color hardener shall be ready-to-use, dry shake type and shall be streak-free intergrind of pigments, surface conditioning and dispersing agents, and Portland cement blended with an approved graded aggregate as specified by the manufacturer.

**Curing Compound.** The curing compound shall be as recommended by the manufacturer of the coloring agent. It shall not reduce the skid resistance of the concrete surface.

**Integrally Colored Concrete Mix Design and Approval Process.** Proportioning and testing of the concrete components and mixture shall be accomplished by using the methods outlined in Section 600. The Contractor shall proportion the concrete mix including the coloring additives and finishing methods to obtain the desired color, texture, and aggregate exposure, and meet the appropriate mixture classification requirements of Tables 1 and 2 of Section 601.

The following information shall be added in addition to the requirements listed in Section 601 to be included in the laboratory test data report:

1. Coloring Agents
2. Color Hardener
3. Release Agent

4. Curing Compound
5. Surface Penetrating Sealer
6. Form Release Agents
7. Special finishing methods used to obtain the desired concrete texture.

Prior to performing the concrete field trial runs the Contractor shall submit to the Engineer the proposed mix design(s) and one concrete prototype (1' x 1' x 3" min.) for each concrete classification, color and texture, and aggregate exposure as specified in the project plans. The prototype shall be submitted to the Engineer sufficiently in advance to allow for review of color, texture, and aggregate exposure of the concrete prototype.

**Field Trial Run.** After the concrete mix design and the prototype provided by the Contractor have been reviewed by the Engineer and no exception taken, the Contractor shall conduct a field trial run prior to production, using the submitted mix design's component materials and proportions including the amount of admixtures, color additives, finishing and curing techniques which will be necessary to produce concrete of the specified plasticity, workability, air content, compressive strength, color, texture, aggregate exposure and any other specified concrete property.

During the field trial run, the Contractor shall prepare a field sample, no less than 20 square feet (4'x5') in size using the proposed mix to achieve the color and texture as specified in the plans. When a penetrating sealer is specified, the Contractor shall apply the sealer to the finished surface of the field sample. This field sample shall not be part of the permanent product. When textured patterns are specified the field sample shall include 90% patterned area impressed from full patterns and 10% patterned area using hand tools and methods to match the full formed area.

When all specified concrete parameters have been attained, including color and texture, the Engineer, in consultation with the RIDOT Historic Preservation Officer, shall approve the proposed mix design, color, texture, and aggregate exposure for production.

**CONSTRUCTION METHODS:** Construction methods shall conform to Sections, 601 and 905 of the R.I. Standard Specifications except as otherwise provided in this Specification.

Concrete beam samples are not required for acceptance testing.

The Contractor shall observe any special treatments required for existing surfaces on which this concrete is cast, as detailed on the Contract Plans.

Specific placement sequences shall be listed on the plans.

**CURING:** All curing procedures and methods shall be completed according to the color additive manufacturer's recommendations and as specified in Section 600 of the R.I. Standard Specifications or as otherwise directed by the Engineer.

**FINISHING:** All exposed surfaces shall be finished straight and true, approximating the original contour as close as practicable. The final finished surfaces shall match the texture, color and aggregate exposure specified in the plans and as directed by the Engineer.

---

---

---

The Contractor shall in each case capture all the waste and water from the finishing operations, process and dispose these materials. Any materials and/or labor resulting from the surface finishing operations, including sedimentation and dewatering controls shall be considered for payment under the terms of this Specification.

**METHOD OF MEASUREMENT:** "Integrally Colored Concrete" shall be measured as provided for in the specifications for the particular item or items under which it is paid.

**BASIS OF PAYMENT:** "Integrally Colored Concrete" shall be paid for as provided in the specification covering the particular use. Any integrally colored concrete not otherwise provided for shall be paid for under the concrete item of the class indicated and required.







**Contract Terms and Conditions**

**Table of Contents**

Terms and Conditions.....VI  
    BID STANDARD TERMS AND CONDITIONS .....VI  
        TERMS AND CONDITIONS FOR THIS BID .....VI  
        RIVIP INFO - BID SUBMISSION REQUIREMENTS .....VI  
        LICENSE REQUIREMENTS .....VI  
        INSURANCE REQUIREMENTS .....VI  
        WAGE REQUIREMENTS .....VII  
        START DATE .....VII

## Terms and Conditions

### BID STANDARD TERMS AND CONDITIONS

### TERMS AND CONDITIONS FOR THIS BID

#### RIVIP INFO - BID SUBMISSION REQUIREMENTS

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

MAILING ADDRESS FOR BID PROPOSALS ISSUED BY THE STATE OF RHODE ISLAND,  
DIVISION OF PURCHASES

All Bid Proposals must be submitted by mail or hand delivered to:

- State of Rhode Island
- Department of Administration
- Division of Purchases, Second floor
- One Capitol Hill
- Providence, RI 02908-5855

#### DIVESTITURE OF INVESTMENTS IN IRAN REQUIREMENT:

**No vendor engaged in investment activities in Iran as described in R.I. Gen. Laws §37-2.5-2(b) may submit a bid proposal to, or renew a contract with, the Division of Purchases. Each vendor submitting a bid proposal or entering into a renewal of a contract is required to certify that the vendor does not appear on the list maintained by the General Treasurer pursuant to R.I. Gen. Laws §37-2.5-3.**

#### LICENSE REQUIREMENTS

VENDOR (OWNER OF COMPANY) IS RESPONSIBLE TO COMPLY WITH ALL LICENSING OR STATE PERMITS REQUIRED FOR THIS TYPE OF SERVICE. A COPY OF LICENSE/PERMIT SHOULD BE SUBMITTED WITH THIS BID. IN ADDITION TO THESE LICENSE REQUIREMENTS, BIDDER, BY SUBMISSION OF THIS BID, CERTIFIES THAT ANY/ALL WORK RELATED TO THIS BID, AND ANY SUBSEQUENT AWARD WHICH REQUIRES A RHODE ISLAND LICENSE(S), SHALL BE PERFORMED BY AN INDIVIDUAL(S) HOLDING A VALID RHODE ISLAND LICENSE.

#### INSURANCE REQUIREMENTS

AN INSURANCE CERTIFICATE IN COMPLIANCE WITH PROVISIONS OF ITEM 31 (INSURANCE) OF THE GENERAL CONDITIONS OF PURCHASE IS REQUIRED FOR COMPREHENSIVE GENERAL LIABILITY, AUTOMOBILE LIABILITY, AND WORKERS' COMPENSATION AND MUST BE SUBMITTED BY THE SUCCESSFUL BIDDER(S) TO THE DIVISION OF PURCHASES PRIOR TO AWARD. THE INSURANCE CERTIFICATE MUST NAME THE STATE OF RHODE ISLAND AS CERTIFICATE HOLDER AND AS AN ADDITIONAL INSURED. FAILURE TO COMPLY WITH THESE PROVISIONS MAY RESULT IN REJECTION OF THE OFFEROR'S BID. ANNUAL RENEWAL CERTIFICATES MUST BE SUBMITTED TO THE AGENCY IDENTIFIED ON THE PURCHASE ORDER. FAILURE TO DO SO MAY BE GROUNDS FOR CANCELLATION OF CONTRACT.

NOTE: IF THIS BID COVERS CONSTRUCTION, SCHOOL BUSING, HAZARDOUS WASTE, OR

VESSEL OPERATION, APPLICABLE COVERAGES FROM THE FOLLOWING LIST MUST ALSO BE SUBMITTED TO THE DIVISION OF PURCHASES PRIOR TO AWARD: \* PROFESSIONAL LIABILITY INSURANCE (AKA ERRORS & OMISSIONS) - \$1 MILLION OR 5% OF ESTIMATED PROJECT COST, WHICHEVER IS GREATER. \* BUILDER'S RISK INSURANCE - COVERAGE EQUAL TO FACE AMOUNT OF CONTRACT FOR CONSTRUCTION. \* SCHOOL BUSING - AUTO LIABILITY COVERAGE IN THE AMOUNT OF \$5 MILLION. \* ENVIRONMENTAL IMPAIRMENT (AKA POLLUTION CONTROL) - \$1 MILLION OR 5% OF FACE AMOUNT OF CONTRACT, WHICHEVER IS GREATER. \* VESSEL OPERATION - (MARINE OR AIRCRAFT) - PROTECTION & INDEMNITY COVERAGE REQUIRED IN THE AMOUNT OF \$1 MILLION.

**WAGE REQUIREMENTS**

BIDDERS ARE ADVISED THAT ALL PROVISIONS OF TITLE 37 CHAPTER 13 OF THE GENERAL LAWS OF RHODE ISLAND APPLY TO THE WORK COVERED BY THIS REQUEST, AND THAT PAYMENT OF THE GENERAL PREVAILING RATE OF PER DIEM WAGES AND THE GENERAL PREVAILING RATE FOR REGULAR, OVERTIME, AND OTHER WORKING CONDITIONS EXISTING IN THE LOCALITY FOR EACH CRAFT, MECHANIC, TEAMSTER, OR TYPE OF WORKMAN NEEDED TO EXECUTE THIS WORK IS A REQUIREMENT FOR BOTH CONTRACTORS AND SUBCONTRACTORS. THE PREVAILING WAGE TABLE MAY BE OBTAINED AT THE RI DIVISION OF PURCHASES HOME PAGE BY INTERNET at [www.purchasing.ri.gov](http://www.purchasing.ri.gov). SELECT "BIDDING INFORMATION", THEN "GENERAL INFORMATION", AND THEN SELECT "PREVAILING WAGE TABLES". PRINTING THE ENTIRE DOCUMENT AVERAGES APPROXIMATELY ONE MINUTE PER PAGE - YOU MAY WANT TO PRINT ONLY THE PAGES APPLICABLE TO YOUR BID. BIDDERS NOTE: IN THE EVENT THIS BID SPECIFIES PRICE OFFERS ON A TIME-AND-MATERIALS BASIS, i.e., AN HOURLY RATE, ANY OR ALL BIDS SUBMITTED IN AN AMOUNT LESS THAN THE PREVAILING RATE IN EFFECT FOR THE WORK COVERED BY THIS REQUEST AS OF THE DATE OF BID ISSUANCE SHALL BE REJECTED BY THE DIVISION OF PURCHASES.

**START DATE**

STARTING DATE \_\_\_\_\_ NO. OF WORKING DAYS REQUIRED FOR COMPLETION  
\_\_\_\_\_