

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
CAPITOL HILL
PROVIDENCE RI 02908

BID NUMBER: B03070

TITLE: UNIFORMS

BID OPENING DATE AND TIME:

11/14/2003 11:15 AM

BUYER: JOHN COWELL
PHONE #: (401) 222 - 2142 ext. 114

**B
I
L
L
T
O**
ENVIRONMENTAL MANAGEMENT
DEM DIV OF LAW ENFORCEMENT
83 PARK STREET
PROVIDENCE RI 02903

**S
H
I
P
T
O**
ENVIRONMENTAL MANAGEMENT
DEM DIV OF LAW ENFORCEMENT
83 PARK STREET
PROVIDENCE RI 02903

Requisition Number(s): R74F039410

Item	Class-Item	Quantity	Unit	Unit Price	Total
	IF SAMPLES ARE REQUESTED, THEY MUST BE PROVIDED WITHIN TEN (10) WORKING DAYS OF REQUEST DATE. FAILURE TO DO SO MAY RESULT IN DISQUALIFICATION OF BID.				
1.0	200-85 SUMMER TROUSERS FECHHIEMER #32245	8.00	PR		
2.0	200-85 WINTER TROUSERS, FECHHIEMER #42215	9.00	PR		
3.0	200-85 SUMMER SHIRTS ELBCCO #2212-3	11.00	EA		
4.0	200-85 WINTER SHIRTS ELBCCO #212-3	18.00	EA		
5.0	200-85 SUMMER SHOES, OXFORD, THOROGOOD #834-6333	1.00	PR		
6.0	200-85 GLOVES, INSULATED, BLACK LEATHER, FINGER FASHIONS #7318, SIZES S, M, L AND XL	6.00	PR		
7.0	200-85 TROUSERS, (BDU) BLAUER #8810 COLOR: OD GREEN	99.00	PR		
	SEE ATTACHED SPECIFICATIONS				

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

**DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.**

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
CAPITOL HILL
PROVIDENCE RI 02908

BID NUMBER: B03070
TITLE: UNIFORMS
BID OPENING DATE AND TIME:
11/14/2003 11:15 AM

BUYER: JOHN COWELL
PHONE #: (401) 222 - 2142 ext. 114

**B
I
L
L
T
O** ENVIRONMENTAL MANAGEMENT
DEM DIV OF LAW ENFORCEMENT
83 PARK STREET
PROVIDENCE RI 02903

**S
H
I
P
T
O** ENVIRONMENTAL MANAGEMENT
DEM DIV OF LAW ENFORCEMENT
83 PARK STREET
PROVIDENCE RI 02903

Requisition Number(s): R74F039410

Item	Class-Item	Quantity	Unit	Unit Price	Total
	<p>THE ABOVE UNIT PRICING INCLUDES THE COST OF UP TO THREE ON-SITE UNIFORM MEASUREMENTS AT THE AGENCY OFFICES PRIOR TO FINAL TAILORING.</p> <p>NO SUBSTITUTION TO BRAND AND STYLE WILL BE ACCEPTED.</p> <p>CONTACT PERSON: TOM GREENE (401) 222-1984</p>				
				TOTAL:	

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

**DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.**

DEPARTEMENT OF ENVIRONMENTAL MANAGEMENT

DIVISION OF ENFORCEMENT

Uniform Specifications

Trousers, Winter (10/7/98)

FECHHIEMER #42215

1. CLASSIFICATION & SCOPE:

- 1.1 This specification covers Winter Uniform Trousers as described herein.
- 1.2 Material: Raeford #6072 75% Dacron Polyester, 25% Wool, Elastique Weave
- 1.3 Weight: 14 1/2 oz./Linear Yard (60")width
- 1.4 Color: Forest Green #92727
- 1.5 Sizes: Trouser must be available in the following stock sizes:
Regular rise: 28-54 (even only over 38)
Short rise: 28-40 even sizes only
Long rise: 32-42 even sizes only

2. Applicable Specification: There are no other specifications applicable to this specification.

3. Requirements:

3.1 Design: Trousers shall be manufactured from a men's uniform pattern. The trouser styling shall incorporate a plain front, two (2) quarter top front pockets, two (2) hip pockets and a watch pocket. Trouser to be straight leg style.

3.2 Pocketing: Pocketing shall be 70% cotton, 30% Cotton, 2.9 oz. per square yard (60"width) with a minimum 78 x 64 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

3.3 Pocket Design: The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 5 3/4" measured from the bottom of the pocket opening. Front pockets to have straight bartacks (use of triangle bartacks will be cause for rejection) at the top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn and topstitch method. Pocket facings to be made of the basic fabric and must measure a minimum of 3" in width at the top. The two hip pockets shall have a minimum opening of 5 1/2" and a minimum depth of 5 3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on a Reece PW Machine and the welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab.

The watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening and depth of 2 3/4". The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

- 3.4 Waistband: The trouser will be made with the Freedom Fit waistband system. The waistband shall be constructed using the "closed method" and shall measure 2" wide when finished. The waistband closure shall be accomplished with a crush proof hook and eye. The hook and eye shall be reinforced with stays made of non-woven fabric that are anchored by the topstitching for the fly facing and curtain. This top stitching must be to the top of the waistband. The waistband must be topstitched 1/16" below the waistband seam for added strength. The top portion of the inside of the waistband is to consist of the same fabric as used for pocketing (70% polyester 30% cotton -minimum 80 x 62(+)-2 count. The fabric is to be cut on the bias for maximum comfort. To be 1 3/4" wide and to finish 1 1/8" wide and to finish 1 1/8" wide after construction. Upper waistband curtain to be inner lined with stretch Ban-Rol canvas. This canvas fabric consists of a warp of 47 ends of texturized nylon and a fill of 34 ends of 750 denier polyester monofilament. The woven fabric is coated with latex, which completely encapsulates all yarns. This finish canvas fabric weighs 12.0 oz/yd. the canvas will be cut 1 3/8" wide with the monofilaments running vertically and have a 10% stretch.
- The bottom portion of the waistband curtain will be a blend of 32% nylon, 38% polyester, 18% rubber (3 strands), 11% lycra and 1% acrylic woven 1 7/8" wide and to finish a minimum of 1 5/8" wide. To have a minimum of 40% stretch characteristics.
- 3.5 Fly: Trouser shall have a Talan #42 memory lock zipper. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic cloth (tabs made of pocketing material or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same fabric as the waistband curtain and pocketing. The fly lining shall be sewn to the left fly below the zipper in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape.
- 3.6 Belt Loops: There shall be a minimum of 7 belt loops, 6 of which are to be Keystone style. Keystone loops shall measure 1 3/4" in width at the top and 1 1/4" at the bottom. The center back loop shall be 3/4" wide straight loop. the Keystone loops shall be sewn into the bottom of the waistband and the top of the loops shall be caught into the waistband curtain seam with a Rocap machine. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband.
- 3.7 Stitching, Pressing & Finishing: Trousers must be stitched with matching thread and all stitching to show must be 10-11 stitches per inch. Trousers must be neatly pressed on hothead Presses and properly shaped. Outseams and inseams must be pressed open. Trouser must be cleaned and finished to eliminate loose threads.
- 3.8 Labels: Trouser must have a care label permanently affixed that also indicates the size. A paper ticket showing the size, fabric content, cut number and WPL number must be on the outside of the waistband. Garment must be made in the United States of America and bear a union label.
- 3.9 Care: Trousers may be home laundered or professionally dry cleaned.

4.0 Workmanship: Trousers shall be first quality, free from any defects affecting appearance or serviceability.

5.0 Inspection: Trousers shall be inspected at point of delivery. The state reserves the right to reject upon inspection.

Bid Samples: Buyer, subsequent to bid opening, may instruct (3) lowest bidders to submit samples. Samples shall not be submitted with bid.

DEPARTEMENT OF ENVIRONMENTAL MANAGEMENT

DIVISION OF ENFORCEMENT

Uniform Specifications

Trousers, Summer (10/7/98)

FECHHIEMER #32245

1. Classification & Scope:

1.1 This Specification covers Summer Trousers as described herein.

1.2 Material: Raeford #573U 55% Dacron/ 45% Wool Tropical Weave

1.3 Weight: 10-10 1/2 oz./Linear Yard (60" width) three (3) ply.

1.4 Color: Forest Green #93389

1.5 Sizes: Trouser must be available in the following stock sizes:

Regular rise: 28-54 (Even only over 38)

Short rise: 28-40 even sizes only

Long rise: 32-42 even only

1.6 Laundering Instructions: Fabric shall be dry cleaned or launderable in home washing machine.

2. Applicable Specification: There are no other specifications applicable to this specification.

SPECIAL REQUIREMENT: Trousers shall have one inch black Nyla-twist braid on outer legs, colorfast, pre-shrunk.

3. Requirements:

3.1 Design: The trousers shall be a straight leg uniform trouser cut from a men's up to date pattern. The trouser styling shall incorporate a plain front, two (2) quarter top front pockets, two (2) hip pockets, and a front watch pocket.

3.2 Construction:

Pockets: The pocketing shall be 70% polyester/30% cotton, 2.9 oz. per square yard (60" width) with minimum 78 x 64 count. Pocketing must have a durable press finish and the pocketing must be black.

Pocket Design: The two (2) front pockets shall be quarter top style with a minimum opening of 6" and a minimum depth of 5 3/4" measured from the bottom of the pocket opening. Front pockets to have straight bartacks (use of triangle bartacks will be cause for rejection) at the top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn and top stitch method. Pocket facings to be made of the basic fabric and must measure a minimum of 3" in width at the top.

Two Hip Pockets: Shall have a minimum opening of 5 1/2" and a minimum depth of 5 3/4" measured from the bottom of the pocket opening. The corners of the pocket openings shall have firm straight bartacks for reinforcing strength (triangle bartacks are unacceptable). The left hip pocket shall have a centered finished tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the tab to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab.

Watch pocket: Shall be located at the right front at the waistband. This pocket shall have a minimum opening and depth of 2 3/4". The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two pieces securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

Waistband: The waistband shall be constructed using the "closed method" and shall measure 2" wide when finished. The waistband curtain is to be of the same fabric and color as the pocketing material and must be attached to the trouser with zig-zag stitch. The waistband must contain Ban-Rol to prevent roll over and have three strand snugtex to keep shirts tucked in. The waistband closure to have a crush-proof hook and eye. The hook and eye shall be reinforced with stays made of non-woven fabric that are anchored by the top stitching for fly facing and curtain. This top-stitching must be to the top of the waistband. The waistband shall be set on and closed using a lockstitch. Use of the chain stitch is unacceptable to stitch the band seam through the outer fabric and the waistband curtain. The waistband must be top-stitched 1/16" below the waistband seam for added strength.

Fly: Trouser shall have a Talon #42 memory lock zipper and there shall be a bartack at the bottom of the fly going through the zipper tape. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic cloth. Tabs made of pocketing material or a "grown on" French Fly will be cause for rejection. The right fly shall be lined with the same fabric as the waistband curtain and pocketing. The Fly lining shall be sewn to the left fly below the zipper in a neat and durable manner. A button shall be located at the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. There shall be a firm straight bartack at the bottom of the fly going through the zipper tape.

Belt Loops: There shall be a minimum of seven belt loops, six of which are to be Keystone style. Keystone loops shall measure 1 3/4" in width at the top and 1 1/4" at the bottom. The center back loop shall be a 3/4" wide straight loop. The keystone loops shall be sewn into the bottom of the waistband and the top of the loops shall be caught into the waistband curtain seam with a rocap machine. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband.

4. **Workmanship:** Trousers shall be made in a first class workmanship manner. Trousers are to be stitched with matching thread and all stitching to show must be 10-11 stitches per inch.
5. **Stitching, Pressing and Finishing:** Trousers are to be neatly pressed on Hothead pressed and properly shaped. Outseams and inseams must be pressed open. Trouser must be cleaned and finished to eliminate loose threads.
6. **Label & Tags:** Trouser must have a sewn in care label permanently affixed giving cleaning instructions and marked with lot number, size, fiber content, cut number and WPL number. A cardboard label must be affixed to outside waistband showing size, fiber content, lot number and WPL number. Garment must be made in the United States of America and bear a union label.
7. **Inspection:** Trousers will be inspected at point of delivery. The State reserves the right to reject upon inspection.

Bid Samples: Buyer, subsequent to bid opening, may instruct (3) lowest bidders to submit samples. Samples shall not be submitted with bid.

DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

DIVISION OF LAW ENFORCEMENT

Uniform Specifications

SHIRT, WINTER(02-03-00)

ELBECO #212-3

1. Classification & Scope:

- 1.1 This Specification covers Winter Shirts as described herein.
- 1.2 65% Dacron Rayon, 35% Light Avril Rayon
- 1.3 Tropical Weight 6 oz.
- 1.4 Color: As specified in bid.

2. Applicable Specification: There are no other specifications applicable to this specification.

3. Requirements:

3.1 Style: Long sleeve fully-lined top center and banded dress type collar, permanent collar stays, epaulets, pencil compartment. (5) Five resin in military creases. The pleated pockets have lines, scalloped flaps with buttons and Velcro closures on both pockets and flaps. There is a metal eyelet badge tab above the left pocket. The cuff has a 2-button styling with a button on the sleeve facing. Full length tails and form fit.

Special Requirements: Division of Enforcement Emblem on both sleeves, to be sewn 3/4" below shoulder seam on both sleeves. Emblem will be furnished by agency and sewn by the vendor.

Buttons: All buttons found on shirt will be standard tan buttons.

Breast Badge Holder: Inside sling-type badge patch of self goods approximately 1 1/2" wide to extend from adjoining seam to pocket to left front. Two small buttonholes, 1 1/4" apart with the lower buttonhole approximately 1 1/8", above flap.

Velcro Patch: The vender shall sew a Velcro patch (3" X 1 1/4"), for attaching a number card, 1/4" above right breast pocket flap centered on pocket flap.

4. Workmanship: Shirts shall be first quality, free from defects affecting appearance or serviceability consistent with good tailoring practices.

5. Label & Tag: Each shirt shall be marked with the lot number, size, fiber content, WPL Number, and shall have a care instruction label sewn in it.

6. Bid Samples: Buyer, subsequent to bid opening, may instruct (3) lowest bidders to submit samples.

PLEASE RETAIN FOR FUTURE REFERENCE.

DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

DIVISION OF LAW ENFORCEMENT

Uniform Specifications

SHIRTS, SUMMER (02-03-00)
ELBECO #2212-3

Agency: Department of Environmental Management/Division of Enforcement

1. Classification & Scope:

- 1.1 Material:** 65% Dacron Rayon, 35% Light Avril Rayon
- 1.2 Weight:** 6 oz. Tropical
- 1.3 Color:** Silvertan

2. Applicable Specification: There are no other specifications applicable to this specification.

3. Requirements:

3.1 Style: Short sleeves, convertible collar, permanent collar stays, pencil compartment, full length tails, form fit, five (5) sewn in military creases.

Breast Badge Holder: Universal Badge Clip.

Special Requirements: Division of Enforcement Emblem on both sleeves, Emblem shall be furnished by the agency and sewed on by the vendor. Individual measurements and alterations to be made by vendor.

Velcro Patch: The vendor shall sew a Velcro patch (3" X 1 1/4"), for attaching a number card, 1/4" above right breast pocket flap centered on pocket flap.

4. Workmanship: Shirts shall be first quality, free from any defects affecting appearance or serviceability.

5. Size Tag: Each shirt shall be marked with lot number, size, fiber content, WPL Number and shall have a care instructions label sewn in it.

Bid Samples: Buyer, subsequent to bid opening, may instruct (3) lowest bidders to submit samples. Samples shall not be submitted with bid.

PLEASE RETAIN FOR FUTURE REFERENCE.

DEPARTEMENT OF ENVIRONMENTAL MANAGEMENT

DIVISION OF LAW ENFORCEMENT

Uniform Specifications

SHOES, SUMMER OXFORD THOROGOOD # 834-6333

1. CLASSIFICATION & SCOPE:
 - 1.1 This specification covers Summer Padded Collar Mud Guard Oxford Shoes as described herein.
 - 1.2 Brand: Thorogood Men's Model #834-6333 Code 3S Oxfords
Women's #534-6333 Code 3S Oxfords
 - 1.3 Color: Black
 - 1.4 Material: Full grain cowhide leather 3 - 3 1/5 oz. minimum thickness.
Quarter Lining - Cambrelle Material. Vamp Lining - Moleskin with 1/8" foam backing for moisture wicking.
 - 1.5 Sizes: Men's; Medium 7 - 12, 13 Wide 7 - 12, 13 XW 7-12
Women's; Medium 5 1/2 - 10, Wide 6 - 10
2. APPLICABLE SPECIFICATION: There are no other specifications applicable to this specification.
3. REQUIREMENTS:
 - 3.1 Style: Six eyelet plain toe mud guard oxford. Full grain cowhide leather. Insole with removable and washable cambrelle covered polyurethane foot bed for maximum shock absorption. Counter 50 bixlon heat activated thermoplastic. Outsole vibram slip and oil resistant rubber wedge with falin side wall stitch. Boxtoe XL 30 Knilon heat activated thermoplastic. 40" braided nylon laces. Moleskin tongue lining.
 - 3.2 Guarantee: Each pair of sneakers shall have a construction warranty.
4. WORKMANSHIP: Sneakers shall be first quality, free from any defects affecting appearance or serviceability.
5. LABEL: Sneakers shall be marked with lot number, size, fiber content and WPL number, a care label sewn in.
6. INSPECTION: Sneakers will be inspected at point of delivery. The State reserves right to reject upon inspection.
7. BID SAMPLES: Buyer, subsequent to bid opening, may instruct (3) lowest bidders to submit samples. Samples shall not be submitted with bid.