

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BID NUMBER: B05756
TITLE: RIDING MOWER
BID OPENING DATE AND TIME:
 11/18/2005 2:00 PM

BUYER: STEPHEN HARRIS
 PHONE #: (401) 222 - 2142 ext. 127

**B
I
L
L
T
O**
 ENVIRONMENTAL MANAGEMENT
 DEM DIV OF PARKS AND RECREATION
 2321 HARTFORD AVENUE
 JOHNSTON RI 02919

**S
H
I
P
T
O**
 ENVIRONMENTAL MANAGEMENT
 DEM PARKS
 SEE BELOW RI N/A

Requisition Number(s): R74B065361

Item	Class-Item	Quantity	Unit	Unit Price	Total
1.0	020-16 LAZER Z LIQUID COOLED MODEL LZ27LKA604 60" MOWERS AS PER ATTACHED SPECIFICATIONS. **** NO SUBSTITUTES **** PRICE TO INCLUDE DELIVERY AND EMPLOYEE DEMONSTRATION TO: PAWTUXET SUPPLY DEPOT 230 WARWICK AVENUE CRANSTON, RI 02905 CONTACT: CARMINO PALIOTTA PRIOR TO DELIVERY AT 401-781-1571 CONTACT PERSON: STEVEN T. WRIGHT 401-222-2632	4.00	EA		
				TOTAL:	

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

**DO NOT SIGN BID ON THIS PAGE!
 USE CERTIFICATION COVER FORM.**

Zero Turn Riding Mower Specifications

Engine: 27 HP Kawasaki Liquid Cooled Engine governed to 3750 rpm.

Air Filter: Heavy Duty canister

Drive System: Two hydro gear 12cc variable displacement pumps with integral SCR valves, powering two high-torque Parker/Ross wheel motors with 1.25" diameter tapered shafts.

Ground Speed: 0 to 10.0 mph forward, 0 to 6.3 mph reverse, infinitely variable.

Hydro Fluid: Mobil 1 SuperSyn oil

Tracking Adjustment: Single adjustment knob [no tools required]

Cutting Deck: 60" Formed and continuous seam welded with 10-gauge top and 7 gauge skirt. 4-point suspension, full-floating deck with 6 adjustable anti-scalp rollers, deck 5.5" deep

Cutting Height: 1.5" to 5.0" in .25" increments and adjustable from operator's seat.

Deck Lift: Manually rises into transport position from operator's seat, without changing cutting height. Hand operated or foot assist.

Drive Tires: 24 x 12-12, 4 ply Multi Trac.

Front Caster Tires: 13 x 6.5-6 Heavy duty smooth tread, semi pneumatic tires.

Casters: 5/8 inch thick double-yoke, caster wheel assembly with pre-installed bearing cups.

Steering and Motion Control: Hydraulically dampened twin levers adjust fore and aft.

Curb Weight: 1403 lbs

Dimensions: 60" Side Discharge

Width: Deflector Up: 61.4" Deflector Down: 72.2"

Length: 80.7" With/ROPS folded: 89.5"

Height Base Unit: 48" W/ROPS folded: 54.0" With ROPS/Up: 72.0"

Blades: 3-20.5" blades

Blade-Tip Speed: 18,000 – 18,500 fpm

Blade Spindles: 1.75" diameter mounted in cast aluminum alloy spindle housings with dual maintenance free bearings.

Tractor Frame: Welded heavy duty tubular steel

Turning Radius: True zero turn

Drive Wheel Release: Allows unit movement without engine running.

Parking Brake: Lever actuated drum and hand integrated with transmission neutral interlock.

Fuel Capacity: 13.5 gallons, twin fuel tanks.

Storage Compartment: Standard

Electrical: 12-Volt battery with 30-amp alternator.

PTO Engagement: Magstop electromagnetic clutch 200 Ft lb 2-year warranty.

Hour Meter: Standard

Engine Temperature Gauge: Standard

Voltage Gauge: Standard

Cooling Standard: Three row core, flat fin radiator with continuously running fan

Safety Package: Operator Presence Controls [OPC] and drive system interlock.

Seat: High-Back, "EVC" [Elastomeric Vibration Control] seat which has no springs. Seat adjusts fore and aft and features padded height adjustable armrests for maximum comfort. Comfort ride adjustable suspension for seat, Item # 104-4754.

Cup Holder: Standard

Roll over Protection: 2 Post foldable ROPS standard with seat belt and latch.

Warranty: 2 Years, parts & labor

No Substitutes: DEM Parks and Recreation operates eight units with an inventory of parts for zero turn mowers.

Price to include delivery and employee demonstration to: Pawtuxet Supply Depot, 230 Warwick Avenue, Cranston, RI 02005
Attention: Carmino Paliotta @ 401-781-1571.

END