

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BID NUMBER: B06174
TITLE: FENCE REPAIRS
BID OPENING DATE AND TIME:
04/20/2006 1:40 PM

BUYER: JOHN O'HARA
 PHONE #: (401) 222 - 2142 ext. 125

**B
I
L
L
T
O**
CORRECTIONS
DOC BUSINESS OFFICE
39 HOWARD AVENUE
CRANSTON RI 02920

**S
H
I
P
T
O**
CORRECTIONS
DOC CDC WAREHOUSE
ATTN: SEE BELOW ON PO
144 POWER RD
CRANSTON RI 02920

Requisition Number(s): R77A067032

| Item | Class-Item | Quantity | Unit | Unit Price | Total |
|------|--|----------|------|------------|-------|
| | <p>THERE WILL BE A MANDATORY PRE-BID MEETING ON APRIL 6, 2006 AT 10:00 AM AT DEPT OF CORRECTIONS MAXIMUM SECURITY 2ND FLOOR CONFERENCE CENTER 1375 PONTIAC AVENUE CRANSTON, RI</p> <p>BIDDER IS REQUIRED TO PROVIDE A BID SURETY IN THE FORM OF A BID BOND, OR A CERTIFIED CHECK PAYABLE TO THE STATE OF RHODE ISLAND, IN THE AMOUNT OF A SUM NOT LESS THAN FIVE PERCENT (5%) OF THE BID PRICE. BID SURETY MUST BE ATTACHED TO THE BID FORM. THE SUCCESSFUL BIDDER WILL ALSO BE REQUIRED TO FURNISH PERFORMANCE AND LABOR AND PAYMENT BONDS AT TIME OF TENTATIVE CONTRACT AWARD.</p> | | | | |

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BID NUMBER: B06174
TITLE: FENCE REPAIRS
BID OPENING DATE AND TIME:
04/20/2006 1:40 PM

BUYER: JOHN O'HARA
 PHONE #: (401) 222 - 2142 ext. 125

**B
I
L
L
T
O**
CORRECTIONS
DOC BUSINESS OFFICE
39 HOWARD AVENUE
CRANSTON RI 02920

**S
H
I
P
T
O**
CORRECTIONS
DOC CDC WAREHOUSE
ATTN: SEE BELOW ON PO
144 POWER RD
CRANSTON RI 02920

Requisition Number(s): R77A067032

| Item | Class-Item | Quantity | Unit | Unit Price | Total |
|------|--|----------|------|------------|-------|
| | <p>BIDDERS ARE ADVISED THAT ALL PROVISIONS OF TITLE 37 CHAPTER 13 OF THE GENERAL LAWS OF RHODE ISLAND APPLY TO THE WORK COVERED BY THIS REQUEST, AND THAT PAYMENT OF THE GENERAL PREVAILING RATE OF PER DIEM WAGES AND THE GENERAL PREVAILING RATE FOR REGULAR, OVERTIME, AND OTHER WORKING CONDITIONS EXISTING IN THE LOCALITY FOR EACH CRAFT, MECHANIC, TEAMSTER, OR TYPE OF WORKMAN NEEDED TO EXECUTE THIS WORK IS A REQUIREMENT FOR BOTH CONTRACTORS AND SUBCONTRACTORS. THE PREVAILING WAGE TABLE MAY BE OBTAINED AT THE RI DIVISION OF PURCHASES HOME PAGE BY INTERNET at www.purchasing.state.ri.us. SELECT "INFORMATION" AND THEN SELECT "PREVAILING WAGE TABLE". THE STATE OF RHODE ISLAND USES THE GENERAL DECISION NUMBER RI20030001. PRINTING THE ENTIRE DOCUMENT AVERAGES APPROXIMATELY ONE MINUTE PER PAGE - YOU MAY WANT TO PRINT ONLY THE PAGES APPLICABLE TO YOUR BID. BIDDERS NOTE: IN THE EVENT THIS BID SPECIFIES PRICE OFFERS ON A TIME-AND-MATERIALS BASIS, i.e., AN HOURLY RATE, ANY OR ALL BIDS SUBMITTED IN AN AMOUNT LESS THAN THE PREVAILING RATE IN EFFECT FOR THE WORK COVERED BY THIS REQUEST AS OF THE DATE OF BID ISSUANCE SHALL BE REJECTED BY THE DIVISION OF PURCHASES.</p> | | | | |

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BID NUMBER: B06174
TITLE: FENCE REPAIRS
BID OPENING DATE AND TIME:
04/20/2006 1:40 PM

BUYER: JOHN O'HARA
 PHONE #: (401) 222 - 2142 ext. 125

**B
I
L
L
T
O**
CORRECTIONS
DOC BUSINESS OFFICE
39 HOWARD AVENUE
CRANSTON RI 02920

**S
H
I
P
T
O**
CORRECTIONS
DOC CDC WAREHOUSE
ATTN: SEE BELOW ON PO
144 POWER RD
CRANSTON RI 02920

Requisition Number(s): R77A067032

| Item | Class-Item | Quantity | Unit | Unit Price | Total |
|------|--|----------|------|------------|-------|
| | <p>BIDDERS ARE RESPONSIBLE FOR INSPECTION OF EQUIPMENT AND/OR LOCATION, TAKING MEASUREMENTS* WHEN REQUIRED, AND MAKING THEMSELVES AWARE OF THE TOTAL REQUIREMENT BEFORE SUBMITTING A BID. *MEASUREMENTS PROVIDED WITH ANY BID ARE FOR REFERENCE PURPOSES AND ARE NOT GUARANTEED TO BE COMPLETELY ACCURATE.</p> <p>ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.</p> <p>VENDOR (OWNER OF COMPANY) IS RESPONSIBLE TO COMPLY WITH ALL LICENSING OR STATE PERMITS REQUIRED FOR THIS TYPE OF SERVICE. A COPY OF LICENSE/PERMIT SHOULD BE SUBMITTED WITH THIS BID. IN ADDITION TO THESE LICENSE REQUIREMENTS, BIDDER, BY SUBMISSION OF THIS BID, CERTIFIES THAT ANY/ALL WORK RELATED TO THIS BID, AND ANY SUBSEQUENT AWARD WHICH REQUIRES A RHODE ISLAND LICENSE(S), SHALL BE PERFORMED BY AN INDIVIDUAL(S) HOLDING A VALID RHODE ISLAND LICENSE.</p> <p>MANDATORY PRE-BID MEETING/WALKTHROUGH PARTIAL PAYMENTS TO BE MADE</p> | | | | |

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BID NUMBER: B06174
TITLE: FENCE REPAIRS
BID OPENING DATE AND TIME:
04/20/2006 1:40 PM

BUYER: JOHN O'HARA
 PHONE #: (401) 222 - 2142 ext. 125

**B
I
L
L
T
O**
CORRECTIONS
DOC BUSINESS OFFICE
39 HOWARD AVENUE
CRANSTON RI 02920

**S
H
I
P
T
O**
CORRECTIONS
DOC CDC WAREHOUSE
ATTN: SEE BELOW ON PO
144 POWER RD
CRANSTON RI 02920

Requisition Number(s): R77A067032

| Item | Class-Item | Quantity | Unit | Unit Price | Total |
|------|---|----------|-------|------------|-------|
| 1.0 | 988-15 REPAIRS REQUIRED TO EXISTING INNER/OUTER FENCING, APPTOXIMATELY 3600-LF AT HIGH SECURITY, 54 POWER ROAD (BLDG.#12) AS FOLLOWS: **REMOVE EXISTING RUSTED STEEL TIES **FURNISH/INSTALL WELDED BANDS **FURNISH/INSTALL 24" RAZOR RIBBON **PAINT EXISTING FENCING SPECIFICATIONS - EXISTING INNER/OUTER FENCING HIGH SECURITY - 54 POWER ROAD (BLDG. #12) SCOPE OF WORK: REMOVE ALL WIRE TIES/WRAPPS THAT ATTACH THE FABRIC TO THE POLES ON BOTH THE INSIDE AND OUTSIDE OF THE EXISTING PERIMETER FENCE AT 3600 LINEAR FEET. REPLACE EACH OF THE TIES/WRAPPS THAT ARE REMOVED WITH A GALVANIZED FENCE BAND THAT IS BOLTED AND TAC-WELDED. REMOVE ALL BARBED WIRE THAT IS ATOP THE EXISTING FENCE AND REPLACE WITH 24-INCH RAZOR RIBBON AND SECURE WITH A STAINLESS STEEL TIE WIRE. THIS WILL BE ON BOTH INNER AND OUTER FENCE ON THE PERIMETER @3600 LINEAR FEET TOTAL. | 1.00 | TOTAL | | |

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.

BID SOLICITATION



STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 CAPITOL HILL
 PROVIDENCE RI 02908

BID NUMBER: B06174
TITLE: FENCE REPAIRS
BID OPENING DATE AND TIME:
04/20/2006 1:40 PM

BUYER: JOHN O'HARA
 PHONE #: (401) 222 - 2142 ext. 125

**B
I
L
L
T
O**
CORRECTIONS
DOC BUSINESS OFFICE
39 HOWARD AVENUE
CRANSTON RI 02920

**S
H
I
P
T
O**
CORRECTIONS
DOC CDC WAREHOUSE
ATTN: SEE BELOW ON PO
144 POWER RD
CRANSTON RI 02920

Requisition Number(s): R77A067032

| Item | Class-Item | Quantity | Unit | Unit Price | Total |
|------|--|----------|------|---------------|-------|
| | <p>PAINT AND PREP THE ENTIRE PERIMETER FENCE INSIDE AND OUTSIDE @3600 LINEAR FEET WITH WEATHERPROOF ALUMINUM PAINT 164 - MANUFACTURED BY BENJAMIN MOORE AND COMPANY OR EQUAL PRODUCT (ATTACHED MSDS SHEETS).</p> <p>ALL INNER AND OUTER FENCING TO BE 12-FT HIGH (CHAIN-LINK TYPE). THIS IS A LABOR INTENSIVE JOB; MATERIALS ARE AT MINIMUM, HENCE THE HIGH COST TO RETROFIT THIS EXISTING FENCE. NO PROJECT MANUAL IS NECESSARY AND CAN BE COVERED VIA A PRE-BID CONFERENCE AND WALKTHROUGH.</p> <p>STARTING DATE _____ NO. OF WORKING DAYS REQUIRED FOR COMPLETION _____</p> <p>CONTACT PERSON: RALPH LEE 401-462-3068</p> | | | | |
| | | | | TOTAL: | _____ |

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

DELIVERY: _____

RIVIP VENDOR ID#: _____

TERMS OF PAYMENT: _____

DO NOT SIGN BID ON THIS PAGE!
USE CERTIFICATION COVER FORM.



Benjamin Moore & Co.

PROFESSIONAL COATINGS

Weatherproof Aluminum Paint 164

Features

- ▲ Produces a beautiful, metallic finish of exceptional brilliance and great durability.
- ▲ Possesses outstanding hiding and leafing properties.
- ▲ Can be applied to large areas without brush or lapmarks.
- ▲ One coat covers most surfaces; two coats provide greater durability and longer wear.
- ▲ Excellent resistance to moisture, weather, and industrial fumes.
- ▲ Withstands temperatures of up to 500° F (260° C).

General Description

A ready-mixed, moderate heat-resistant aluminum paint.

Recommended For:

Residential or commercial applications where a premium quality finish is desired.

For new and previously painted exterior or interior wood, metal, and cured masonry surfaces.

Limitations:

- Do not apply when air and surface temperatures are below 50° F (10° C).

Product Information

Colors: —Standard:
Brilliant Metallic

—Tint Bases:
Not available

—Special Colors:
Not available

Certification:

Formulated without lead, mercury, or chromates.
Formulated with non-photochemically reactive solvents.

Federal Specifications Generic Equivalent
TT-P-38D

Technical Assistance

Available through your local authorized independent Benjamin Moore & Co. dealer.
For the location of the dealer nearest you, call 1-800-826-2623, see www.benjaminmoore.com, or consult your local Yellow Pages.

| Technical Data | Brilliant Metallic |
|--|--|
| Vehicle Type | Linseed Coumarone-Indene |
| Pigment Type | Aluminum |
| Volume Solids | 30% |
| Theoretical Coverage At | 650-700 Sq. Ft. |
| Recommended Film Thickness | Depending on surface texture and porosity. <i>Be sure to estimate the right amount of product for the job. This will ensure color uniformity and minimize the disposal of excess paint.</i> |
| Recommended Film Thickness – Wet | 2.4 Mils |
| – Dry | 0.7 Mils |
| Dry Time @ 77° F | — Set To Touch 3 Hours |
| (25° C) @ 50% RH | — To Handle 8 Hours |
| | — To Recoat Overnight |
| Dries By | Oxidation |
| Viscosity | < 50 KU |
| Flash Point (Seta) | Flammable |
| 60° Specular Gloss | Metallic |
| Surface Temperature at application – Min. | 50° F |
| – Max. | 90° F |
| Thin With: | Do Not Thin |
| Clean Up Thinner | Mineral Spirits |
| Weight Per Gallon | 7.7 lbs |
| Storage Temperature – Min. | 40° F |
| – Max. | 90° F |
| Volatile Organic Compounds (VOC) <i>Unthinned, this product is formulated not to exceed 500 Grams/Liter**</i> | |

** Contact Benjamin Moore & Co. for actual levels, which may or may not be substantially less than stated.

Surface Preparation

Surfaces must be clean, dry, and free of grease, wax, rust, chalk, loose paint, and mildew.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For additional information, contact the USEPA/Lead Information Hotline at 1-800-424-LEAD.

Primer/Finish Systems

Wood, New or Repaint (Including Shakes and Shingles):
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Hardboard Siding, Bare, Factory Primed, or Repaint:
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Masonry, New and Unpainted (Including Unglazed Brick): Poured and precast concrete must be allowed to cure for 30 days; block construction should be allowed to cure for 30 days. All surfaces must be thoroughly prepared by removing the laitance and all loose particles.
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Masonry, Repaint (Including Unglazed Brick): A common exterior paint failure on masonry construction is peeling and scaling, often caused by painting over heavy chalky deposits. The most practical and efficient way to remove this substance is with high pressure spray equipment. Multiple coats of paint that are in an advanced state of deterioration or prior applications of cement based coatings must be removed to a sound substrate. Sandblasting or using a mechanical grinder are effective means of preparation. Surfaces should then be primed with a chalk binding primer such as Moore's Alkyd Masonry Sealer — White (C077 01) or Clear (C077 00).
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Ferrous Metal, New: All ferrous metal surfaces must be wiped with mineral spirits to remove oily, greasy residue. Solvent and rags should be changed frequently. When shop coat is abraded and rust has developed, remove by sanding or wirebrushing to a sound surface.
Primer: IronClad® Alkyd Low Lustre Metal & Wood Enamel (163)
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Ferrous Metal, Repaint: All surfaces must be free of grease and oil, and cleaned in accordance with SSPC-SP1 "Solvent Cleaning", followed by removal of all loose, scaling paint by hand scraping, or by use of power tools. Rusted surfaces to be cleaned in accordance with SSPC-SP2 "Hand Tool Cleaning" or SSPC-SP3 "Power Tool Cleaning". Glossy surfaces should be dulled by sanding. Where heavy rust, corrosion, and deteriorated coatings exist, the surface should be abrasive blast cleaned in accordance with SSPC-SP6 "Commercial Blast Cleaning". The surface should be blown off with compressed air to remove traces of blast products, and must be primed within 24 hours with IronClad Alkyd Low Lustre Metal & Wood Enamel (163).
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Galvanized Iron, New: All new galvanized iron surfaces must be thoroughly cleaned with mineral spirits, then primed with IronClad Latex Low Lustre Metal & Wood Enamel (363).
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Galvanized Iron, Repaint: All surfaces must be free of grease, oils, and industrial contaminants, cleaned in accordance with SSPC SP1 "solvent Cleaning". Peeling or scaling paint must be removed by scraping, sanding, or wirebrushing. Rusty surfaces must be wire-brushed and sanded free of rust and spot primed with IronClad Alkyd Low Lustre Metal & Wood Enamel (163).
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Aluminum, New: Wipe with mineral spirits.
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Aluminum, Weathered: Clean by sanding and wiping with mineral spirits.
Finish: 1 or 2 coats Moore's Weatherproof Aluminum Paint

Application

Stir contents of can until mixture is smooth and uniform. Stir occasionally during use, enough to keep the metallic flakes in suspension. Apply with brush, roller or spray gun. A full, flowing coat produces the best results.

Do not thin. Do not paint when temperature of air is below 50° F (10° C), nor on damp or rainy days.

Spray, Airless: Fluid Pressure—1,500 to 2,000 PSI;
Tip—.013. Orifice; Filter—100 mesh.

Thinning/Cleanup

Do not thin.

Clean brushes and equipment with mineral spirits.

USE COMPLETELY OR DISPOSE OF PROPERLY. This product contains organic solvents which may cause adverse effects to the environment if handled improperly. Save unused product for touch up purposes or a household hazardous waste collection program. Dry, empty containers may be recycled in a can recycling program. **Local disposal requirements vary; consult your sanitation department or state-designated environmental agency for more information on disposal options.**

DANGER - RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER USE. PLEASE RAGS, STEEL WOOD OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

Environmental & Safety Information

WARNING! COMBUSTIBLE LIQUID AND VAPOR!
Contains Stoddard Solvent, Aluminum Flake, and Linseed Oil VAPOR HARMFUL. CAUSES SKIN, NOSE AND THROAT IRRITATION

Aluminum flake will react with water slowly generating hydrogen gas and heat. Care should be taken when opening a previously used container to allow possible built-up pressure to escape (hold down lid with one hand while opening container away from yourself with the other hand).

NOTICE: Repeated and prolonged exposure to solvents may lead to permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are signs that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.


Keep away from heat and flame. **Use only with adequate ventilation.** Do not breathe vapors, spray mist or sanding dust. Avoid contact with eyes and prolonged or repeated contact with skin. Wear eye protection and gloves. To avoid breathing vapors or spray mist, open window and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear a properly fitted vapor/particulate respirator approved by NIOSH for use with paints or leave the area. In all cases follow respirator manufacturer's directions for respirator use. Close container after each use.

FIRST AID: If affected by inhalation of vapors or spray mist, remove to fresh air. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and call a physician; for skin, wash thoroughly with soap and water. In case of ingestion — **DO NOT** induce vomiting, get medical help immediately.

IN CASE OF: **FIRE** — Use foam, CO₂, dry chemical, or water fog.
SPILL — Absorb with inert material and dispose of as specified under Thinning/Cleanup.

KEEP OUT OF REACH OF CHILDREN

**Material Safety Data Sheets available
on request from your servicing dealer.**



Printed on
Recycled Paper

SECTION IV FIRE AND EXPLOSION HAZARD DATA

D.O.T. FLAMMABILITY CLASS.: NOT REGULATED FLASH POINT: > 250 F PMCC
LEL: Not Applicable
EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS:
Toxic gases may form when product burns.
Closed containers may burst if exposed to extreme heat or fire.
SPECIAL FIRE FIGHTING PROCEDURES:
Cool exposed containers with water. Use self-contained breathing apparatus.

SECTION V HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - ACUTE:
Inhalation - Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea.
Contact - Causes eye irritation.
Ingestion of large amounts could cause serious injury.
EFFECTS OF OVEREXPOSURE - CHRONIC:
Contains: Crystalline Silica which has been determined to be carcinogenic to humans (1) by IARC when in respirable form. Risk of cancer depends on duration and level of inhalation exposure to dust from sanding the dried paint or spray mist.
NOTICE: Reports have associated permanent brain and nervous system damage with repeated, prolonged overexposure to solvents among persons engaged in the painting trade. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:
None expected when used in accordance with Safe Handling and Use Information (Section VIII).
Inhalation statement: Sanding dust inhalation may cause lung damage.
PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION
EMERGENCY AND FIRST AID PROCEDURES :
Inhalation - Remove to fresh air. Get medical help for any breathing difficulty.
Eye Contact - Flush thoroughly with water. Call physician.
Skin Contact - Wash with soap and water.
Ingestion - Drink 1 or 2 glasses of water to dilute.
DO NOT induce vomiting. Call physician.

SECTION VI REACTIVITY DATA

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR
CONDITIONS TO AVOID: Elevated temperatures
HAZARDOUS DECOMPOSITION PRODUCTS:
Burning may produce carbon dioxide and carbon monoxide.
INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Flush with water. Absorb with sawdust or rags.
WASTE DISPOSAL METHOD:
Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

SECTION VIII SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:

Use NIOSH approved respirator specified for protection against paint spray mist and sanding dust in restricted or confined areas.

VENTILATION:

Adequate to maintain working atmosphere below T.L.V. and L.E.L.

(See Sect. II for ingredient data and concentrations). Mechanical exhaust may be required in confined areas.

PROTECTIVE GLOVES: Waterproof during repeated contact.

EYE PROTECTION : Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES:

Remove and wash clothing before reuse. Wash hands before eating, smoking or using the washroom.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Do not throw or drop containers.

OTHER PRECAUTIONS :

Avoid contact with eyes and prolonged contact with skin or breathing of spray mist or sanding dust.

Close container after each use. Keep out of reach of children. Do not take internally.

SECTION XX

HMIS (Hazardous Materials Identification System) (R) NPCA
HMIS is a recognized workplace Hazard Communications System as required by OSHA (29 CFR 1910.1200). Information on establishing a compliant hazardous communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division
5724 N. Pulaski Rd., Chicago, IL 60646
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings; the contractor/employer has ultimate responsibility for HMIS rating where this system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's as it depends on application technique and the workplace ventilation. Please read Sections II through IX of this MSDS before deciding on appropriate protective equipment and beginning work. There are codes available for this section which can be obtained from Labelmaster. This product contains at least one toxic chemical listed in Section II that is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372.

DISCLAIMER

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

NOTICE: Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. Exposure to lead dust or fumes may cause adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For additional information, contact the USEPA/Lead Information Hotline at 1-800-LEAD-FYI.