



# Request for Quote

Page 1 of 1

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS  
 ONE CAPITOL HILL  
 PROVIDENCE RI 02908

CREATION DATE : 12-SEP-17  
 BID NUMBER: 7554618,2  
 TITLE: BOX TRUCK - REFRIGERATION, VAN BODY AND LIFT GATE  
 BID CLOSING DATE AND TIME:26-SEP-2017 01:00:00

BUYER: Mosca, Gary  
 PHONE #: 401-574-8124

B  
I  
L  
L  
S  
M  
I  
T  
H  
O  
 DOA-CS STATE FLEET  
 ONE CAPITOL HILL, 2ND FLOOR  
 SMITH ST  
 PROVIDENCE, RI 02908  
 US

S  
H  
I  
P  
T  
O  
 DOA-CS STATE FLEET  
 ONE CAPITOL HILL, 2ND FLOOR  
 SMITH ST  
 PROVIDENCE, RI 02908  
 US

Requisition Number: 1522665  
 Amendment Description: Revised Specification Sheet (attached)  
 Addendum #2

Line	Description	Quantity	Unit	Unit Price	Total
1	Refrigeration Box Truck per the attached specifications. Provide the following information:  Make/Manufacturer: _____  Model: _____  Model Year: _____  Anticipated Delivery: _____	1.00	Each		

Delivery: \_\_\_\_\_

Terms of Payment: \_\_\_\_\_

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer



State of Rhode Island  
Department of Administration / Division of Purchases  
One Capitol Hill, Providence, Rhode Island 02908-5855  
Tel: (401) 574-8100 Fax: (401) 574-8387

**ADDENDUM # 2**

9/13/17

**Solicitation #7554618**

**Title: Box Truck- Refrigeration, Van Body and Lift Gate**

**Submission Deadline: September 26, 2017 @ 1:00 PM**

---

**Per the issuance of ADDENDUM #2 the following are noted:**

**Revised Specification Sheet (attached):**

Prospective bidders and all concerned are hereby advised of the attached changes/modifications for the above referenced RFQ and are hereby requested to change their copies accordingly.

Bidders **MUST** include a signed copy of this addendum with their proposals submission as acknowledgement.

\_\_\_\_\_  
Company Name (print)

\_\_\_\_\_  
Signature of Authorized Representative

*Interested Parties should monitor this website on a regular basis, for any additional information that may be posted.*

**Gary P. Mosca**  
**Chief Buyer**

**DESCRIPTION: Conventional Cab 4x2 Box Truck with 14 FT. Van Body and Hydraulic Lift Gate**

<b>Quantity:</b>	<b>One (1)</b>			<b>Vendor Indicate Compliance Yes/No</b>
	<b>Color: White</b>			
<b>Department:</b>	<b>URI Dining Services</b>	<b>Fuel Type:</b>	<b>Diesel</b>	
<b>Division:</b>	<b>Warehouse</b>	<b>Color:</b> <small>*if not offered may be changed at award</small>	<b>White</b>	

<b>Bid # 7554618</b>	<b>Revised Specification Sheet - Addendum # 2</b>		
Bidders Must submit proposal using revised specification sheet			
STANDARD FEATURES	FOR VENDOR USE ONLY TO INDICATE COMPLIANCE		
	Yes/No	Specify Alternative (if responding no)	
<b>ENGINE</b> (Cummins B 6.7) EPA 2017, 240 HP @2400 RPM 560 lb-ft Torque @1600 RPM, 2600 RPM Governed Speed 240 Peak HP (Max)			
<b>ALTERNATOR</b> (Leece-Neville AV1160P2013) Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense			
<b>BATTERY</b> Maintenance-free, (3) 12-Volt 1950CCA Total Alternator (Leece-Neville AV1160P2013) Brush Type: 12 Volt 160 Amp. Capacity, Pad Mount, with remote Sense			
<b>BRAKES</b> AIR Dual System for Straight Truck Applications			
<b>HUB CAPS</b> MANUFACTURER'S STANDARD			
<b>BUMPERS</b> Powder Coated Gray (Argent)			
<b>COOLING SYSTEM</b> Heavy Duty Engine Cooling System			
<b>FLOOR</b> Factory Floor mats			
<b>FUEL TANK</b> Top Draw; D-Style, Non-polished aluminum 16" Tank Depth 50 U.S. Gal 189L Capacity, with quick Connect Outlet Mounted Lift Side, Under Cab			
<b>GVW</b> 25999			
<b>GAUGES</b> Standard Factory			
<b>GLASS</b> Power windows Power locks to include Express Down Feature			
<b>LIGHTS</b> Standard lighting package			
<b>HEATER/DEFROSTER</b> Factory Standard			
<b>MIRRORS</b>			

(2) ea L/R (Lang Mekra) Rectangular, Thermostatically Controlled Heated Heads, Black Heads, Brackets and Arms, Breakaway Type 7.55" x 14.1" Integral Convex Both Sides, 102" Inside Spacing		
<b>RADIO</b> MANUFACTURER'S STANDARD AM/FM		
<b>AIR CONDITIONING</b> (Blend-Air) With Integral Heater & Defroster		
<b>SEATING</b> Cloth seating Dark Grey		
<b>WINDSHIELD WIPERS</b> Factory Standard		
<b>HUB CAPS/WHEEL COVER</b> Front/Read (Accuride) DISC; 22.5" Painted Steel, 10-Stud (285.75MM BC) Hub Piloted, 5 Hand Hole, Flanged Nut, Metric Mount 7.50 DC Rims, with Steel Hubs.		
<b>STEERING</b> POWER		
<b>SUSPENSION SYSTEM</b> Factory Heavy Duty Suspension		
<b>TIRES</b> Tires to fit 19.5" Steel Rims		
<b>TRANSMISSION</b> AUTOMATIC (Allison 2100_RDS_P) 5 <sup>th</sup> Generation Controls; Close Ration 6-Speed with Double Overdrive On/Off Hwy; Includes Oil Level Sensor, with PTO provision less Retarder, with 26,000lb GVW & GCW Max.		
<b>WHEELBASE</b> Standard for model		
<b>STANDARD EQUIPMENT</b> Vehicles shall be equipped with all standard features and accessories as noted in the manufacturer's literature for proposed model. No deletion of standard equipment and accessories will be allowed without approval of State Fleet Operations.		
<b>SAFETY</b> Vehicles shall be equipped with all safety standards as administered by the National Highway Traffic and Safety Administration. This is to include ABS if available in model bid. All vehicles will be required to have SRS on drivers side		
<b>PRE-DELVIERY</b> Vehicle shall be completely inspected, serviced and cleaned by the vendor in accordance with pre-delivery service standards. The manufacturer's warranty (minimum of 3 years of 36,000 miles), owner's manual and related information shall be delivered with each unit. Deliver window sticker with details of factory options with each vehicle. No dealer identification on delivered vehicle. Include front license plate bracket. <b>All fluids must be topped off. Fuel Tank minimum ½ tank.</b>		
<ul style="list-style-type: none"> <li>• <b>Front License Plate Bracket</b> <ul style="list-style-type: none"> <li>• <b>Two (2) sets of keys required</b></li> </ul> </li> </ul>		

<b>Morgan Nominal Dry Freight Insulated Van Body 14 FT PA-morgantown Model# GVSDI09114096</b>		
<b>Sub-frame</b> 3" I-Beam Crossmembers on 12" Centers with 4" Long-rail (Qty 1)		
Mylar tape is applied between all steel sub-frame components and extruded aluminum lower (qty 1)		
Extra cross-members (qty 3)		
Locate (3) extra cross-members at rear on 6 in. center (qty 1)		
<b>Mounting</b> Full mount-U Bolt (qty 1)		
Mud-flaps-Morgan 24"x36" Black		
<b>Floor</b> 1 1/8 in laminated hardwood fastened to sub-frame with 2 countersunk screws per floor board per cross member in a staggered pattern. Floor boards are ship lapped and pre-undercoated for protection from elements. (qty 1)		
<b>Threshold</b> steel galvanized angle flush to rear		
<b>Rear Door</b> Morgan standard rear overhead door (qty 1)		
<b>Rear Frame</b> Header sub-component galvanized with 35 or S36 lights (qty 1)		
Post sub-component stainless steel for overhead door with recessed combo lights (qty 1)		
Endplate sub-component for overhead door for 4.12" end plate (qty 1)		
Galvanized header post gusset (qty 1)		
<b>Skins-sides</b> .040 aluminum preprinted white (qty 1)		
Rivets for front and sidewalls-14 body (qty 1)		
<b>Side wall</b> Extruded aluminum top and bottom rails with 1 3/8 in. deep galvanized steel z-shaped vertical posts installed on 16 in centers curbside (qty 1)		
Extruded aluminum top and bottom rails with 1 3/8 in. deep galvanized steel z-shaped vertical posts installed on 16 in. centers roadside (qty 1)		
<b>Liner-side</b> Glassboard full height no door		
<b>Scuff</b> side scuff special costing (qty 2). SPR170653 1/8" Aluminum tread plate scuff 40" up above 6" pan floor sides and front		
<b>Interior Ties</b> Series e-track recessed sidewall (qty 4)		
Locate recessed row at 24 in from top of floor to center of track (qty 1)		
Locate recessed row at 50 in from top of floor to center of track (qty 1)		
Series E track recessed front wall (qty 2)		

Locate recessed row at 24in. from top of floor to center of track (qty 1)		
Locate recessed row at 50 in. from top of floor to center of track (qty 1)		
<b>Front End</b> Aerodynamic aluminum RADII with steel Z post (qty 1)		
<b>Skins-Front</b> .040 Aluminum pre-painted white (qty 1)		
<b>Liner-Front</b> Liner-Front 3/32" glassboard		
<b>Scuff</b> Scuff-Front special costing		
<b>Insulation</b> Fiberglass insulation for rear frame		
2 9/16" Polystyrene block foam - between sills (qty 1)		
4" polystyrene block foam-front (qty 1)		
1 5/16" polystyrene block foam-ceiling (qty 1)		
1 5/16" polystyrene block foam-side no door (qty 2)		
<b>Reefer (Mounting hardware)</b> Front wall, non thru two piece reefer mounting equipment		
Universal reinforcement for two piece units (qty 1)		
Reinforcement for ceiling - Integra 50X (qty 1)		
(4) Folding steps and grab handle mounted on front radius		
<b>Roof</b> .032 one piece aluminum sheet with anti-srag roof bows on 24 in centers with crowned roof design which prevents water/ice pooling		
without radll, used in conjunction with dormer		
<b>Liner-Ceiling</b> ceiling liner 3/32" glassboard (qty 1)		
<b>Interior lights</b> One interior dome lamp w/ ceiling liner (qty 1)		
Total dome light(s) =1		
Switch with indicator mounted in cab dash		
Switch for dome light circuit		
<b>LIFTGATE</b> Palfinger ILR- 25 54x80 2500 lb capacity aluminum platform.		
Liftgate power cut-off switch mounted in cab dash		
Liftgate narrow structural with 3"x24" rubber bumper blocks		
<b>Exterior lights</b> TECNIQ S36 LED sealed clearance light, per FMVSS-108 installed in front corner caps side top rails and five across rear header (qty 1)		
Components used for chassis wiring and lights int/grnd (qty 1)		
License plate light mounted rear corner post (qty 1)		
<b>Paint</b> rear end plate - black		

<b>REFRIGERATION UNIT</b>  Integra 40X Truck Refrigeration Unit Includes: <ul style="list-style-type: none"> <li>• Capacity @35F: 15,000 Btu; @OF: 8.100 Btu; @-ZOF: 4,000 Btu</li> <li>• Heating Capacity: 13,640 Btu</li> <li>• Deluxe Cab Command with Full Alarm Codes</li> <li>• Composite Skins</li> <li>• Six Cylinder Swash Plate Compressor</li> <li>• e Slim Line Ceiling Evaporator</li> <li>• Hot Gas Heat/Defrost</li> <li>• R-404A Refrigerant</li> <li>• Condenser Valve Supplemental Heat</li> </ul>		
End specification sheet.		

**Contract Terms and Conditions**

**Table of Contents**

Terms and Conditions.....VI  
    BID STANDARD TERMS AND CONDITIONS .....VI  
    TERMS AND CONDITIONS FOR THIS BID .....VI  
    RIVIP INFO - BID SUBMISSION REQUIREMENTS .....VI  
    DELIVERY PER AGENCY .....VI  
    FISCAL YEAR - AWARD EXTENDING PAST FISCAL YR END .....VI  
    AUTO / VEHICLE PURCHASE ORDER .....VI  
    AWARD .....VII  
    VENDOR SPECIFICATIONS .....VII



**Terms and Conditions**

**BID STANDARD TERMS AND CONDITIONS**

**TERMS AND CONDITIONS FOR THIS BID**

**RIVIP INFO - BID SUBMISSION REQUIREMENTS**

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer. When delivering offers in person to One Capitol Hill, vendors are advised to allow at least one hour additional time for clearance through security checkpoints.

MAILING ADDRESS FOR BID PROPOSALS ISSUED BY THE STATE OF RHODE ISLAND,  
DIVISION OF PURCHASES

All Bid Proposals must be submitted by mail or hand delivered to:

- State of Rhode Island
- Department of Administration
- Division of Purchases, Second floor
- One Capitol Hill
- Providence, RI 02908-5855

**DIVESTITURE OF INVESTMENTS IN IRAN REQUIREMENT:**

No vendor engaged in investment activities in Iran as described in R.I. Gen. Laws §37-2.5-2(b) may submit a bid proposal to, or renew a contract with, the Division of Purchases. Each vendor submitting a bid proposal or entering into a renewal of a contract is required to certify that the vendor does not appear on the list maintained by the General Treasurer pursuant to R.I. Gen. Laws §37-2.5-3.

**DELIVERY PER AGENCY**

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.

**FISCAL YEAR - AWARD EXTENDING PAST FISCAL YR END**

AWARDS EXTENDING BEYOND JUNE 30TH ARE SUBJECT TO AVAILABILITY OF FUNDS. CONTINUATION OF THE CONTRACT BEYOND THE INITIAL FISCAL YEAR WILL BE AT THE DISCRETION OF THE STATE. TERMINATION MAY BE EFFECTED BY THE STATE BASED UPON DETERMINING FACTORS SUCH AS UNSATISFACTORY PERFORMANCE OR THE DETERMINATION BY THE STATE TO DISCONTINUE THE GOODS/SERVICES, OR TO REVISE THE SCOPE AND NEED FOR THE TYPE OF GOODS/SERVICES; ALSO MANAGEMENT OWNER DETERMINATIONS THAT MAY PRECLUDE THE NEED FOR GOODS/SERVICES.

**AUTO / VEHICLE PURCHASE ORDER**

THE FOLLOWING ADDITIONAL TERMS AND CONDITIONS APPLY TO THIS PURCHASE ORDER: 1. ALL VEHICLES MUST BE DELIVERED WITHOUT DEALER'S NAME OR ADVERTISING OF ANY TYPE VISIBLE ON THE BODY. 2. EACH VEHICLE DELIVERED TO THE STATE MUST BE ACCOMPANIED BY A "CERTIFICATE OF ORIGIN" CONTAINING THE MANUFACTURER'S VEHICLE IDENTIFICATION NUMBER (VIN), THE NUMBER OF ENGINE CYLINDERS AND ENGINE TYPE, A GENERAL DESCRIPTION OF THE BODY, AND THE MODEL

NAME OR NUMBER. CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO STATE OF RI/FLEET OPERATIONS, ONE CAPITOL HILL, PROVIDENCE, RI 02908 UNLESS THE VEHICLE IS BEING PURCHASED BY THE RHODE ISLAND STATE POLICE. IF SO, CERTIFICATE OF ORIGIN MUST BE ASSIGNED TO RHODE ISLAND STATE POLICE, 311 DANIELSON PIKE, NORTH SCITUATE, RI 02857. 3. THE VENDOR MUST WARRANT FULL AND UNENCUMBERED TITLE TO THE VEHICLE(S) AS OF THE DATE OF DELIVERY TO THE STATE. 4. TITLE CERTIFICATES MUST BE PROVIDED AT THE TIME OF DELIVERY TO THE STATE.

**AWARD**

THE STATE, AT ITS SOLE DISCRETION, SHALL RESERVE THE RIGHT TO MAKE ONE OR MULTIPLE AWARDS FOR THIS REQUIREMENT AND/OR TO REJECT ANY OR ALL BIDS.

**VENDOR SPECIFICATIONS**

ALL VENDORS MUST INCLUDE SPECIFICATIONS WITH BID PROPOSAL (EVEN THOSE BIDDING BRAND SPECIFIED). FAILURE TO SUBMIT SPECIFICATIONS WITH BID PROPOSAL MAY RESULT IN DISQUALIFICATION OF BID. ITEMS IN CATALOGS MUST BE CLEARLY MARKED AND PAGES TABBED.