



Request for Quote

STATE OF RHODE ISLAND AND PROVIDENCE PLANTATIONS
 ONE CAPITOL HILL
 PROVIDENCE RI 02908

BUYER: McGurn, Cheryl A
 PHONE #: 401-574-8130

CREATION DATE : 18-SEP-18
BID NUMBER: 7596708,1
TITLE: POLICE AND SECURITY UNIFORMS FOR CCRI AND RIC
BLANKET START : 01-NOV-18
BLANKET END : 30-JUN-20
BID CLOSING DATE AND TIME: 11-OCT-2018 10:30:00

**B
I
L
L
T
O**
 RIC-PURCHASING
 600 MOUNT PLEASANT AVENUE
 PROVIDENCE, RI 02908
 US

**S
H
I
P
T
O**
 RIC-PURCHASING
 600 MOUNT PLEASANT AVENUE
 PROVIDENCE, RI 02908
 US

Requisition Number:

Note to Bidders: ATTACHMENT "A" TO BE FILLED OUT AND RETURNED WITH BID SOLICITATION.

Questions concerning this solicitation must be received by the Division of Purchases at: Cheryl.mcgurn@purchasing.ri.gov no later than 10/3/2018 @ 3:00 PM (EST). Questions should be submitted in a Microsoft Word attachment. Please reference RFQ # 7594587 on all correspondence. Questions received, if any, will be posted on the internet as an Addendum to this solicitation. It is the responsibility of all interested parties to download this information.

Any Supplier responding to this solicitation must be an Authorized Dealer/Distributor of the Name Brands listed.

NO SUBSTITUTIONS ACCEPTED.

Amendment Description: ATTACHMENT "A"

Line	Description	Quantity	Unit	Unit Price	Total
1	11/1/18 - 6/30/20 POLICE AND SECURITY UNIFORMS FOR CCRI AND RIC. PER THE ATTACHED SPECIFICATION	1.00	Total		

Delivery: _____

Terms of Payment: _____

It is the Vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form must be attached to the front of the offer

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	<p>IF THIS IS A MULTI-YEAR BID/CONTRACT. CONTINUATION OF THE CONTRACT BEYOND THE INITIAL FISCAL YEAR WILL BE AT THE DISCRETION OF THE UNIVERSITY. TERMINATION MAY BE EFFECTED BY THE UNIVERSITY BASED UPON DETERMINING FACTORS SUCH AS UNSATISFACTORY PERFORMANCE OR THE DETERMINATION BY THE UNIVERSITY TO DISCONTINUE THE GOODS/SERVICES, OR TO REVISE THE SCOPE AND NEED FOR THE TYPE OF GOODS/SERVICES; ALSO MANAGEMENT OWNER DETERMINATIONS THAT MAY PRECLUDE THE NEED FOR GOODS/ SERVICES AND SUBJECT TO AVAILABILITY OF FUNDS.</p>			
	<p>DELIVERY AS REQUESTED</p>			
	<p>BLANKET REQUIREMENTS: November 1, 2018 - June 30, 2020</p>			
	<p>Campus Police Uniforms</p>			
	<p>The following bid is for the 2 Public Institutions of Higher Education in Rhode Island; Rhode Island College and the Community College of Rhode Island.</p>			
	<p>Each institution and their individual requirements have been identified below.</p>			
	<p>The following specifications apply to all:</p>			
	<p>No return or restock fee to be added. If an item is returned, there will not be a return fee, a restock fee, or anything associated with a re-order. No shipping fees to be added. Shipping is to be included in price of item.</p>			
	<p>Section A - Rhode Island College (RIC)</p>			
	<p>Rhode Island College is a single campus in Providence RI. http://www.ric.edu/</p>			
1	Blauer Cruiser Jacket - 9010Z Color: Dark Navy Sew on two shoulder patches. Hard epaulet matching uniform piping to be sewn on in place of original piping. (Note: 48" chest and up will have a 20% additional charge) FY 19 - 11/1/18 - 6/30/19	8	\$ _____ /ea	\$ _____
2	Blauer Cruiser Jacket - 9010Z Color: Dark Navy Sew on two shoulder patches. Hard epaulet matching uniform piping to be sewn on in place of original piping. (Note: 48" chest and up will have a 20% additional charge) FY 20 - 7/1/19 - 6/30/20	8	\$ _____ /ea	\$ _____
3	Walls Blizzard Proof Ultra Cover-All - Style #2024 Color: Black Reflective stripe sewn on legs. Silver embroidery lettering (RIC police) sewn on back of suit. Badge tab and velcro for badge number board to be sewn on right chest. (Note: Sizes XXL and above will have a 20% additional charge) FY 19 - 11/1/18 - 6/30/19	4	\$ _____ /ea	\$ _____
4	Walls Blizzard Proof Ultra Cover-All - Style #2024 Color: Black Reflective stripe sewn on legs. Silver embroidery lettering (RIC police) sewn on back of suit. Badge tab and velcro for badge number board to be sewn on right chest. (Note: Sizes XXL and above will have a 20% additional charge) FY 20 - 7/1/19 - 6/30/20	4	\$ _____ /ea	\$ _____
5	#733 Blauer Defender Reversible raincoat Color: Black/F Yellow (Note: Sizes XXL and above will have a 20% additional charge) FY 19 - 11/1/18 - 6/30/19	3	\$ _____ /ea	\$ _____
6	#733 Blauer Defender Reversible Raincoat	3	\$ _____ /ea	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	Color: Black/F Yellow (Note: Sizes XXL and above will have a 20% additional charge) FY 20 - 7/1/19 - 6/30/20			
7	#210 Blauer Commando V-Neck Sweater Color: Dark Navy Sew on the following: Velcro to hold number board (on right chest) piping and hard shoulder epaulets to match uniform. (Note: Sizes XXL and above will have a 20% additional charge) FY 19 - 11/1/18 - 6/30/19	4	\$ _____ /ea	\$ _____
8	#210 Blauer Commando V-Neck Sweater Color: Dark Navy Sew on the following: Velcro to hold number board (on right chest) piping and hard shoulder epaulets to match uniform. (Note: Sizes XXL and above will have a 20% additional charge) FY 20 - 7/1/19 - 6/30/20	4	\$ _____ /ea	\$ _____
9	Uniform Long Sleeve Shirts per spec No. 4290-URI-04 #333 Range by Hamburger, 55% Dacron Polyester/45% wool with a mechanical 10-12% filling stretch. 14 1/2 oz. serge weave Color: Navy Blue (Note: Chest size of 48" and above will have a 15% additional charge) FY 19 - 11/1/18 - 6/30/19	24	\$ _____ /ea	\$ _____
10	Uniform Long Sleeve Shirts per spec No. 4290-URI-04 #333 Range by Hamburger, 55% Dacron Polyester/45% wool with a mechanical 10-12% filling stretch. 14 1/2 oz. serge weave Color: Navy Blue (Note: Chest size of 48" and above will have a 15% additional charge) FY 20 - 7/1/19 - 6/30/20	24	\$ _____ /ea	\$ _____
11	Uniform Trousers Per Spec. No. 4290-URI-03 Trousers uniform dress (Winter) Color: Navy Blue with Maroon Piping FY 19 - 11/1/18 - 6/30/19	24	\$ _____ /ea	\$ _____
12	Uniform Trousers Per Spec. No. 4290-URI-03 Trousers uniform dress (Winter) Color: Navy Blue with Maroon Piping FY 20 - 7/1/19 - 6/30/20	24	\$ _____ /ea	\$ _____
13	Summer Uniform Shirts Spec No. 4290-URI-02 #651 Range by Hamburger Custom Tailor fitted to individual. Material: 55% Dacron Polyester / 45% worsted wool, 10-12% mechanical filling stretch. FY 19 - 11/1/18 - 6/30/19	24	\$ _____ /ea	\$ _____
14	Summer Uniform Shirts Spec No. 4290-URI-02 #651 Range by Hamburger Custom Tailor fitted to individual. Material: 55% Dacron Polyester / 45% worsted wool, 10-12% mechanical filling stretch. FY 20 - 7/1/19 - 6/30/20	24	\$ _____ /ea	\$ _____
15	Summer Uniform Trousers	24	\$ _____ /ea	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	Spec. NO. 4290-URI-01 #333 Range by Hamburger custom tailor made. Material: 55% Dacron Polyester/45% wool with a mechanical 10-12% filling stretch. Construction: 75 ends per inch, 67 picks per inch Breaking strength: warp: 195 lbs. Filling: 170 lbs. Fiber Length: 3-3.5" Weight: 10.5-11.5 oz. serge weave Color: Navy Blue with Maroon Piping (Note: Waist sizes of 42" and above will have a 15% additional charge) FY 19 - 11/1/18 - 6/30/19			
16	Summer Uniform Trousers Spec. NO. 4290-URI-01 #333 Range by Hamburger custom tailor made. Material: 55% Dacron Polyester/45% wool with a mechanical 10-12% filling stretch. Construction: 75 ends per inch, 67 picks per inch Breaking strength: warp: 195 lbs. Filling: 170 lbs. Fiber Length: 3-3.5" Weight: 10.5-11.5 oz. serge weave Color: Navy Blue with Maroon Piping (Note: Waist sizes of 42" and above will have a 15% additional charge) FY 20 - 7/1/19 - 6/30/20	24	\$ _____ /ea	\$ _____
17	Dress Garrison Hat Type: Garrison/Round Material: 55% Dacron Polyester/45% Wool with a mechanical 10% - 12% filling stretch. Weight: 14 1/2 ounce serge weave P & F Construction: Leather Sweat Band with two row of red sash on band. Plastic badge ring holder above front band. FY 19 - 11/1/18 - 6/30/19	10	\$ _____ /ea	\$ _____
18	Dress Garrison Hat Type: Garrison/Round Material: 55% Dacron Polyester/45% Wool with a mechanical 10% - 12% filling stretch. Weight: 14 1/2 ounce serge weave P & F Construction: Leather Sweat Band with two row of red sash on band. Plastic badge ring holder above front band. FY 20 - 7/1/19 - 6/30/20	10	\$ _____ /ea	\$ _____
19	Blauer 8110X Mock Turtleneck 3XDRY. 90% cotton / 10% LYCRA blend fabric with 4-way stretch performance 10.5 oz. jersey knit. Dark Navy. FY 19 - 11/1/18 - 6/30/19	20	\$ _____ /ea	\$ _____
20	Blauer 8110X Mock Turtleneck 3XDRY. 90% cotton / 10% LYCRA blend fabric with 4-way stretch performance 10.5 oz. jersey knit. Dark Navy. FY 20 - 7/1/19 - 6/30/20	20	\$ _____ /ea	\$ _____
21	Thorogood Commando II- The Deuce > 8" Waterproof Lace Up Boot Upper: Black full Grain Leather/Black Action Leather/1200 Denier Nylon Construction: Cement Outsole: Two Density Rubber with Integrated EVA Impact Pads Lining: Two Zone Wicking Mesh Insole: Removable Two Density Polyurethane "Shock Zone" Insert with Air Flow Vents Shank: Composite Special Features: Total Non-Metallic. Thoro>dri TM WATERPROOF System.	10	\$ _____ /ea	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	Blood Borne Pathogen Compliant. <i>FY 19 - 11/1/18 - 6/30/19</i>			
22	Thorogood Commando II- The Deuce > 8" Waterproof Lace Up Boot Upper: Black full Grain Leather/Black Action Leather/1200 Denier Nylon Construction: Cement Outsole: Two Density Rubber with Integrated EVA Impact Pads Lining: Two Zone Wicking Mesh Insole: Removable Two Density Polyurethane "Shock Zone" Insert with Air Flow Vents Shank: Composite Special Features: Total Non-Metallic. Thoro>dri TM WATERPROOF System. Blood Borne Pathogen Compliant. <i>FY 20 - 7/1/19 - 6/30/20</i>	10	\$ _____ /ea	\$ _____
23	Thorogood Classic Leather Oxford Shoe Upper: Black Smooth High Shine Leather Construction: Goodyear Weave Outsole: Single Density Soft Polyurethane Lining: Comfort Weave Insole: Removable Dual Density Ultimate Shock Absorption TM Footbed Midsole: Rubber Shank: Fiberglass Special Features: US Postal Certified. Made in USA by ISO 9001 Certified Shoe Company. <i>FY 19 - 11/1/18 - 6/30/19</i>	10	\$ _____ /ea	\$ _____
24	Thorogood Classic Leather Oxford Shoe Upper: Black Smooth High Shine Leather Construction: Goodyear Weave Outsole: Single Density Soft Polyurethane Lining: Comfort Weave Insole: Removable Dual Density Ultimate Shock Absorption TM Footbed Midsole: Rubber Shank: Fiberglass Special Features: US Postal Certified. Made in USA by ISO 9001 Certified Shoe Company. <i>FY 20 - 7/1/19 - 6/30/20</i>	10	\$ _____ /ea	\$ _____
			Total RIC	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	Section B - Community College of Rhode Island (CCRI)			
	CCRI consists of 4 campuses; deliveries will be made to both the			
	Flanagan Campus in Lincoln and the Knight Campus in Warwick.			
	http://www.ccri.edu/			
25	8560 – Trousers. Pants will be fitted; no stitching to be visible on pant leg, hems all will have a 1-inch black braid. Color: Black Material: Polyester <i>FY 19 - 11/1/18 - 6/30/19</i>	120	\$ _____ /ea	\$ _____
26	8560 – Trousers. Pants will be fitted; no stitching to be visible on pant leg, hems all will have a 1-inch black braid. Color: Black Material: Polyester <i>FY 20 - 11/1/19 - 6/30/20</i>	120	\$ _____ /ea	\$ _____
27	8910 – Short Sleeve shirt, Blauer Material: Rayon with epilates (grey w/black border; silver buttons patrol officers, lieutenants will have grey w/black border with gold buttons on pockets. Captains, deputy and Chief will have black w/gold border with gold buttons on pockets/epilates. A uniform patch will be on left and reverse American flag on right. Color: Heather Grey <i>FY 19 - 11/1/18 - 6/30/19</i>	120	\$ _____ /ea	\$ _____
28	8910 – Short Sleeve shirt, Blauer Material: Rayon with epilates (grey w/black border; silver buttons patrol officers, lieutenants will have grey w/black border with gold buttons on pockets. Captains, deputy and Chief will have black w/gold border with gold buttons on pockets/epilates. A uniform patch will be on left and reverse American flag on right. Color: Heather Grey <i>FY 20 - 7/1/19 - 6/30/20</i>	120	\$ _____ /ea	\$ _____
29	8900 – Long Sleeve shirt, Blauer Material: Rayon with epilates (grey w/black border) silver buttons patrol, lieutenants will have (grey w/black border) gold buttons on pockets. Sleeve Cuffs, blk ¼" line. Captain, deputy, chief will have black w/gold border, gold buttons on pockets. Sleeve cuffs blk/gold border. Police Patch on left shoulder and reverse American Flag on right shoulder. Color: Heather Grey <i>FY 19 - 11/1/18 - 6/30/19</i>	120	\$ _____ /ea	\$ _____
30	8900 – Long Sleeve shirt, Blauer Material: Rayon with epilates (grey w/black border) silver buttons patrol, lieutenants will have (grey w/black border) gold buttons on pockets. Sleeve Cuffs, blk ¼" line. Captain, deputy, chief will have black w/gold border,	120	\$ _____ /ea	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	gold buttons on pockets. Sleeve cuffs blk/gold border. Police Patch on left shoulder and reverse American Flag on right shoulder. Color: Heather Grey FY 20 - 7/1/19 - 6/30/20			
31	210 – Blauer V-neck sweater Color: black with uniform patch on right shoulder and reverse American Flag on left shoulder FY 19 - 11/1/18 - 6/30/19	30	\$ _____ /ea	\$ _____
32	210 – Blauer V-neck sweater Color: black with uniform patch on right shoulder and reverse American Flag on left shoulder FY 20 - 7/1/19 - 6/30/20	30	\$ _____ /ea	\$ _____
33	8300 – Blauer Tie, Black, 18 & 20 inch FY 19 - 11/1/18 - 6/30/19	30	\$ _____ /ea	\$ _____
34	8300 – Blauer Tie, Black, 18 & 20 inch FY 20 - 7/1/19 - 6/30/20	30	\$ _____ /ea	\$ _____
35	Uniform Hats – Blauer Color: Black with borders above the brim. All hats will be pinned down, patrol officers will have silver band and badge. Lt.'s & Capt.'s, Deputy, Chief will have a gold band and badge. FY 19 - 11/1/18 - 6/30/19	30	\$ _____ /ea	\$ _____
36	Uniform Hats – Blauer Color: Black with borders above the brim. All hats will be pinned down, patrol officers will have silver band and badge. Lt.'s & Capt.'s, Deputy, Chief will have a gold band and badge. FY 20 - 7/1/19 - 6/30/20	30	\$ _____ /ea	\$ _____
37	9101 – Reversible hat cover, Black FY 19 - 11/1/18 - 6/30/19	30	\$ _____ /ea	\$ _____
38	9101 – Reversible hat cover, Black FY 20 - 7/1/19 - 6/30/20	30	\$ _____ /ea	\$ _____
39	9154 – Baseball style police cap, Blauer Color: black, adjustable strap w/CCRI PD logo white lettering for patrol, gold lettering for lt.'s, capt.'s, chief FY 19 - 11/1/18 - 6/30/19	30	\$ _____ /ea	\$ _____
40	9154 – Baseball style police cap, Blauer Color: black, adjustable strap w/CCRI PD logo white lettering for patrol, gold lettering for lt.'s, capt.'s, chief FY 20 - 7/1/19 - 6/30/20	30	\$ _____ /ea	\$ _____
41	Number Boards –Lt. & Patrol officers will have black/grey border. Captains & Chief will have black/gold border. Honor Guard will have white/black border. FY 19 - 11/1/18 - 6/30/19	60	\$ _____ /ea	\$ _____
42	Number Boards –Lt. & Patrol officers will have	60	\$ _____ /ea	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
	black/grey border. Captains & Chief will have black/gold border. Honor Guard will have white/black border. FY 20 - 7/1/19 - 6/30/20			
43	9910Z – Blauer winter jacket Color: black with uniform patch on right shoulder and reverse American flag on left shoulder. FY 19 - 11/1/18 - 6/30/19	30	\$ _____/ea	\$ _____
44	9910Z – Blauer winter jacket Color: black with uniform patch on right shoulder and reverse American flag on left shoulder. FY 20 - 7/1/19 - 6/30/20	30	\$ _____/ea	\$ _____
45	733 – Blauer, Raincoat, Black FY 19 - 11/1/18 - 6/30/19	30	\$ _____/ea	\$ _____
46	733 – Blauer, Raincoat, Black FY 20 - 7/1/19 - 6/30/20	30	\$ _____/ea	\$ _____
47	6001 – Reversible Jacket, Blauer Color: Black Uniform patch on left, reverse American flag on right, silver buttons for patrol, gold buttons for Lt.'s, Capt.'s, Deputy, & Chief. FY 19 - 11/1/18 - 6/30/19	30	\$ _____/ea	\$ _____
48	6001 – Reversible Jacket, Blauer Color: Black Uniform patch on left, reverse American flag on right, silver buttons for patrol, gold buttons for Lt.'s, Capt.'s, Deputy, & Chief. FY 20 - 7/1/19 - 6/30/20	30	\$ _____/ea	\$ _____
49	Thorogood Classic Leather Oxford Shoe Color: Black FY 19 - 11/1/18 - 6/30/19	30	\$ _____/ea	\$ _____
50	Thorogood Classic Leather Oxford Shoe Color: Black FY 20 - 7/1/19 - 6/30/20	30	\$ _____/ea	\$ _____
51	Thorogood-Dri Boot , Color: Black Stk: 834-6529 FY 19 - 11/1/18 - 6/30/19	30	\$ _____/ea	\$ _____
52	Thorogood-Dri Boot , Color: Black Stk: 834-6529 FY 20 - 7/1/19 - 6/30/20	30	\$ _____/ea	\$ _____
53	Garrison Belt , Color: Black Silver buckle for patrol, gold buckle for Lt.'s, Capt.'s & Chief FY 19 - 11/1/18 - 6/30/19	30	\$ _____/ea	\$ _____
54	Garrison Belt , Color: Black Silver buckle for patrol, gold buckle for Lt.'s, Capt.'s & Chief FY 20 - 7/1/19 - 6/30/20	30	\$ _____/ea	\$ _____
			Total CCRI	\$ _____

ATTACHMENT "A"				
ITEM NO.	DESCRIPTION	QUANTITY	UNIT PRICE	EXTENDED PRICE
			Total RIC	\$ _____
			Total CCRI	\$ _____
			Overall Total:	\$ _____

Specification No. 4290-04 Shirts, Uniform Dress Winter

Agency: Rhode Island College Police Department: (Main Campus) and CCRI Police

Classification and Scope:

The specification covers Uniform Shirts as described herein. Custom tailored fitted to individual.

Material: 55% Dacron polyester/45% Worsted wool #651 Range by Hamburger.

10-12% mechanical filling stretch

Weight: 14 oz. per linear yard plain weave 2 ply.

Color: Navy Blue

Applicable Specification: There are no other specifications applicable to this specification.

Requirements:

Design: Long sleeves shirt shall be 5 crease military style with banded dress collar and permanent silicone adhesive creases. There shall be epaulets, pleated pockets with scalloped pocket flaps, badge eyelets with internal support strap, 2-button adjustable cuffs and self-lined yoke. Patterns shall provide for extra long shirt tails.

Sleeves: Sleeve ends shall have plackets finishing 1 1/4 inches wide on the top placket and 1/2 inch wide under placket and shall have a single pleat where attached to the cuffs. Cuffs shall finish 2 1/2 inches wide, shall be constructed of two plies of shell fabric plus one ply of the specified interlining, and shall be topstitched 1/4 inch on the edges. The cuff shall be 2-button adjustable with buttons set side 3/4 inches apart on center. Sleeve setting and closing shall be sewn with an over edge safety stitch.

Special Requirements: Sleeves to have one (1) inch band of Red Serge Material at a position designated by agency. Buttons to be supplied by vendor. RIC & CCRI Police and Security will furnish shoulder emblems which are to be sewed on by vendor. Individual measurements and alternations to be furnished by vendor.

Collar: The collar shall be banded dress style. Collar shall be die cut with the collar stand measuring 1 1/2 inches high in back. Both the collar and collar stand shall be made of two plies of shell fabric plus one ply of the specified interlining. There shall be permanent collar stays sewn to the interlining so that no stitches are visible through the under collar. The collar shall be topstitched around the edges and collar points shall be 3 1/8 inches long. The collar stand shall close with one button.

Epaulets: Epaulets shall be die cut from shell fabric creased and interlined with the specified interlining, and then folded and topstitched. Epaulets shall be sewn into the sleeve head seam and shall measure 1 7/8 inches wide at the sleeve head and taper to 1 1/2 inches wide with the end finishing in a point. Epaulets shall be stitched to the shoulders with a row of stitch 2 1/2 inches from the sleeve head and sewn diagonally from each end of the seam to the sleeve. There shall be an unslit buttonhole at the pointed end of the epaulet with the specified button sewn on top. The epaulets shall then be topstitched along both edges of "V" forming the point to the shoulder of the shirt.

Pockets: There shall be two breast pockets with pleated patch pockets and scalloped pocket flaps. The patch pocket shall measure 5 1/2 inches wide and 5 3/4 inches long with mitered corners and a 1 1/2 inch box pleat stitched closed. The left pocket shall have a sewn pencil opening 1 1/4 inch wide. Hook tape 1/2 inch wide by 1 inch high shall be sewn to the upper corners of each pocket to secure the pocket flap. The scalloped pocket flap shall be die cut, creased and interlined with the specified interlining, then folded and topstitched. The top of the flap shall be set 3/4 inches above the top of the pocket and shall have one centered unslit buttonhole with a button. There shall be loop tape 1/2 inches wide by 1 inch high set on the under ply of the pocket to secure to the hook tape on the pocket. There shall be a pencil opening in the left flap 1 inch wide with the two rows of topstitching continuing across the pencil pocket opening.

Yoke: There shall be a two-ply back yoke lined on the inside with shell fabric. The yoke shall measure approximately 3 1/2 inches at the center and 3 inches at the sleeve head.

Fronts: The left front shall have a shell fabric top center placket measuring 1 1/1 inches wide and constructed with the specified interlining. The placket shall show two rows of stitching 1 inch wide. The button stand shall have an additional row of topstitching along the edge. There shall be six buttons and buttonholes set down the front and one button and buttonhole on the collar stand.

Stitching: All stitching shall be single needle at 10-12 stitches per inch except for sleeving and closing seams which shall be safety stitched.

Badge Attachment: There shall be an inside sling constructed of shell fabric 1 1/8 inches wide extending front the shoulder seam to the pocket on the left front. There shall be two unslit horizontal 1/2 inch buttonholes set vertically on the left front 1 3/8 inches center to center and with the bottom buttonhole set 1 1/4 inches above the top of the pocket flap.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, fiber content, and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and shirts shall be pressed completely prior to packaging.

Packaging: Shirts shall be folded, pinned, and individually polybagged with cardboard, collar stand, and butterfly clip. Shirts shall be packed 3 to a box which shall be clearly labeled on one end with style number, quantity, color, and size.

Sizes and Measurements: Each shirt shall be marked with lot number, size, and fiber content and shall have a care instruction label sewn in it.

Testing Pre-bid Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Stock Product: To insure availability of style and color for the purpose of maintaining departmental uniformity for future purchases bidders must provide evidence in the form of catalogs, price lists, or similar written material that this item is currently available on an "as needed" basis. The pre-bid sample must be provided from current manufacturer's stock of the specified style. The successful bidder will be required to provide a full size run of try-on-garments within 10 days of agency approval, sizing of personnel, and for further evidence of in-stock availability.

Sampling and Inspection: Shirts will be inspected at point of delivery.

Packaging: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

Specification No. 4290-03 Trousers, Uniform, Dress Winter

Agency: Rhode Island College Police (Main Campus) and CCRI Police

Classification and Scope:

The specification covers Uniform Dress Trousers, of a worsted wool blend, machine washable and dry cleanable, to provide user comfort, uniform appearance durability, easy care and low maintenance cost. Custom tailored made.

Material: No 333 Range by Hamburger, 55% Dacron polyester/45% wool with a mechanical 10-12% filling stretch.

Construction: 75 ends per inch, 67 picks per inch

Breaking strength: Wrap: 195 lbs Filling: 170 lbs.

Fiber length: 3-3.5 inches

Weight: 14 ounce serge weave P & F

Color: Navy Blue

Applicable Specifications: There are no other specifications applicable to this specification.

Requirements:

Design: The uniform trousers shall be tailored split-seam construction dress uniform style with two straight side pockets, two button-tab hip pockets, two Billy hip pockets, one drop watch pocket and a wide waistband with belt loops inserted into the bottom and tacked to the top. There shall be a stretch waistband with a silicone shirt-grip stripe, permanent silicone adhesive creases on both the front and back of the legs, front crotch panels and fly lining with button table. The patterning shall allow generous seat and thigh let out to accommodate alterations and athletic builds. The trousers shall be machine washable/dryable as well as dry cleanable. The waistband construction and trouser patterning shall accommodate an optional removable wind proof breathable liner.

Construction:

Front Pockets: Front pockets shall be on-seam style with straight pockets. Pockets shall be constructed on one piece of the specified pocketing material finishing approximately 6.5 inch wide at the bottom of the pocket opening and 12.5 inches long from where the pocket is sewn into the waistband. There shall be a facing of shell fabric material running from the side seam and waistband and into the pocket measuring 2 inches wide. There shall be a facing of shell fabric material on the inside of the pocket away from the body measuring 1.5 inches wide. There shall be a straight bartack across the top of the pocket opening 1 inch down from the waistband and a straight bartack across the bottom of the pocket opening. The pocket opening shall be a minimum of 6 inches.

Hip Pockets: Hip pockets shall be inverted double corded type with button tabs. Finished pocket opening shall measure 5.125 inch and finished pocket depth shall be 6 inches. The finished pocket bag

shall measure 6.5 inches wide and shall extend down 9.25 inches from where it is sewn into the waistband. The button shall be 0.44 inch wide looping constructed of two plies of shell fabric and one ply of fusible interlining. The tab shall finish in a miter fold point with the ends under the top corded welt of the pocket and shall extend 1.25 inches in length. There shall be two straight horizontal bartacks set top and bottom on the tab to define the button opening. There shall be topstitched. All facings shall be clean finished inside the pocket bag. There shall be triangular bartacks set at each end of the pocket opening.

Billy Pockets: Billy pockets shall be inverted double-corded type. Finished pocket opening shall measure 3.375 inch and finished pocket depth shall be 8.5 inches. The finished pocket bag shall measure 5 inches wide and shall be caught at the top in the hip pocket assemble. The bottom of the pocket bag shall have an additional 3 inches folded toward the shell and topstitched. All facings shall be clean finished inside the pocket bag. There shall be triangular bartacks set at each end of the pocket opening.

Watch Pocket: The drop watch pocket shall be inverted double corded type and will be set 3 inches down from the bottom of the waistband. Finished pocket opening shall measure 3.375 inch and finished pocket depth shall be 3.5 inches. The finished pocket bag shall measure 5 inches wide and shall be caught at the top in the hip pocket assembly. The top and bottom pocket cord shall be top stitched. All facings shall be clean finished inside the pocket opening.

Wristband: The waistband shall finish 2 inches wide and shall be constructed of one ply of shell fabric cut along the filling direction for maximum stretch and the specified waistband material. The finished waistband in the trouser shall stretch at least 2 inches. The waistband will close with 2 sets of hook and eye fasteners set vertically.

Fly: The right side of the fly shall be lined with a crotch reinforcement extension construction of two piles of pocketing plus one ply of interlining and measuring 2 inches wide and extending down and clean finishing at the inseam. Inserted between the lining and the shell is a fly tab measuring 1.5 inches wide and extending at an upward angle so that the tab extends 1.75 inches along the top edge and 2.5 inches along the bottom edge. The tab shall finish in a point with a buttonhole and the tab shall be topstitched around the edges. The left inside edge of the fly shall be bound with the specified binding. The left fly shall be J-stitched 1.5 inch from the folded edge. The specified zipper shall be attached to the fly and the bottom of the fly opening shall be straight tacked.

Crotch Lining: Crotch shall be lined in the front quarters with 2 plies of the specified pocketing material bias cut with a folded edge.

Belt Loops: The belt loops shall be inserted into the waistband at the bottom, bell tacked to the trouser body 0.25 inches down and tacked to the top of the waistband. Loops shall be 1 inch wide, have a 2.25 inch opening, and be constructed of two plies of shell fabric and one ply of interlining butted on the reverse side and sewn with a looping machine. There shall be a minimum of seven belt loops per pair with larger sizes getting additional pairs as required.

Outlets: The seat outlet shall measure 1.5 inches on each side of the waistband tapering to 0.375 inches at the crotch. There shall be thigh outlets with the backside of the inseam measuring 1 inch at the crotch tapering to 0.375 inch at the knee.

Stitching: All seams shall be sewn at 10-12 stitches per inch. Stitching on waistband, out seam and inseam shall be single needle chain stitch. Stitching for seat seam shall be tandem needle chain stitch. Stitching for belt loops shall be double needle blind stitch. Over edge stitching for fronts and backs shall be 2 threads over edge stitch. All other seams shall be single needle lockstitch. Straight bartacks shall be 28 stitch count 0.375 inches long. Triangle bartacks shall be 124 stitch counts 0.375 on each side.

Button holes: Button holes shall be eyelet end, taper bar cut-after type.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, and fiber content and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and trousers shall be pressed completely and properly with the seat seam, inseam and outseam pressed open. There will be a plastic clip attached to the top of the fly of the finished trousers. Trousers shall be individually polybagged.

Packing: Trousers shall be packed 4 pair per box for each individual in boxes labeled with each individual's name on the end flap and box contents.

Optional Removable Windproof Breathable Liner: The trousers shall be designed to accommodate an optional removable windproof breathable liner which when installed shall provide additional winter weather protection. The liner shall be constructed from WindStopper windproof-breathable material laminated to a black brushed polyester tricot material with the brushed surface toward the body for comfort. There shall be a facing of 2-ply nylon taslan fabric with buttonholes set at the top hem of the liner and buttons set to the underside of the trouser waistband to fasten the liner to trouser. The liner shall be machine washable and dryable.

Measurements will be done for each person at the site. The tolerance of the measurements shall be ± 0.25 inch for 1/2 waist, 1/2 seat, 1/2 knee and 1/2 bottom measurements; ± 0.5 inch for outseams and inseams. Measurements rounded to the nearest 0.125 inch.

1. With zipper closed and the waistband hooked, measure along top edge of waistband from folded edge to folded edge.
2. With zipper closed measure across trousers three inches above crotch seam from folded edge to folded edge.
3. The location of the knee measurement shall be 14 inches down from crotch seam. Measure from folded edge to folded edge.
4. Measure along unhemmed bottom edge to the leg from folded edge to folded edge.
5. Measure along inseam from crotch seam to unhemmed bottom edge; for men's long rise add 2.5 inches.
6. Measure along outseam from bottom edge of waistband to unhemmed bottom edge of leg. Outseam measurements given are for regular rise; for men's long rise add 4 inches.
7. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.

8. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.

Other Requirements:

Standard Sample: In all details not specifically described herein, tailoring, styling, construction, materials, and the components shall conform to the standard sample.

Testing Bid-Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Warranty: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of one (1) year from date of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective. This warranty does not cover normal wear and tear, improper cleaning, and damage from chemicals, fire, misuse, accident or negligence. A complete copy of the manufacturer's warranty will be available upon request.

Sampling & Inspection: Trousers will be inspected at point of delivery.

Preparation for Delivery:

Packaging: Unless otherwise specified, commercial packages will be acceptable under this specification.

Marketing: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

Specification No. 4290-02 Shirts, Uniform Dress Summer

Special Requirements: Buttons to be supplied by vendor. RIC & CCRI Police will furnish shoulder emblems, which are to be sewed on by vendor. Individual measurements and alterations to be furnished by vendor. Patrol Officer shirt to have silver buttons.

Classification:

This specification covers Uniform Shirts as described herein.

Material: No. 333 Range by Hamburger, 55% Dacron Polyester/45% wool with mechanical 10-12% filling stretch.

Weight: 10.5-11.5 ounce Tropical weave

Color: Navy Blue

Applicable specification:

There are no other specifications applicable to this specification.

Requirements: Design and Construction

Short Sleeve shirt shall be a 5-crease military style with sport collar and permanent silicone adhesive creases. There shall be epaulets, pleated pockets with scalloped pocket flaps, badge eyelets with internal support strap, and self lined yoke and collar. Patterns shall provide for extra long shirt tails.

Sleeves: Short sleeve ends shall be clean finished with a 1 inch hem constructed after sleeve closing seam. Sleeve setting and closing shall be sewn with an overedge safety stitch.

Collar: The collar shall be a sport collar style. The collar shall measure 3 3/8 inches high in back when opened flat and shall be made of two plies of shell fabric plus one ply of the specified interlining. There shall be permanent collar stays sewn to the collar. The collar shall be topstitched around the edges and collar points shall be 3 1/8 inches long. The collar shall close with one button set to the top of the placket.

Epaulets: Epaulets shall be die cut from shell fabric, creased and interlined with the specified interlining. Epaulets shall be sewn into the sleeve head seam and shall measure 1 7/8 inches wide at the sleevehead and taper to 1 1/2 inches wide with the end finished in a point. Epaulets shall be set with the point approximately 1 inch from the collar seam. The epaulets shall be stitched to the shoulders with a row of stitching 2 1/2 inches from the sleeve head and sewn diagonally from each end of the seam to the sleeve. There shall be an unslit buttonhole at the pointed end of the epaulet with the specified button sewn on top. The epaulets shall then be topstitched along both edges of "v" forming the point to the shoulder of the shirt.

Pockets: There shall be two breast pockets with pleated patch pockets and scalloped pocket flaps. The patch pocket shall measure 5 1/2 inches wide and 5 3/4 inches long with mitered corners and a 1 1/2

inch box pleat stitched closed. The left pocket shall have a sewn pencil opening 1 1/4 inch wide. Hook tape 1/2 inch wide by 1 inch high shall be sewn to the upper corners of each pocket to secure the pocket flap. The scalloped pocket flap shall be die cut, creased and interlined with the specified interlining, then folded and topstitched. The top of the flap shall be set 3/4 inches above the top of the pocket and shall have one centered unslit buttonhole with a button. There shall be loop tape 1/2 inches wide by 1 inch high set on the under ply of the pocket to secure to the hook tape on the pocket. There shall be a pencil opening in the left flap 1 inch wide with the two rows of topstitching continuing across the pencil pocket opening.

Yoke: There shall be a two-ply back yoke lined on the inside with shell fabric. The yoke shall measure approximately 3 1/2 inches at the center and 3 inches at the sleeve head.

Fronts: The left front shall have a shell fabric top center placket measuring 1 1/1 inches wide and constructed with the specified interlining. The placket shall show two rows of stitching 1 inch wide. The button stand shall have an additional row of topstitching along the edge. There shall be six buttons and buttonholes set down the front and one button and buttonhole on the collar stand.

Stitching: All stitching shall be single needle at 10-12 stitches per inch except for sleeving and closing seams which shall be safety stitched.

Badge Attachment: There shall be an inside sling constructed of shell fabric 1 1/8 inches wide extending from the shoulder seam to the pocket on the left front. There shall be two unslit horizontal 1/2 inch buttonholes set vertically on the left front 1 3/8 inches center to center and with the bottom buttonhole set 1 1/4 inches above the top of the pocket flap.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, fiber content, and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and shirts shall be pressed completely prior to packaging.

Packaging: Shirts shall be folded, pinned, and individually polybagged with cardboard, collar stand, and butterfly clip. Shirts shall be packed 3 to a box which shall be clearly labeled on one end with style number, quantity, color, and size.

Sizes and Measurements: Each shirt shall be marked with lot number, size, and fiber content and shall have a care instruction label sewn in it.

Testing Pre-bid Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Stock Product: To insure availability of style and color for the purpose of maintaining departmental uniformity for future purchases bidders must provide evidence in the form of catalogs, price lists, or

similar written material that this item is currently available on an "as needed" basis. The pre-bid sample must be provided from current manufacturer's stock of the specified style. The successful bidder will be required to provide a full size run of try-on-garments within 10 days of agency approval, sizing of personnel, and for further evidence of in-stock availability.

Sampling and Inspection: Shirts will be inspected at point of delivery.

Packaging: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

Specifications, Trousers, Uniform Dress Summer

Agency: Rhode Island College Police (Main Campus) and CCRI police

Classification and Scope:

The specification covers Uniform Dress Trousers, of a worsted wool blend, machine washable and dry cleanable, to provide user comfort, uniform appearance durability, easy care and low maintenance cost. Custom tailored made.

Material: No 333 Range by Hamburger, 55% Dacron polyester/45% wool with a mechanical 10-12% filling stretch.

Construction: 75 ends per inch, 67 picks per inch

Breaking strength: Wrap: 195 lbs Filling: 170 lbs.

Fiber length: 3-3.5 inches

Weight: 10.5-11.5 ounce serge weave

Color: Navy Blue

Applicable Specifications: There are no other specifications applicable to this specification.

Requirements:

Design: The uniform trousers shall be tailored split-seam construction dress uniform style with two straight side pockets, two button-tab hip pockets, two Billy hip pockets, one drop watch pocket and a wide waistband with belt loops inserted into the bottom and tacked to the top. There shall be a stretch waistband with a silicone shirt-grip stripe, permanent silicone adhesive creases on both the front and back of the legs, front crotch panels and fly lining with button table. The patterning shall allow generous seat and thigh let out to accommodate alterations and athletic builds. The trousers shall be machine washable/dryable as well as dry cleanable. The waistband construction and trouser patterning shall accommodate an optional removable wind proof breathable liner.

Construction:

Front Pockets: Front pockets shall be on-seam style with straight pockets. Pockets shall be constructed on one piece of the specified pocketing material finishing approximately 6.5 inch wide at the bottom of the pocket opening and 12.5 inches long from where the pocket is sewn into the waistband. There shall be a facing of shell fabric material running from the side seam and waistband and into the pocket measuring 2 inches wide. There shall be a facing of shell fabric material on the inside of the pocket away from the body measuring 1.5 inches wide. There shall be a straight bartack across the top of the pocket opening 1 inch down from the waistband and a straight bartack across the bottom of the pocket opening. The pocket opening shall be a minimum of 6 inches.

Outlets: The seat outlet shall measure 1.5 inches on each side of the waistband tapering to 0.375 inches at the crotch. There shall be thigh outlets with the backside of the inseam measuring 1 inch at the crotch tapering to 0.375 inch at the knee.

Stitching: All seams shall be sewn at 10-12 stitches per inch. Stitching on waistband, out seam and inseam shall be single needle chain stitch. Stitching for seat seam shall be tandem needle chain stitch. Stitching for belt loops shall be double needle blind stitch. Over edge stitching for fronts and backs shall be 2 threads over edge stitch. All other seams shall be single needle lockstitch. Straight bartacks shall be 28 stitch count 0.375 inches long. Triangle bartacks shall be 124-stitch counts 0.375 on each side.

Button holes: Button holes shall be eyelet end, taper bar cut-after type.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, and fiber content and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and trousers shall be pressed completely and properly with the seat seam, inseam and outseam pressed open. There will be a plastic clip attached to the top of the fly of the finished trousers. Trousers shall be individually polybagged.

Packing: Trousers shall be packed 4 pair per box for each individual in boxes labeled with each individual's name on the end flap and box contents.

Measurements will be done for each person at the site. The tolerance of the measurements shall be +/-0.25 inch for 1/2 waist, 1/2 seat, 1/2 knee and 1/2 bottom measurements; +/-0.5 inch for outseams and inseams. Measurements rounded to the nearest 0.125 inch.

1. With zipper closed and the waistband hooked, measure along top edge of waistband from folded edge to folded edge.
2. With zipper closed measure across trousers three inches above crotch seam from folded edge to folded edge.
3. The location of the knee measurement shall be 14 inches down from crotch seam. Measure from folded edge to folded edge.
4. Measure along unhemmed bottom edge to the leg from folded edge to folded edge.
5. Measure along inseam from crotch seam to unhemmed bottom edge; for men's long rise add 2.5 inches.
6. Measure along outseam from bottom edge of waistband to unhemmed bottom edge of leg. Outseam measurements given are for regular rise; for men's long rise add 4 inches.
7. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.
8. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.

Other Requirements:

Standard Sample: In all details not specifically described herein, tailoring, styling, construction, materials, and the components shall conform to the standard sample.

Testing Bid-Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Warranty: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of one (1) year from date of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective. This warranty does not cover normal wear and tear, improper cleaning, and damage from chemicals, fire, misuse, accident or negligence. A complete copy of the manufacturer's warranty will be available upon request.

Sampling & Inspection: Trousers will be inspected at point of delivery.

Preparation for Delivery:

Packaging: Unless otherwise specified, commercial packages will be acceptable under this specification.

Marketing: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

BID 7594587

Specifications, Trousers, Uniform Dress Summer

Agency: Rhode Island College Police (Main Campus) and CCRI police

Classification and Scope: Uniform Dress Trousers

The specification covers Uniform Dress Trousers, of a worsted wool blend, machine washable and dry cleanable, to provide user comfort, uniform appearance durability, easy care and low maintenance cost. Custom tailored made.

Material: No 333 Range by Hamburger, 55% Dacron polyester/45% wool with a mechanical 10-12% filling stretch.

Construction: 75 ends per inch, 67 picks per inch

Breaking strength: Wrap: 195 lbs. Filling: 170 lbs.

Fiber length: 3-3.5 inches

Weight: 10.5-11.5 ounce serge weave

Color: Navy Blue

Applicable Specifications: There are no other specifications applicable to this specification.

Requirements:

Design: The uniform trousers shall be tailored split-seam construction dress uniform style with two straight side pockets, two button-tab hip pockets, two Billy hip pockets, one drop watch pocket and a wide waistband with belt loops inserted into the bottom and tacked to the top. There shall be a stretch waistband with a silicone shirt-grip stripe, permanent silicone adhesive creases on both the front and back of the legs, front crotch panels and fly lining with button table. The patterning shall allow generous seat and thigh let out to accommodate alterations and athletic builds. The trousers shall be machine washable/dryable as well as dry cleanable. The waistband construction and trouser patterning shall accommodate an optional removable wind proof breathable liner.

Construction:

Front Pockets: Front pockets shall be on-seam style with straight pockets. Pockets shall be constructed on one piece of the specified pocketing material finishing approximately 6.5 inch wide at the bottom of the pocket opening and 12.5 inches long from where the pocket is sewn into the waistband. There shall be a facing of shell fabric material running from the side seam and waistband and into the pocket measuring 2 inches wide. There shall be a facing of shell fabric material on the inside of the pocket away from the body measuring 1.5 inches wide. There shall be a straight bartack across the top of the pocket opening 1 inch down from the waistband and a straight bartack across the bottom of the pocket opening. The pocket opening shall be a minimum of 6 inches.

Hip Pockets: Hip pockets shall be inverted double corded type with button tabs. Finished pocket opening shall measure 5.125 inch and finished pocket depth shall be 6 inches. The finished pocket bag

shall measure 6.5 inches wide and shall extend down 9.25 inches from where it is sewn into the waistband. The button shall be 0.44 inch wide looping constructed of two plies of shell fabric and one ply of fusible interlining. The tab shall finish in a miter fold point with the ends under the top corded welt of the pocket and shall extend 1.25 inches in length. There shall be two straight horizontal bartacks set top and bottom on the tab to define the button opening. There shall be topstitched. All facings shall be clean finished inside the pocket bag. There shall be triangular bartacks set at each end of the pocket opening.

Billy Pockets: Billy pockets shall be inverted double-corded type. Finished pocket opening shall measure 3.375 inch and finished pocket depth shall be 8.5 inches. The finished pocket bag shall measure 5 inches wide and shall be caught at the top in the hip pocket assemble. The bottom of the pocket bag shall have an additional 3 inches folded toward the shell and topstitched. All facings shall be clean finished inside the pocket bag. There shall be triangular bartacks set at each end of the pocket opening.

Watch Pocket: The drop watch pocket shall be inverted double corded type and will be set 3 inches down from the bottom of the waistband. Finished pocket opening shall measure 3.375 inch and finished pocket depth shall be 3.5 inches. The finished pocket bag shall measure 5 inches wide and shall be caught at the top in the hip pocket assembly. The top and bottom pocket cord shall be top stitched. All facings shall be clean finished inside the pocket opening.

Waistband: The waistband shall finish 2 inches wide and shall be constructed of one ply of shell fabric cut along the filling direction for maximum stretch and the specified waistband material. The finished waistband in the trouser shall stretch at least 2 inches. The waistband will close with 2 sets of hook and eye fasteners set vertically.

Fly: The right side of the fly shall be lined with a crotch reinforcement extension construction of two piles of pocketing plus one ply of interlining and measuring 2 inches wide and extending down and clean finishing at the inseam. Inserted between the lining and the shell is a fly tab measuring 1.5 inches wide and extending at an upward angle so that the tab extends 1.75 inches along the top edge and 2.5 inches along the bottom edge. The tab shall finish in a point with a buttonhole and the tab shall be topstitched around the edges. The left inside edge of the fly shall be bound with the specified binding. The left fly shall be J-stitched 1.5 inch from the folded edge. The specified zipper shall be attached to the fly and the bottom of the fly opening shall be straight tacked.

Crotch Lining: Crotch shall be lined the front quarters with 2 plies of the specified pocketing material bias cut with a folded edge.

Belt Loops: The belt loops shall be inserted into the waistband at the bottom, bell tacked to the trouser body 0.25 inches down and tacked to the top of the waistband. Loops shall be 1 inch wide, have a 2.25 inch opening, and be constructed of two plies of shell fabric and one ply of interlining butted on the reverse side and sewn with a looping machine. There shall be a minimum of seven belt loops per pair with larger sizes getting additional pairs as required.

Outlets: The seat outlet shall measure 1.5 inches on each side of the waistband tapering to 0.375 inches at the crotch. There shall be thigh outlets with the backside of the inseam measuring 1 inch at the crotch tapering to 0.375 inch at the knee.

BID 7594587

Stitching: All seams shall be sewn at 10-12 stitches per inch. Stitching on waistband, out seam and inseam shall be single needle chain stitch. Stitching for seat seam shall be tandem needle chain stitch. Stitching for belt loops shall be double needle blind stitch. Over edge stitching for fronts and backs shall be 2 threads over edge stitch. All other seams shall be single needle lockstitch. Straight bartacks shall be 28 stitch count 0.375 inches long. Triangle bartacks shall be 124-stitch counts 0.375 on each side.

Button holes: Button holes shall be eyelet end, taper bar cut-after type.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, and fiber content and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and trousers shall be pressed completely and properly with the seat seam, inseam and outseam pressed open. There will be a plastic clip attached to the top of the fly of the finished trousers. Trousers shall be individually polybagged.

Packing: Trousers shall be packed 4 pair per box for each individual in boxes labeled with each individual's name on the end flap and box contents.

Measurements will be done for each person at the site. The tolerance of the measurements shall be +/- .25 inch for 1/2 waist, 1/2 seat, 1/2 knee and 1/2 bottom measurements; +/- 0.5 inch for outseams and inseams. Measurements rounded to the nearest 0.125 inch.

1. With zipper closed and the waistband hooked, measure along top edge of waistband from folded edge to folded edge.
2. With zipper closed measure across trousers three inches above crotch seam from folded edge to folded edge.
3. The location of the knee measurement shall be 14 inches down from crotch seam. Measure from folded edge to folded edge.
4. Measure along unhemmed bottom edge to the leg from folded edge to folded edge.
5. Measure along inseam from crotch seam to unhemmed bottom edge; for men's long rise add 2.5 inches.
6. Measure along outseam from bottom edge of waistband to unhemmed bottom edge of leg. Outseam measurements given are for regular rise; for men's long rise add 4 inches.
7. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.
8. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.

Other Requirements:

Standard Sample: In all details not specifically described herein, tailoring, styling, construction, materials, and the components shall conform to the standard sample.

Testing Bid-Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Warranty: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of one (1) year from date of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective. This warranty does not cover normal wear and tear, improper cleaning, and damage from chemicals, fire, misuse, accident or negligence. A complete copy of the manufacturer's warranty will be available upon request.

Sampling & Inspection: Trousers will be inspected at point of delivery.

Preparation for Delivery:

Packaging: Unless otherwise specified, commercial packages will be acceptable under this specification.

Marketing: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

Specification No. 4290-02 Shirts, Uniform Dress Summer

Special Requirements: Buttons to be supplied by vendor. RIC & CCRI Police will furnish shoulder emblems, which are to be sewed on by vendor. Individual measurements and alterations to be furnished by vendor. Patrol Officer shirt to have silver buttons.

Classification:

This specification covers Uniform Shirts as described herein.

Material: No. 333 Range by Hamburger, 55% Dacron Polyester/45% wool with mechanical 10-12% filling stretch.

Weight: 10.5-11.5 ounce Tropical weave

Color: Navy Blue

Applicable specification:

There are no other specifications applicable to this specification.

Requirements: Design and Construction

Short Sleeve shirt shall be a 5-crease military style with sport collar and permanent silicone adhesive creases. There shall be epaulets, pleated pockets with scalloped pocket flaps, badge eyelets with internal support strap, and self-lined yoke and collar. Patterns shall provide for extra-long shirt tails.

Sleeves: Short sleeve ends shall be clean finished with a 1 inch hem constructed after sleeve closing seam. Sleeve setting and closing shall be sewn with an overedge safety stitch.

Collar: The collar shall be a sport collar style. The collar shall measure 3 3/8 inches high in back when opened flat and shall be made of two plies of shell fabric plus one ply of the specified interlining. There shall be permanent collar stays sewn to the collar. The collar shall be topstitched around the edges and collar points shall be 3 1/8 inches long. The collar shall close with one button set to the top of the placket.

Epaulets: Epaulets shall be die cut from shell fabric, creased and interlined with the specified interlining. Epaulets shall be sewn into the sleeve head seam and shall measure 1 7/8 inches wide at the sleeve-head and taper to 1 1/2 inches wide with the end finished in a point. Epaulets shall be set with the point approximately 1 inch from the collar seam. The epaulets shall be stitched to the shoulders with a row of stitching 2 1/2 inches from the sleeve head and sewn diagonally from each end of the seam to the sleeve. There shall be an un-slit buttonhole at the pointed end of the epaulet with the specified button sewn on top. The epaulets shall then be topstitched along both edges of "v" forming the point to the shoulder of the shirt.

Pockets: There shall be two breast pockets with pleated patch pockets and scalloped pocket flaps. The patch pocket shall measure 5 1/2 inches wide and 5 3/4 inches long with mitered corners and a 1 1/2 inch box pleat stitched closed. The left pocket shall have a sewn pencil opening 1 1/4 inch wide. Hook tape 1/2 inch wide by 1 inch high shall be sewn to the upper corners of each pocket to secure the pocket flap. The scalloped pocket flap shall be die cut, creased and interlined with the specified interlining, then

folded and topstitched. The top of the flap shall be set 3/4 inches above the top of the pocket and shall have one centered un-slit buttonhole with a button. There shall be loop tape 1/2 inches wide by 1 inch high set on the under ply of the pocket to secure to the hook tape on the picket. There shall be a pencil opening in the left flap 1 inch wide with the two rows of top stitching continuing across the pencil pocket opening.

Yoke: There shall be a two-ply back yoke lined on the inside with shell fabric. The yoke shall measure approximately 3 1/2 inches at the center and 3 inches at the sleeve head.

Fronts: The left front shall have a shell fabric top center placket measuring 1 1/1 inches wide and constructed with the specified interlining. The placket shall show two rows of stitching 1 inch wide. The button stand shall have an additional row of topstitching along the edge. There shall be six buttons and buttonholes set down the front and one button and buttonhole on the collar stand.

Stitching: All stitching shall be single needle at 10-12 stitches per inch except for sleeving and closing seams which shall be safety stitched.

Badge Attachment: There shall be an inside sling constructed of shell fabric 1 1/8 inches wide extending from the shoulder seam to the pocket on the left front. There shall be two unslit horizontal 1/2 inch buttonholes set vertically on the left front 1 3/8 inches center to center and with the bottom buttonhole set 1 1/4 inches above the top of the pocket flap.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, fiber content, and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and shirts shall be pressed completely prior to packaging.

Packaging: Shirts shall be folded, pinned, and individually polybagged with cardboard, collar stand, and butterfly clip. Shirts shall be packed 3 to a box which shall be clearly labeled on one end with style number, quantity, color, and size.

Sizes and Measurements: Each shirt shall be marked with lot number, size, and fiber content and shall have a care instruction label sewn in it.

Testing Pre-bid Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Stock Product: To insure availability of style and color for the purpose of maintaining departmental uniformity for future purchases bidders must provide evidence in the form of catalogs, price lists, or similar written material that this item is currently available on an "as needed" basis. The pre-bid sample must be provided from current manufacturer's stock of the specified style. The successful bidder will be

BID 7594587

required to provide a full size run of try-on-garments within 10 days of agency approval, sizing of personnel, and for further evidence of in-stock availability.

Sampling and Inspection: Shirts will be inspected at point of delivery.

Packaging: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

BID 7594587

Specification No. 4290-03 Trousers, Uniform, Dress Winter

Agency: Rhode Island College Police (Main Campus) and CCRI Police

Classification and Scope: Uniform Dress Trousers

The specification covers Uniform Dress Trousers, of a worsted wool blend, machine washable and dry cleanable, to provide user comfort, uniform appearance durability, easy care and low maintenance cost. Custom tailored made.

Material: No 333 Range by Hamburg 55% Dacron polyester/45% wool with a mechanical 10-12% filling stretch.

Construction: 75 ends per inch, 67 picks per inch

Breaking strength: Wrap: 195 lbs. Filling: 170 lbs.

Fiber length: 3-3.5 inches

Weight: 14 ounce serge weave P & F

Color: Navy Blue

Applicable Specifications: There are no other specifications applicable to this specification.

Requirements:

Design: The uniform trousers shall be tailored split-seam construction dress uniform style with two straight side pockets, two button-tab hip pockets, two Billy hip pockets, one drop watch pocket and a wide waistband with belt loops inserted into the bottom and tacked to the top. There shall be a stretch waistband with a silicone shirt-grip stripe, permanent silicone adhesive creases on both the front and back of the legs, front crotch panels and fly lining with button table. The patterning shall allow generous seat and thigh let out to accommodate alterations and athletic builds. The trousers shall be machine washable/dryable as well as dry cleanable. The waistband construction and trouser patterning shall accommodate an optional removable wind proof breathable liner.

Construction:

Front Pockets: Front pockets shall be on-seam style with straight pockets. Pockets shall be constructed on one piece of the specified pocketing material finishing approximately 6.5 inch wide at the bottom of the pocket opening and 12.5 inches long from where the pocket is sewn into the waistband. There shall be a facing of shell fabric material running from the side seam and waistband and into the pocket measuring 2 inches wide. There shall be a facing of shell fabric material on the inside of the pocket away from the body measuring 1.5 inches wide. There shall be a straight bartack across the top of the pocket opening 1 inch down from the waistband and a straight bartack across the bottom of the pocket opening. The pocket opening shall be a minimum of 6 inches.

Hip Pockets: Hip pockets shall be inverted double corded type with button tabs. Finished pocket opening shall measure 5.125 inch and finished pocket depth shall be 6 inches. The finished pocket bag

shall measure 6.5 inches wide and shall extend down 9.25 inches from where it is sewn into the waistband. The button shall be 0.44 inch wide looping constructed of two plies of shell fabric and one ply of fusible interlining. The tab shall finish in a miter fold point with the ends under the top corded welt of the pocket and shall extend 1.25 inches in length. There shall be two straight horizontal bartacks set top and bottom on the tab to define the button opening. There shall be topstitched. All facings shall be clean finished inside the pocket bag. There shall be triangular bartacks set at each end of the pocket opening.

Billy Pockets: Billy pockets shall be inverted double-corded type. Finished pocket opening shall measure 3.375 inch and finished pocket depth shall be 8.5 inches. The finished pocket bag shall measure 5 inches wide and shall be caught at the top in the hip pocket assemble. The bottom of the pocket bag shall have an additional 3 inches folded toward the shell and topstitched. All facings shall be clean finished inside the pocket bag. There shall be triangular bartacks set at each end of the pocket opening.

Watch Pocket: The drop watch pocket shall be inverted double corded type and will be set 3 inches down from the bottom of the waistband. Finished pocket opening shall measure 3.375 inch and finished pocket depth shall be 3.5 inches. The finished pocket bag shall measure 5 inches wide and shall be caught at the top in the hip pocket assembly. The top and bottom pocket cord shall be top stitched. All facings shall be clean finished inside the pocket opening.

Wristband: The waistband shall finish 2 inches wide and shall be constructed of one ply of shell fabric cut along the filling direction for maximum stretch and the specified waistband material. The finished waistband in the trouser shall stretch at least 2 inches. The waistband will close with 2 sets of hook and eye fasteners set vertically.

Fly: The right side of the fly shall be lined with a crotch reinforcement extension construction of two piles of pocketing plus one ply of interlining and measuring 2 inches wide and extending down and clean finishing at the inseam. Inserted between the lining and the shell is a fly tab measuring 1.5 inches wide and extending at an upward angle so that the tab extends 1.75 inches along the top edge and 2.5 inches along the bottom edge. The tab shall finish in a point with a buttonhole and the tab shall be topstitched around the edges. The left inside edge of the fly shall be bound with the specified binding. The left fly shall be J-stitched 1.5 inch from the folded edge. The specified zipper shall be attached to the fly and the bottom of the fly opening shall be straight tacked.

Crotch Lining: Crotch shall be lined in the front quarters with 2 plies of the specified pocketing material bias cut with a folded edge.

Belt Loops: The belt loops shall be inserted into the waistband at the bottom, bell tacked to the trouser body 0.25 inches down and tacked to the top of the waistband. Loops shall be 1 inch wide, have a 2.25 inch opening, and be constructed of two plies of shell fabric and one ply of interlining butted on the reverse side and sewn with a looping machine. There shall be a minimum of seven belt loops per pair with larger sizes getting additional pairs as required.

Outlets: The seat outlet shall measure 1.5 inches on each side of the waistband tapering to 0.375 inches at the crotch. There shall be thigh outlets with the backside of the inseam measuring 1 inch at the crotch tapering to 0.375 inch at the knee.

Stitching: All seams shall be sewn at 10-12 stitches per inch. Stitching on waistband, out seam and inseam shall be single needle chain stitch. Stitching for seat seam shall be tandem needle chain stitch. Stitching for belt loops shall be double needle blind stitch. Over edge stitching for fronts and backs shall be 2 threads over edge stitch. All other seams shall be single needle lockstitch. Straight bartacks shall be 28 stitch count 0.375 inches long. Triangle bartacks shall be 124 stitch counts 0.375 on each side.

Button holes: Button holes shall be eyelet end, taper bar cut-after type.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, and fiber content and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and trousers shall be pressed completely and properly with the seat seam, inseam and outseam pressed open. There will be a plastic clip attached to the top of the fly of the finished trousers. Trousers shall be individually polybagged.

Packing: Trousers shall be packed 4 pair per box for each individual in boxes labeled with each individual's name on the end flap and box contents.

Optional Removable Windproof Breathable Liner: The trousers shall be designed to accommodate an optional removable windproof breathable liner which when installed shall provide additional winter weather protection. The liner shall be constructed from Wind-Stopper windproof-breathable material laminated to a black brushed polyester tricot material with the brushed surface toward the body for comfort. There shall be a facing of 2-ply nylon taslan fabric with buttonholes set at the top hem of the liner and buttons set to the underside of the trouser waistband to fasten the liner to trouser. The liner shall be machine washable and dryable.

Measurements will be done for each person at the site. The tolerance of the measurements shall be +/- .25 inch for 1/2 waist, 1/2 seat, 1/2 knee and 1/2 bottom measurements; +/- 0.5 inch for out-seams and inseams. Measurements rounded to the nearest 0.125 inch.

1. With zipper closed and the waistband hooked, measure along top edge of waistband from folded edge to folded edge.
2. With zipper closed measure across trousers three inches above crotch seam from folded edge to folded edge.
3. The location of the knee measurement shall be 14 inches down from crotch seam. Measure from folded edge to folded edge.
4. Measure along unhemmed bottom edge to the leg from folded edge to folded edge.
5. Measure along inseam from crotch seam to unhemmed bottom edge; for men's long rise add 2.5 inches.
6. Measure along out-seam from bottom edge of waistband to unhemmed bottom edge of leg. Out-seam measurements given are for regular rise; for men's long rise add 4 inches.
7. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.

8. Measure from crotch seam along the seat seam to bottom edge of waistband; for men's long rise add 1.5 inches.

Other Requirements:

Standard Sample: In all details not specifically described herein, tailoring, styling, construction, materials, and the components shall conform to the standard sample.

Testing Bid-Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

Warranty: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of one (1) year from date of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective. This warranty does not cover normal wear and tear, improper cleaning, and damage from chemicals, fire, misuse, accident or negligence. A complete copy of the manufacturer's warranty will be available upon request.

Sampling & Inspection: Trousers will be inspected at point of delivery.

Preparation for Delivery:

Packaging: Unless otherwise specified, commercial packages will be acceptable under this specification.

Marketing: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

Specification No. 4290-04 Shirts, Uniform Dress Winter

Agency: Rhode Island College Police Department: (Main Campus) and CCRI Police

Classification and Scope:

The specification covers Uniform Shirts as described herein. Custom tailored fitted to individual.

Material: 55% Dacron polyester/45% Worsted wool #651 Range by Hamburger.

10-12% mechanical filling stretch

Weight: 14 oz. per linear yard plain weave 2 ply.

Color: Navy Blue

Applicable Specification: There are no other specifications applicable to this specification.

Requirements:

Design: Long sleeves shirt shall be 5 crease military style with banded dress collar and permanent silicone adhesive creases. There shall be epaulets, pleated pockets with scalloped pocket flaps, badge eyelets with internal support strap, 2-button adjustable cuffs and self-lined yoke. Patterns shall provide for extra-long shirt tails.

Sleeves: Sleeve ends shall have plackets finishing 1 1/4 inches wide on the top placket and 1/2 inch wide under placket and shall have a single pleat where attached to the cuffs. Cuffs shall finish 2 1/2 inches wide, shall be constructed of two plies of shell fabric plus one ply of the specified interlining, and shall be topstitched 1/4 inch on the edges. The cuff shall be 2-button adjustable with buttons set side 3/4 inches apart on center. Sleeve setting and closing shall be sewn with an over edge safety stitch.

Special Requirements: Sleeves to have one (1) inch band of Red Serge Material at a position designated by agency. Buttons to be supplied by vendor. RIC & CCRI Police and Security will furnish shoulder emblems which are to be sewed on by vendor. Individual measurements and alternations to be furnished by vendor.

Collar: The collar shall be banded dress style. Collar shall be die cut with the collar stand measuring 1 1/2 inches high in back. Both the collar and collar stand shall be made of two plies of shell fabric plus one ply of the specified interlining. There shall be permanent collar stays sewn to the interlining so that no stitches are visible through the under collar. The collar shall be topstitched around the edges and collar points shall be 3 1/8 inches long. The collar stand shall close with one button.

Epaulets: Epaulets shall be die cut from shell fabric creased and interlined with the specified interlining, and then folded and topstitched. Epaulets shall be sewn into the sleeve head seam and shall measure 1 7/8 inches wide at the sleeve head and taper to 1 1/2 inches wide with the end finishing in a point. Epaulets shall be stitched to the shoulders with a row of stitch 2 1/2 inches from the sleeve head and sewn diagonally from each end of the seam to the sleeve. There shall be an un-slit buttonhole at the pointed end of the epaulet with the specified button sewn on top. The epaulets shall then be topstitched along both edges of "V" forming the point to the shoulder of the shirt.

Pockets: There shall be two breast pockets with pleated patch pockets and scalloped pocket flaps. The patch pocket shall measure 5 1/2 inches wide and 5 3/4 inches long with mitered corners and a 1 1/2 inch box pleat stitched closed. The left pocket shall have a sewn pencil opening 1 1/4 inch wide. Hook tape 1/2 inch wide by 1 inch high shall be sewn to the upper corners of each pocket to secure the pocket flap. The scalloped pocket flap shall be die cut, creased and interlined with the specified interlining, then folded and topstitched. The top of the flap shall be set 3/4 inches above the top of the pocket and shall have one centered un-slit buttonhole with a button. There shall be loop tape 1/2 inches wide by 1 inch high set on the under ply of the pocket to secure to the hook tape on the pocket. There shall be a pencil opening in the left flap 1 inch wide with the two rows of topstitching continuing across the pencil pocket opening.

Yoke: There shall be a two-ply back yoke lined on the inside with shell fabric. The yoke shall measure approximately 3 1/2 inches at the center and 3 inches at the sleeve head.

Fronts: The left front shall have a shell fabric top center placket measuring 1 1/1 inches wide and constructed with the specified interlining. The placket shall show two rows of stitching 1 inch wide. The button stand shall have an additional row of topstitching along the edge. There shall be six buttons and buttonholes set down the front and one button and buttonhole on the collar stand.

Stitching: All stitching shall be single needle at 10-12 stitches per inch except for sleeving and closing seams which shall be safety stitched.

Badge Attachment: There shall be an inside sling constructed of shell fabric 1 1/8 inches wide extending front the shoulder seam to the pocket on the left front. There shall be two unslit horizontal 1/2 inch buttonholes set vertically on the left front 1 3/8 inches center to center and with the bottom buttonhole set 1 1/4 inches above the top of the pocket flap.

Labeling: The garment shall be permanently labeled with the manufacturer, country of origin, size, fiber content, and care instructions.

Pressing and Finishing: Loose threads shall be trimmed and shirts shall be pressed completely prior to packaging.

Packaging: Shirts shall be folded, pinned, and individually polybagged with cardboard, collar stand, and butterfly clip. Shirts shall be packed 3 to a box which shall be clearly labeled on one end with style number, quantity, color, and size.

Sizes and Measurements: Each shirt shall be marked with lot number, size, and fiber content and shall have a care instruction label sewn in it.

Testing Pre-bid Sample: Samples submitted by bidders will be compared for tailoring, styling, construction, materials and components with the standard sample on file with the department. Nonconformity of the sample to the specification will be cause for rejection. Any sample by a bidder may be subjected to such test or tests by any Testing Laboratory as the Contracting Officer may select. All costs in connection with any such tests shall be paid for by the bidder.

Country of Origin: The garment must be manufactured entirely in the United States of America from fabrics and materials manufactured entirely in the United States of America.

BID 7594587

Stock Product: To insure availability of style and color for the purpose of maintaining departmental uniformity for future purchases bidders must provide evidence in the form of catalogs, price lists, or similar written material that this item is currently available on an "as needed" basis. The pre-bid sample must be provided from current manufacturer's stock of the specified style. The successful bidder will be required to provide a full size run of try-on-garments within 10 days of agency approval, sizing of personnel, and for further evidence of in-stock availability.

Sampling and Inspection: Shirts will be inspected at point of delivery.

Packaging: Unless otherwise specified, all packages must be marked on the side with the name of the commodity, size, color and count.

Contract Terms and Conditions

Table of Contents

Terms and Conditions.....II

 BID STANDARD TERMS AND CONDITIONSII

 TERMS AND CONDITIONS FOR THIS BIDII

 DELIVERY PER AGENCYII

 MULTI YEAR AWARDII

 READING VENDOR NAMES ONLYII

 AWARDII

 CLOTHING SAMPLESII

 RIVIP INFO - BID SUBMISSION REQUIREMENTSII

 PURCHASE AGREEMENT BIDIII

Terms and Conditions

BID STANDARD TERMS AND CONDITIONS

TERMS AND CONDITIONS FOR THIS BID

DELIVERY PER AGENCY

DELIVERY OF GOODS OR SERVICES AS REQUESTED BY AGENCY.

MULTI YEAR AWARD

THIS IS A MULTI-YEAR BID/CONTRACT. PER RHODE ISLAND STATE LAW 37-2-33, CONTRACT OBLIGATIONS BEYOND THE CURRENT FISCAL YEAR ARE SUBJECT TO AVAILABILITY OF FUNDS. CONTINUATION OF THE CONTRACT BEYOND THE INITIAL FISCAL YEAR WILL BE AT THE DISCRETION OF THE STATE. TERMINATION MAY BE EFFECTED BY THE STATE BASED UPON DETERMINING FACTORS SUCH AS UNSATISFACTORY PERFORMANCE OR THE DETERMINATION BY THE STATE TO DISCONTINUE THE GOODS/SERVICES, OR TO REVISE THE SCOPE AND NEED FOR THE TYPE OF GOODS/SERVICES; ALSO MANAGEMENT OWNER DETERMINATIONS THAT MAY PRECLUDE THE NEED FOR GOODS/SERVICES.

READING VENDOR NAMES ONLY

DUE TO LENGTH OF BID AND TIME CONSTRAINTS, THE STATE WILL ONLY ACKNOWLEDGE RECEIPT AND READ THE NAMES OF VENDORS SUBMITTING PROPOSALS. NO EXAMINATION OF DOCUMENTS OR PRESENTATION OF INFORMATION CONTAINED IN PROPOSALS WILL BE MADE AVAILABLE AT THE BID OPENING; HOWEVER, INSTRUCTIONS TO OBTAIN THE TABULATION OR SUMMARY OF BID RESPONSES WILL BE MADE AVAILABLE AT THE RI DIVISION OF PURCHASES WEBSITE AT WWW.PURCHASING.RI.GOV

AWARD

THE STATE, AT ITS SOLE DISCRETION, SHALL RESERVE THE RIGHT TO MAKE ONE OR MULTIPLE AWARDS FOR THIS REQUIREMENT AND/OR TO REJECT ANY OR ALL BIDS.

CLOTHING SAMPLES

IF SAMPLES ARE REQUESTED, THEY MUST BE PROVIDED WITHIN TEN (10) WORKING DAYS OF REQUEST DATE. FAILURE TO DO SO MAY RESULT IN DISQUALIFICATION OF BID.

RIVIP INFO - BID SUBMISSION REQUIREMENTS

It is the vendor's responsibility to check and download any and all addenda from the RIVIP. This offer may not be considered unless a signed RIVIP generated Bidder Certification Cover Form is attached and the Unit Price column is completed. The signed Certification Cover Form should be attached to the front of the offer. Each bid proposal must be submitted in a separate sealed envelope with the bidder's name and address and the specific "Solicitation Number," "Solicitation Title," and the "Bid Proposal Submission Deadline" marked in the upper left-hand corner of the envelope.

The bid proposal must be delivered (via mail, messenger service, or personal delivery) to the Division of Purchases and date-stamped/receipted by the date and time specified for the bid proposal submission deadline. Bidders should mail bid proposals sufficiently in advance of the bid proposal

submission deadline to ensure timely delivery to the Division of Purchases or, when delivering a bid proposal in person or by messenger, should allow additional time for parking and clearance through security checkpoints. Bid proposals must be addressed to:

Rhode Island Department of Administration
Division of Purchases, 2nd Floor
One Capitol Hill, Providence, RI 02908-5855

Bid proposals that are not received by the Division of Purchases by the bid proposal submission deadline for whatever reason will be deemed late and will not be considered. The submission time will be determined by the time clock in the Division of Purchases. Postmarks will not be considered proof of timely submission.

Bid proposals in electronic format are not accepted at this time.

At the bid proposal submission deadline, bid proposals will be opened and read aloud in public.

DIVESTITURE OF INVESTMENTS IN IRAN REQUIREMENT:

No vendor engaged in investment activities in Iran as described in R.I. Gen. Laws §37-2.5-2(b) may submit a bid proposal to, or renew a contract with, the Division of Purchases. Each vendor submitting a bid proposal or entering into a renewal of a contract is required to certify that the vendor does not appear on the list maintained by the General Treasurer pursuant to R.I. Gen. Laws §37-2.5-3.

PURCHASE AGREEMENT BID

BIDDING (a) A single price shall be quoted for each item against which a proposal is submitted. This price will be the maximum in effect during the agreement period. Any price decline at the manufacturer's level shall be reflected in a reduction of the agreement price to the State. (b) Quantities, if any, are estimated only. The agreement shall cover the actual quantities ordering during the period. Deliveries will be billed at the single, firm, awarded unit price quoted regardless of the quantities ordered. (c) Bid price is net F.O.B. destination and shall include inside delivery at no extra cost. (d) Bids for single items and/or a small percentage of total items listed, may, at the State's sole option, be rejected as being non-responsive to the intent of this request. **ORDERING** (a) The User Agency(s) will submit individual orders for the various items and various quantities as may be required during the agreement period. (b) Exception - Regardless of any agreement resulting from this bid, the State reserves the right to solicit prices separately for any extra large requirements for delivery to specific destinations.

Mailing Address for Bid Proposals issued by the State of Rhode Island, Division of Purchases:

All Bid Proposals must be submitted to the following address:

State of Rhode Island
Department of Administration
Division of Purchases, 2nd Floor
One Capitol Hill
Providence, RI 02908